



# PRODUCT DATA SHEET

## Universal Flattening Agent

L7550

DESCRIPTION	CHARACTERISTICS	SPECIFICATIONS
<p>L7550 is a pre-dispersed flattening paste designed to be used as a post addition product for the purpose of gloss reduction. This product is for use in Solvent based coatings only.</p> <p><b>Product Advantages:</b></p> <ul style="list-style-type: none"> <li>➤ Ready To Use</li> <li>➤ Efficient Gloss Reduction</li> <li>➤ Ease of Incorporation</li> <li>➤ Improved Clarity</li> <li>➤ Improved Color</li> <li>➤ Improved Stability</li> </ul>	<p><b>Weight Solids:</b> 14%</p> <p><b>Volume Solids:</b> 7.54%</p> <p><b>Weight/Gallon:</b> 7.65 lbs/gal</p> <p><b>VOC (Reg/coating):</b> 6.58 lb/gal or 789 g/l</p> <p><b>VOC (Act./material):</b> 6.58 lb/gal or 789 g/l</p> <p><b>HAPs:</b> 3.84</p> <p><b>Shelf Life:</b> 12 months if unopened and stored in a cool dry area. Always rotate stock.</p> <p><i>Note: These numbers represent actual control values on a smooth, sanded substrate. Spray techniques, texture, and sealing as well as film thickness may give different results on actual work, but they may be used for comparison. To the best of our knowledge, the above technical data is true and accurate at the date of issuance but is subject to change without prior notice.</i></p>	<p><b>Material Preparation:</b> This product must be mixed well prior to each use. We recommend the use of a variable speed mixer or paint shaker to accomplish this. In addition, L7550 should be incorporated into the solvent based coating while the coating is under moderate agitation. Again, we recommend a variable speed mixer or paint shaker to accomplish this. Mix the coating until the flattening paste is thoroughly dispersed. Keep the flattening agent container sealed when not in use.</p> <p><b>Application:</b> The amount of flattening agent required to achieve a specific gloss will vary with each product and is dependent upon such variables as product type, solids content and final film build of the complete coating system. We recommend that a test panel be prepared to verify gloss prior to application on the job site. Lacquer products require a minimum of one hour to achieve final gloss, under optimum drying conditions. Conversion Coatings require 24 hours.</p> <p><b>Clean Up:</b> Use #500 Lacquer Thinner to clean all equipment. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.</p>

The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. **HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.

**CAUTION: DANGER! FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN!** BEFORE using this product it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact the manufacturer.

Date: Feb. 2012