

Safety Data Sheet

Hardener

Safety Data Sheet dated 11/30/2017, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name:

Hardener

Other means of identification:

Trade code:

6CTH43

Recommended use of the chemical and restrictions on use

Recommended use: Surface coating

Restrictions on use:

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

Sirca S.p.A.

Address:

Viale Roma, 85

35010 S.Dono di Massanzago (PD) - ITALY

Tel. +39 0499322311

Distributed by:

GEMINI INDUSTRIES, INC.

2300 Holloway Drive

El Reno, OK 73036

USA

Tel. 1-800-262-5710

Fax 1-405-262-9310

www.gemini-coatings.com

Competent person responsible for the safety data sheet:

safety@sirca.it

Emergency phone number

For Hazardous Materials [or Dangerous Goods] Incident

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

1-800-424-9300 / +1 703-527-3887.

2. HAZARD(S) IDENTIFICATION

Classification of the chemical



Danger, Flam. Liq. 2, Highly flammable liquid and vapour.



Warning, Eye Irrit. 2A, Causes serious eye irritation.



Danger, Resp. Sens. 1, May cause allergy or asthma symptoms or breathing difficulties if inhaled.



Warning, Skin Sens. 1, May cause an allergic skin reaction.



Warning, Carc. 2, Suspected of causing cancer.



Warning, STOT SE 3, May cause respiratory irritation.



Warning, STOT SE 3, May cause drowsiness or dizziness.

Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

Safety Data Sheet

Hardener

Precautionary statements:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash your face, hands and every exposed part thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P284 [In case of inadequate ventilation] wear respiratory protection.
P302+P352 IF ON SKIN: Wash with plenty of water and soap.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER/doctor/... if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor/...
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire: Use a CO2, Foam, Chemical powders for extinction.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



HMIS rating:

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		1
PERSONAL PROTECTION		

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances






















N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

Safety Data Sheet

Hardener

- >= 25% - < 48% n-butyl acetate
 REACH No.: 01-2119485493-29-xxxx, Index number: 607-025-00-1, CAS: 123-86-4, EC: 204-658-1
 B.6/3 Flam. Liq. 3 H226
 A.8/3 STOT SE 3 H336
- >= 25% - < 48% Hexamethylene diisocyanate, oligomers
 REACH No.: 01-2119485796-17-xxxx, CAS: 28182-81-2
 A.1/4/Inhal Acute Tox. 4 H332
 A.8/3 STOT SE 3 H335
 A.4.2/1 Skin Sens. 1 H317
- >= 12.5% - < 20% Aromatic polyisocyanate
 CAS: 9017-01-0
 A.4.2/1 Skin Sens. 1 H317
- >= 12.5% - < 20% butanone
 REACH No.: 01-2119457290-43-xxxx, Index number: 606-002-00-3, CAS: 78-93-3, EC: 201-159-0
 B.6/2 Flam. Liq. 2 H225
 A.3/2A Eye Irrit. 2A H319
 A.8/3 STOT SE 3 H336
- >= 1% - < 2% Solvent naphtha (petroleum), light arom
 REACH No.: 01-2119455851-35-xxxx, Index number: 649-356-00-4, CAS: 64742-95-6, EC: 265-199-0
 B.6/3 Flam. Liq. 3 H226
 A.8/3 STOT SE 3 H335
 A.8/3 STOT SE 3 H336
 US-HAE/C2 Aquatic Chronic 2 H411
 A.10/1 Asp. Tox. 1 H304
- >= 0.1% - < 0.2% m-tolylidene diisocyanate (Mixture of isomers)
 REACH No.: 01-2119454791-34-xxxx, Index number: 615-006-00-4, CAS: 26471-62-5, EC: 247-722-4
 A.6/2 Carc. 2 H351
 A.3/2A Eye Irrit. 2A H319
 A.8/3 STOT SE 3 H335
 A.2/2 Skin Irrit. 2 H315
 A.4.1/1 Resp. Sens. 1 H334
 A.4.2/1 Skin Sens. 1 H317
 US-HAE/C3 Aquatic Chronic 3 H412
 A.1/2/Inhal Acute Tox. 2 H330

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.
 Remove contaminated clothing immediately and dispose off safely.
 After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.



Safety Data Sheet

Hardener

Protect uninjured eye.
In case of Ingestion:
Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.
In case of Inhalation:
In case of inhalation, consult a doctor immediately and show him packing or label.
Most important symptoms/effects, acute and delayed
None
Indication of immediate medical attention and special treatment needed
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
Treatment:
None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:
In case of fire: Use a CO₂, Foam, Chemical powders for extinction.
Unsuitable extinguishing media:
None in particular.
Specific hazards arising from the chemical
Do not inhale explosion and combustion gases.
Burning produces heavy smoke.
Hazardous combustion products:
None
Explosive properties: N.A.
Oxidizing properties: N.A.
Special protective equipment and precautions for fire-fighters
Use suitable breathing apparatus.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures
Wear personal protection equipment.
Remove all sources of ignition.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Provide adequate ventilation.
Remove persons to safety.
Use appropriate respiratory protection.
See protective measures under point 7 and 8.
Methods and materials for containment and cleaning up
Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Do not use on extensive surface areas in premises where there are occupants.
Use localized ventilation system.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
Conditions for safe storage, including any incompatibilities
Always keep in a well ventilated place.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from flame and sparks. Avoid accumulating electrostatic charge.
Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.

Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
Safety electric system.
Storage temperature:
Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters
n-butyl acetate - CAS: 123-86-4

Safety Data Sheet

Hardener

TWA (Italia) - TWA: 150 ppm - STEL: 200 ppm
 ACGIH - TWA: 150 ppm - STEL: 200 ppm - Notes: Eye and URT irr
 butanone - CAS: 78-93-3
 (OEL (IT)) - TWA(8h): 600 mg/m³, 200 ppm - STEL: 900 mg/m³, 300 ppm - Behaviour: Binding
 EU - TWA(8h): 600 mg/m³, 200 ppm - STEL: 900 mg/m³, 300 ppm
 ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair
 m-tolylidene diisocyanate (Mixture of isomers) - CAS: 26471-62-5
 VLE - TWA(8h): 0.005 ppm - STEL: 0.02 ppm
 ACGIH - TWA: 0.04 mg/m³, 0.01 ppm - STEL: 0.14 mg/m³, 0.02 ppm - Notes: A4 sen
DNEL Exposure Limit Values
 n-butyl acetate - CAS: 123-86-4
 Worker Professional: 600 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
 Worker Professional: 300 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
 Worker Professional: 11 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Professional: 11 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects
 Consumer: 300 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, local effects
 Consumer: 35.7 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
 Consumer: 6 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects
 Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
 Hexamethylene diisocyanate, oligomers - CAS: 28182-81-2
 Worker Industry: 0.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
 Consumer: 1 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
 butanone - CAS: 78-93-3
 Worker Industry: 1161 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 600 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 412 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 106 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 31 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects
 Solvent naphtha (petroleum), light arom - CAS: 64742-95-6
 Worker Professional: 25 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Professional: 150 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 11 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 32 mg/Kg-bw/day - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 11 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects
 m-tolylidene diisocyanate (Mixture of isomers) - CAS: 26471-62-5
 Worker Industry: 0.14 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 0.14 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
 Worker Industry: 0.035 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 0.0035 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
PNEC Exposure Limit Values
 n-butyl acetate - CAS: 123-86-4
 Target: Fresh Water - Value: 0.18 mg/l
 Target: Marine water - Value: 0.018 mg/l
 Target: Freshwater sediments - Value: 0.981 mg/kg
 Target: Marine water sediments - Value: 0.0981 mg/kg
 Target: Soil (agricultural) - Value: 0.0903 mg/kg
 Target: STP - Value: 35.6 mg/l
 Hexamethylene diisocyanate, oligomers - CAS: 28182-81-2
 Target: Fresh Water - Value: 0.127 mg/l
 Target: Marine water - Value: 0.0127 mg/l
 Target: occasional emission - Value: 1.27 mg/l
 Target: Freshwater sediments - Value: 266700 mg/kg dwt
 Target: Marine water sediments - Value: 26670 mg/kg dwt
 Target: Microorganisms in sewage treatments - Value: 38.3 mg/l
 Target: Soil (agricultural) - Value: 53182 mg/kg dwt
 butanone - CAS: 78-93-3
 Target: Marine water - Value: 55.8 mg/l
 Target: Fresh Water - Value: 55.8 mg/l
 Target: occasional emission - Value: 55.8 mg/l
 Target: STP - Value: 709 mg/l
 Target: Freshwater sediments - Value: 284.7 mg/kg dwt
 Target: Marine water sediments - Value: 284.7 mg/kg dwt
 Target: Soil (agricultural) - Value: 22.5 mg/kg
 Target: orally (secondary poisoning) - Value: 1000 mg/kg
 Solvent naphtha (petroleum), light arom - CAS: 64742-95-6
 Target: Marine water - Value: 0.327 mg/l
 Target: Fresh Water - Value: 0.327 mg/l
 Target: Marine water sediments - Value: 12.46 mg/kg
 Target: Freshwater sediments - Value: 12.46 mg/kg
 Target: Soil (agricultural) - Value: 2.31 mg/kg
 Target: Microorganisms in sewage treatments - Value: 6.58 mg/l



Safety Data Sheet

Hardener

m-tolylidene diisocyanate (Mixture of isomers) - CAS: 26471-62-5

Target: Fresh Water - Value: 0.013 mg/l

Target: Marine water - Value: 0.00125 mg/l

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	liquid
Odour:	characteristic
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	< 1° C
Initial boiling point and boiling range:	> 55° C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	< 21° C - < 69.8 °F
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	0.9600 Kg/l a 20°C
Solubility in water:	N.A.
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	> 250° C
Decomposition temperature:	N.A.
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

10. STABILITY AND REACTIVITY

Reactivity	It may generate dangerous reactions (See subsections below)
Chemical stability	It may generate dangerous reactions (See subsections below)
Possibility of hazardous reactions	No dangerous reaction is stored and used appropriately.
Conditions to avoid	Avoid accumulating electrostatic charge. Vapours can form explosive mixtures with air.
Incompatible materials	Avoid contact with combustible materials. The product could catch fire.
Hazardous decomposition products	None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects	
Toxicological information of the product:	N.A.
Toxicological information of the main substances found in the product:	
n-butyl acetate - CAS: 123-86-4	
a) acute toxicity:	
Test: LC50 - Route: Inhalation - Species: Rat	> 21 mg/l - Duration: 4h
Test: LD50 - Route: Oral - Species: Rat	= 10736 mg/kg - Notes: Method OECD linee guide 402
Test: LD50 - Route: Skin - Species: Rabbit	> 14000 mg/kg
Hexamethylene diisocyanate, oligomers - CAS: 28182-81-2	
a) acute toxicity:	

Safety Data Sheet

Hardener

- Test: LD50 - Route: Oral - Species: Rat > 2500 mg/kg
 Test: LC50 - Route: Inhalation - Species: Rat = 390 mg/m³ - Duration: 4h - Notes: (OCSE Guide line 403)
 Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg
- b) skin corrosion/irritation:
 Test: Skin Irritant - Species: Rabbit Negative
 Test: Respiratory Tract Irritant Positive
- c) serious eye damage/irritation:
 Test: Eye Irritant Negative
- d) respiratory or skin sensitisation:
 Test: Skin Sensitization - Species: Cavia porcellus Positive
- Aromatic polyisocyanate - CAS: 9017-01-0
- a) acute toxicity:
 Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg
- b) skin corrosion/irritation:
 Test: Skin Sensitization - Route: Skin - Species: Cavia porcellus Positive
- butanone - CAS: 78-93-3
- a) acute toxicity:
 Test: LD50 - Route: Oral - Species: Rat = 2737 mg/kg
 Test: LD50 - Route: Skin - Species: Rabbit = 6480 mg/kg
 Test: LC50 - Route: Inhalation - Species: Rat = 23.5 mg/l - Duration: 8h
- b) skin corrosion/irritation:
 Test: Skin Corrosive - Species: Rabbit Negative - Notes: moderatamente irritante
- Solvent naphtha (petroleum), light arom - CAS: 64742-95-6
- a) acute toxicity:
 Test: LD50 - Route: Oral - Species: Rat = 3592 mg/kg - Source: guide line 401 (OECD)
 Test: LD50 - Route: Skin - Species: Rabbit > 3160 mg/kg - Source: guide line 402 (OECD)
 Test: LC50 - Route: Inhalation - Species: Rat > 6.193 mg/l - Duration: 4h - Source: guide line 403 (OECD)
- b) skin corrosion/irritation:
 Test: Respiratory Tract Irritant - Species: Rabbit Positive
- c) serious eye damage/irritation:
 Test: Eye Irritant - Species: Rabbit Negative
- d) respiratory or skin sensitisation:
 Test: Skin Sensitization - Species: Cavia porcellus Negative
- g) reproductive toxicity:
 Test: Reproductive Toxicity Negative - Source: method OECD TG414
 Test: Reproductive Toxicity Negative - Source: method OECD TG471 - Notes: TEST di AMES
- m-tolylidene diisocyanate (Mixture of isomers) - CAS: 26471-62-5
- a) acute toxicity:
 Test: LD50 - Route: Oral - Species: Rat male = 5110 mg/kg
 Test: LD50 - Route: Oral - Species: Rat Female = 4130 mg/kg
 Test: LD50 - Route: Skin - Species: Rabbit > 9400 mg/kg
 Test: LC50 - Route: Inhalation Mist - Species: Rat = 101 mg/m³ - Duration: 4h - Notes: Satur vapor concentration at 25°C : 255 mg/m³
 Test: LC50 - Route: Inhalation Vapour - Species: Rat 0.47 mg/l - Duration: 1h
- b) skin corrosion/irritation:
 Test: Skin Irritant - Route: Skin - Species: Rabbit Positive
- j) aspiration hazard:
 Test: Respiratory Tract Corrosive - Route: Inhalation - Species: Rabbit Positive

Substance(s) listed on the NTP report on Carcinogens:

m-tolylidene diisocyanate (Mixture of isomers).

Substance(s) listed on the IARC Monographs:

m-tolylidene diisocyanate (Mixture of isomers) - Group 2B.

Substance(s) listed as OSHA Carcinogen(s):

m-tolylidene diisocyanate (Mixture of isomers).

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 64 mg/l - Duration h: 48

Endpoint: EC50 - Species: Daphnia = 73 mg/l - Duration h: 24

Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72

Hexamethylene diisocyanate, oligomers - CAS: 28182-81-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 8.9 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 127 mg/l - Duration h: 48

Endpoint: CE20 - Species: Active mud = 3828 mg/l - Duration h: 3



Safety Data Sheet

Hardener

Endpoint: ErC50 - Species: Algae > 1000 mg/l - Duration h: 72
Aromatic polyisocyanate - CAS: 9017-01-0
a) Aquatic acute toxicity:
Endpoint: EC50 - Species: Active mud > 10000 mg/l
butanone - CAS: 78-93-3
a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish > 3220 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia > 520 mg/l - Duration h: 48
Solvent naphtha (petroleum), light arom - CAS: 64742-95-6
a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish = 9.22 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia = 6.14 mg/l - Duration h: 48
Endpoint: EC50 - Species: Algae = 2.9 mg/l - Duration h: 72
m-tolylidene diisocyanate (Mixture of isomers) - CAS: 26471-62-5
a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish = 133 mg/l - Duration h: 96
Endpoint: ErC50 - Species: Algae = 4300 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia = 12.5 mg/l - Duration h: 48
Endpoint: NOEC - Species: Daphnia = 1.1 mg/l - Duration h: 504
Endpoint: ErC50 - Species: Algae 4300 mg/l - Duration h: 96
Persistence and degradability
N.A.
Bioaccumulative potential
N.A.
Mobility in soil
N.A.
Other adverse effects
None

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

UN number
ADR-UN Number: 1263
DOT-UN Number: 1263
IATA-UN Number: 1263
IMDG-UN Number: 1263
UN proper shipping name
ADR-Shipping Name: Paint Related material
DOT-Shipping Name: Paint Related material
IATA-Shipping Name: Paint Related material
IMDG-Shipping Name: Paint Related material
Transport hazard class(es)
ADR-Class: 3
DOT-Class: 3
IATA-Class: 3
IMDG-Class: 3
Packing group
ADR-Packing Group: II
DOT-Packing Group: II
IATA-Packing group: II
IMDG-Packing group: II
Environmental hazards
ADR-Environmental Pollutant: No
IMDG-Marine pollutant: No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)
No
Special precautions
ADR-Tunnel Restriction Code: D/E
DOT-Special provisions: 149, B52, IB2, T4, TP1, TP8, TP28
IATA-Passenger Aircraft: 353
IATA-Cargo Aircraft: 364
IATA-S.P.: A72
IATA-ERG: 8L
IMDG-EmS: F-E, S-E
IMDG-Storage category: B
IMDG-Storage notes: None
N.A.



Safety Data Sheet

Hardener

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)
No

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory.

TSCA listed substances:

n-butyl acetate is listed in TSCA Section 4, Section 12b

m-tolylidene diisocyanate (Mixture of isomers) is listed in TSCA Section 8a - CAIR, Section 8d, Section 8d HSDR.

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: no substances listed.

Section 313 – Toxic chemical list: m-tolylidene diisocyanate (Mixture of isomers).

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: n-butyl acetate - Reportable quantity: 5000 pounds

butanone - Reportable quantity: 5000 pounds

m-tolylidene diisocyanate (Mixture of isomers) - Reportable quantity: 100 pounds.

Reportable quantity for mixture: 11979.49169 pounds.

CAA - Clean Air Act

CAA listed substances:

n-butyl acetate is listed in CAA Section 111

butanone is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

m-tolylidene diisocyanate (Mixture of isomers) is listed in CAA Section 111, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

n-butyl acetate is listed in CWA Section 311, Section 304.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

m-tolylidene diisocyanate (Mixture of isomers) - Listed as carcinogen.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

n-butyl acetate

butanone

m-tolylidene diisocyanate (Mixture of isomers).

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

n-butyl acetate

butanone

m-tolylidene diisocyanate (Mixture of isomers).

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

n-butyl acetate

butanone

m-tolylidene diisocyanate (Mixture of isomers).

16. OTHER INFORMATION

Text of phrases referred to under heading 3:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H317 May cause an allergic skin reaction.

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H304 May be fatal if swallowed and enters airways.

H351 Suspected of causing cancer.

H315 Causes skin irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H412 Harmful to aquatic life with long lasting effects.

H330 Fatal if inhaled.

Safety Data Sheet dated 11/30/2017, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.



Safety Data Sheet

Hardener

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average