



GEMINI
COATINGS

PRODUCT DATA SHEET

Waterborne Retarder
SOL-0090

DESCRIPTION

SOL-0090 is used specifically for increasing the open time of waterborne coatings. In hot weather or adverse conditions (such as areas of high heat or air flow), it will improve flow and leveling properties in coatings, and increase the open time and workability of wiping stains and glazes.

PRODUCT NUMBERS / SHEENS	COATING PROPERTIES	INSTRUCTIONS FOR USE
SOL-0090	<p>Weight/Gallon: 8.67 lbs./gal</p> <p>VOC (reg./coating): 8.7 lbs./gl. or 1037.7 g/l VOC (actual/material): 8.7 lbs./gl. or 1037.7 g/l HAPs Lbs./gl.: 0.0 HAPs Ratio: 0.0</p> <p>Shelf Life: 3 years @77° F if unopened and stored in a cool dry area. Always rotate stock.</p> <p>Storage: Keep away from heat or sparks.</p> <p>Clean Up: Dispose of in accordance with Federal, State, and local regulations regarding pollution.</p> <p><i>Note: These numbers represent actual control values on a smooth, sanded substrate. Spray techniques, texture, and sealing as well as film thickness may give different results on actual work, but they may be used for comparison. To the best of our knowledge, the above technical data is true and accurate at the date of issuance but is subject to change without prior notice.</i></p>	<p>May be added to Gemini's Waterborne coatings up to 5% max*</p> <p>May be added to Gemini's Waterborne stains and glazes up to 10% max*</p> <p>Use: This product should be mixed thoroughly into the liquid coating prior to application of the coating. Incorporate only the required level to achieve the desired viscosity or effect. DO NOT Shake waterborne coatings.</p> <p>*Refer to the Product Data Sheet for the specific coating you are using for reduction instructions. Use only the solvents/thinners recommended on the Product Data Sheet for the product you are using.</p> <p>Use of this material may result in increasing the VOC levels of your product. Refer to your local regulations before thinning.</p>
PRODUCT ADVANTAGES		
<ul style="list-style-type: none">➤ Slows Dry For Better Open Time In Extreme Conditions➤ Add Only A Small Amount (1-5%) To Achieve Desired Results➤ Improves Flow And Leveling Of Waterborne Coatings in areas of high heat and excessive air flow➤ HAPs Free		

March, 2019

The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. **HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER. **CAUTION: DANGER! FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN! BEFORE using this product it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact the manufacturer.**