



Safety Data Sheet

The Craftsman Collection

TOBACCO



1. Identification

Product identifier	The Craftsman Collection TOBACCO		
Product code	CC007		
Other means of identification	N/Av.		
Recommended use of the chemical and restrictions on use	PAINT. A protective and/or decorative finish or accompanying paint product.		
Manufacturer	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 Tel. 1-800-262-5710 Fax 1-405-262-9310 www.geminicoatings.com	Distributor	Gemini Industries, Inc. 850 Flint Road Toronto, Ontario Canada M3J 2T7 Tel. 1-800-262-5710
Emergency phone number	INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English) 24-hour PPG Architectural Coatings Canada Inc. 1-450-442-7999, 8h00-17h00 HAZMAT Response and MSDS help: EMI 800-510-8510		

2. Hazard identification

Summary	Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved.
----------------	---

WHMIS 2015/OSHA HCS 2012/GHS



Flammable liquids (Category 3)
 Acute toxicity, inhalation (Category 4)
 Skin corrosion/irritation (Category 2)
 Serious eye damage/eye irritation (Category 2A)
 Skin sensitizer (Category 1)
 Germ cell mutagenicity (Category 1B)
 Carcinogenicity (Category 1B)
 Reproductive toxicity (Category 1B)
 Specific target organ toxicity, repeated exposure (Category 1)
 Aspiration hazard (Category 1)

Other hazards which do not result in classification :

Acute toxicity, dermal (Category 5)

DANGER

- H226: Flammable liquid and vapour
- H350: May cause cancer
- H340: May cause genetic defects
- H360: May damage fertility or the unborn child
- H372: Causes damage to the central nervous system through prolonged or repeated exposure by inhalation
- H304: May be fatal if swallowed and enters airways

H332: Harmful if inhaled
H319: Causes serious eye irritation
H315: Causes skin irritation
H317: May cause an allergic skin reaction
H313: May be harmful in contact with skin
P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P240: Ground or bond container and receiving equipment.
P241: Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe mist, vapours and spray.
P264: Wash skin thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only in a well-ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves, protective clothing and eye protection.
P301+310+331: IF SWALLOWED: Immediately call a POISON CENTER or a physician. Do NOT induce vomiting.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or take a shower if necessary.
P333+313: If skin irritation or a rash occurs: Get medical advice/attention.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337+313: If eye irritation persists: Get medical advice or attention.
P308+313: IF exposed or concerned: Get medical advice/attention.
P321: Specific treatment (see on this label).
P362+364: Take off contaminated clothing and wash before reuse.
P370+378: In case of fire: Use the National Fire Protection Association Class B extinguisher for extinction.
P403+235: Store in a well ventilated place. Keep cool.
P405: Store locked up.
P501: Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

3. Composition/information on ingredients

Common name	CAS	Weight % content
Solvent naphtha (petroleum), heavy aromatic (C9-C16)	64742-94-5	36 - 37 %
Stoddard solvent (Mineral Spirits)	8052-41-3	30 - 31 %
2-Butoxyethanol	111-76-2	4.5 - 5.5 %
Naphthalene	91-20-3	3.5 - 4.5 %
1,2,4-Trimethylbenzene	95-63-6	3.5 - 4.5 %
Solvent naphtha (petroleum), light aromatic (C8 to C10)	64742-95-6	2.5 - 3.5 %
Synthetic Amorphous Fumed Silica	112945-52-5	1.5 - 2.5 %
Naphtha (petroleum), hydrotreated heavy (C6-C13)	64742-48-9	1 - 2 %
Carbon black	1333-86-4	0.5 - 1.5 %
Xylene	1330-20-7	0.1 - 1 %

4. First-aid measures

Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
Skin contact	Wash skin with warm water and mild soap for at least 15 minutes. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.
Eye contact	IMMEDIATELY flush with plenty of water. Remove contact lenses. Flush with water for at least 15 minutes. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If victim is conscious rinse mouth with water and give 1-2 glasses of water to drink. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.
Other	No information available.
Symptoms	May cause irritation to skin and eyes. May cause an allergic reaction of the skin. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. Aspiration hazard for the lungs (ingestion/vomiting). Can enter lungs and cause damage. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discolouration of the skin. Coughing, choking and gagging are often noted at the time of aspiration.
Notes to the physician	Treat symptomatically. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire-fighting measures

Suitable extinguishing media	Class B extinguishers. Dry chemicals, alcohol resistant foam, carbon dioxide (CO ₂). Do not use direct water jet.
Specific hazards arising from the chemical	Vapours are heavier than air and may travel to an ignition source distant from the material handling point. May be ignited by heat, sparks, flame or static electricity. Do not apply to hot surfaces. Contact with strong oxidizers may cause fire. In a fire or if heated, a pressure increase will occur and the container may burst. Emits toxic fumes under fire conditions.
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
Special protective actions for fire-fighters	Water stream can scatter and spread fire. If water is used, fog nozzles are preferable. Use water spray to cool fire-exposed containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
Environmental precautions	Prevent entry in sewer and other enclosed area. For a large spill, consult the Department of Environment or the relevant authorities.
Methods and materials for containment and cleaning up	Remove sources of ignition. Ventilate the area well. Make sure you have a fire extinguisher near you. Stop leak, if it's possible to do so without risk. Use non-sparking and antistatic tools. Absorb with inert material (soil, sand, vermiculite, Dustbane) and place in an appropriate waste disposal clearly identified. Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water. PS: Rags and others materials soaked with paint or solvent may spontaneously catch fire if improperly store or discarded. Immediately after each use place rags and paper towels in a sealed water-filled metal container to prevent spontaneous combustion.

7. Handling and storage

Precautions for safe handling	Keep away from heat, sparks and open flame. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Use non-sparking and antistatic tools. Ground/bond all containers when transferring large quantities (5 gallons US or 20 L and more). Use only in well ventilated area. Avoid prolonged or repeated breathing of vapour or mists. Avoid contact with skin, eyes and clothing. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet. Keep containers tightly closed when not in use. Containers of this material may be hazardous even when empty. Since empty containers retain product residues (vapour, liquid), all hazard precautions given in this sheet must be observed. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse. Rags, steel wool and paper towels soaked with this product may overheat and spontaneously ignite if piled in a heap. After use immediately store them in water-filled metal can with tight fitting lid.
Conditions for safe storage, including any incompatibilities	Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10).
Storage temperature	10 to 25°C (50 to 77°F)

8. Exposure controls/personal protection

Immediately Dangerous to Life or Health	Stoddard solvent (Mineral Spirits): 20000 mg/m ³ . 2-Butoxyethanol: 700 ppm. Naphthalene: 250 ppm. Synthetic Amorphous Fumed Silica: 3000 mg/m ³ . Xylenes: 900 ppm. Carbon Black: 1750 mg/m ³ .		
Stoddard solvent (Mineral Spirits)	STEL	580 mg/m ³	BC
	TWA (8h)	290 mg/m ³	BC
		100 ppm	525 mg/m ³ ACGIH , ON, RSST
		500 ppm	2900 mg/m ³ OSHA
2-Butoxyethanol	TWA (8h)	20 ppm	ACGIH , BC, ON
		20 ppm	97 mg/m ³ RSST
		50 ppm	240 mg/m ³ OSHA
1,2,4-Trimethylbenzene	TWA (8h)	25 ppm	ACGIH , BC, ON, OSHA
		25 ppm	123 mg/m ³ RSST
Naphthalene	STEL	15 ppm	BC
		15 ppm	78 mg/m ³ ON
		15 ppm	79 mg/m ³ ACGIH , RSST
	TWA (8h)	10 ppm	BC , OSHA
		10 ppm	52 mg/m ³ ACGIH , ON, RSST
Synthetic Amorphous Fumed Silica	TWA (8h) Respirable Dust	1.5 mg/m ³	BC
	Respirable Dust	3 mg/m ³	ACGIH , ON
	Total Dust	4 mg/m ³	BC
	Respirable Dust	6 mg/m ³	RSST
	Total Dust	10 mg/m ³	ACGIH , ON
Naphtha (petroleum), hydrotreated heavy (C6-C13) TWA (8h) Mist		5 mg/m ³	ACGIH , RSST
		175 ppm	1200 mg/m ³ Other
		300 ppm	OSHA
Carbon black	Ceiling	3.5 mg/m ³	OSHA
	TWA (8h)	3 mg/m ³	ACGIH , BC, ON

Xylene	STEL	3.5 mg/m ³	RSST	
		150 ppm	ACGIH , BC, ON, OSHA	
	TWA (8h)	150 ppm	651 mg/m ³	RSST
		100 ppm	100 ppm	ACGIH , BC, ON, OSHA
		100 ppm	434 mg/m ³	RSST
Appropriate engineering controls	Provide sufficient mechanical ventilation (general and/or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.			
Individual protection measures				
Eye	If there is a risk of contact with eyes, wear chemical splash goggles.			
Hands	If any risk of skin contact wear nitrile or neoprene gloves. Disposable nitrile gloves can also be used, but discard after single use. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly.			
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. Wear synthetic apron, if necessary, to prevent repeated or prolonged contact with skin.			
Respiratory	Respiratory protection is not required for normal use. Respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and CSA Standard Z 94.4 and approved by NIOSH / MSHA. In case of insufficient ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times the exposure limit, wear a half mask respirator with organic vapour cartridges fitted with P100 filters. For an APF until maximum 100 times of exposure limit, wear a full face respirator mask with organic vapour cartridges and P100 filters.			
Feet	Wear rubber boots to clean up a spill.			

9. Physical and chemical properties

Physical state	Liquid	Flammability	Flammable
Colour	Brownish	Flammability limits	N/Av.
Odour	Solvent	Flash point	41°C (105.8°F)
Odour threshold	N/Av.	Auto-ignition temperature	226°C (438.8°F)
pH	N/Av.	Sensibility to electrostatic charges	Yes
Melting point	N/Av.	Sensibility to sparks and/or friction	N/Av.
Freezing point	N/Av.	Vapour density	>1 (Air = 1)
Boiling point	150 to 210°C (302 to 410°F)	Relative density	0.918 kg/L (Water = 1)
Solubility	Negligible (<5%) in water	Partition coefficient n-octanol/water	N/Av.
Evaporation rate	> Butyl Acetate	Decomposition temperature	N/Av.
Vapour pressure	N/Av.	Viscosity	N/Av.
Percent Volatile	83.4%	Molecular mass	N/Av.

N/Av.: Not Available N/Av.: Not Applicable Und.: Undetermined N/E: Not Established

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions (including polymerizations)	A dangerous reaction will not occur.
Conditions to avoid	Avoid heat, flame and sparks. Avoid contact with incompatible materials.
Incompatible materials	Strong oxidants, strong bases, mineral acids, strong acids.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Numerical measures of toxicity	Solvent naphtha (petroleum), heavy aromatic (C9-C16)	Ingestion 7050 mg/kg	Rat	LD50
		Inhalation >5.2 mg/l/4h	Rat	LC50
		Skin >2000 mg/kg	Rat	LD50
	Stoddard solvent (Mineral Spirits)	Ingestion >5000 mg/kg	Rat	LD50
		Inhalation >12 mg/l/4h	Rat	LC50
		Skin >3000 mg/kg	Rabbit	LD50
	2-Butoxyethanol	Ingestion 560 mg/kg	Rat	LD50
		Inhalation 2.21 mg/l/4h	Rat	LC50
		Skin 220 mg/kg	Rabbit	LD50
	1,2,4-Trimethylbenzene	Ingestion 5000 mg/kg	Rat	LD50
		Inhalation 18 mg/l/4h	Rat	LC50
		Skin >3160 mg/kg	Rabbit	LD50
	Naphthalene	Ingestion 490 mg/kg	Rat	LD50
		Inhalation >1 mg/l/1h	Rat	LC50
	Skin 1120 mg/kg	Rabbit	LD50	
Solvent naphtha (petroleum), light aromatic (C8 to C10)	Ingestion 8400 mg/kg	Rat	LD50	
	Inhalation >5.2 mg/l/4h	Rat	LC50	
	Skin >3750 mg/kg	Rabbit	LD50	
Synthetic Amorphous Fumed Silica	Ingestion >5000 mg/kg	Rat	LD50	
	Inhalation >2.08 mg/l/4h	Rat	LC50	
	Skin >5000 mg/kg	Rabbit	LD50	
Naphtha (petroleum), hydrotreated heavy (C6-C13)	Ingestion >10000 mg/kg	Rat	LD50	
	Inhalation >8.5 mg/l/4h	Rat	LC50	
	Skin >3200 mg/kg	Rabbit	LD50	
Carbon black	Ingestion >15400 mg/kg	Rat	LD50	
	Skin >3000 mg/kg	Rabbit	LD50	
Xylene	Ingestion 3523 mg/kg	Rat	LD50	
	Inhalation 27.6 mg/l/4h	Rat	LC50	
	Skin 3200 mg/kg	Rabbit	LD50	
Likely routes of exposure	Skin, eyes, inhalation, ingestion.			
Delayed, immediate and chronic effects	Eye contact	May cause irritation, redness, tearing and blurred vision. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with each ingredient of this mixture gave not irritating to irritating results.		
	Skin contact	May cause redness, dryness or rash of the skin. Prolonged and repeated contact may cause dry skin, irritation or dermatitis. Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient of this mixture gave not irritating to irritating results.		


	<p>Inhalation Excessive inhalation is harmful. May cause irritation to nose, throat and respiratory tract. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. The severity of symptoms may vary depending on exposure conditions. Numerous studies on human, especially from the monitoring of painters, suggest that long-term occupational exposure to white spirit (all types) cause chronic toxic encephalopathy (adverse central nervous system effects).</p> <p>Ingestion Harmful or fatal if inhaled into the lungs (ingestion/vomiting). Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discolouration of the skin. Coughing, choking and gagging are often noted at the time of aspiration. Contains a substance that can cause target organ damage, according to data obtained on animals.</p> <p>Respiratory or skin sensitization There is a case of dermatitis allergy to naphthalene reported in human. However, there is a report of negative results in 2 guinea pig skin sensitizing tests (OECD Guideline 406).</p> <p>IARC/NTP Classification Common name IARC NTP Naphthalene 2B R Carbon black 2B - IARC : 1- Carcinogenic; 2A- Probably carcinogenic; 2B- Possibly carcinogenic. NTP : K- Known to be carcinogens; R- Reasonably anticipated to be carcinogens.</p> <p>Carcinogenicity Many carcinogenicity Studies with solvent naphtha (petroleum) products containing no significant concentrations of known carcinogens compounds (<0.1%) have shown dermal tumours developed. It was concluded that these middle distillate petroleum product are potential skin carcinogens (OECD Guideline 451). Contains substances that can cause cancer based on animal data. The risk of cancer depends on duration and level of exposure.</p> <p>Mutagenicity Some solvent naphtha (petroleum) products are considered mutagenic in bacterial assay (OECD Guideline 471).</p> <p>Reproductive toxicity Xylene overexposure may affect fetal development in laboratory animals by inhalation during pregnancy. The inhalation of high concentration of 2-Butoxyethanol has an embryotoxic and/or foetotoxic effect on rats and rabbits at doses which were severely toxic to the animals</p> <p>Specific target organ toxicity - single exposure No target organ is listed.</p> <p>Specific target organ toxicity - repeated exposure Central nervous system.</p>
Interactive effects	No information available for this product.
Other information	The oral and skin acute toxicity estimates (ATE) of the mixture were calculated to be greater than 2000 mg/kg but lower than 5000 mg/Kg. These values are classified category 5 by the GHS. These values are not classified according to WHMIS 2015 and OSHA HCS 2012. The acute toxicity estimate (ATE) by inhalation of the mixture was calculated to be greater than 10 mg/L/4h but lower than 20 mg/L/4h. This value is classified according to GHS: Acute toxicity, inhalation (Category 4).

12. Ecological information


Ecological toxicity	<p>Oncorhynchus mykiss LC50 2.34 mg/L - 96 h (Solvent naphtha (petroleum), heavy aromatic (C9-C16))*</p> <p>Daphnia magna EC50 0.95 mg/L - 48 h (Solvent naphtha (petroleum), heavy aromatic (C9-C16))*</p> <p>Oncorhynchus mykiss LC50 0.91-2.82 mg/L - 96 h (naphthlene)*</p> <p>Daphnia magna EC50 1.09-3.4 mg/L - 48 h (naphthlene)*</p> <p>Pimephales promelas LC50 7.19-8.28 mg/L - 96 h (1,2,4-trimethylbenzene)*</p> <p>Daphnia magna EC50 6.14 mg/L - 48 h (1,2,4-trimethylbenzene)*</p> <p>Oncorhynchus mykiss LC50 9.22 mg/L - 96 h (Solvent naphtha (petroleum), light aromatic (C8 to C10))*</p> <p>Daphnia magna EC50 6.14 mg/L - 48 h (Solvent naphtha (petroleum), light aromatic (C8 to C10))*</p>
----------------------------	---

Persistence	The product contains components that may persist in the environment.
Degradability	No information available for this product. The product is a heavy hydrocarbon mixture in which some ingredients are not expected to be readily biodegradable (OECD 301). Stoddard solvent (Mineral Spirits) is not rapidly degrading, according to Biochemical Oxygen Demand (BOD) of 12-13% (EHC187, 1996). 2-Butoxyethanol is readily biodegradable 90.4% in 28 days (OECD Guideline 301B). Naphthalene is considered to be not readily biodegradable, but is inherently or easily biodegradable under aerobic conditions in many non-standard tests. 1,2,4-Trimethylbenzene is not readily biodegradable (4 to 18% in 28 days) according to OECD 301C Guideline. The term biodegradability, as such, is not applicable to inorganic compounds like Titanium dioxide.
Bioaccumulative potential	No information available for this product. The product is a hydrocarbon mixture of which some ingredients have different bioaccumulation potential. 2-Butoxyethanol is not expected to bioaccumulate based on a low partition coefficient (Log Kow <2). Naphthalene exhibits a low potential of accumulation with a Bioconcentration Factors (BCF) of <200 (OECD Guideline 305).
Mobility in soil	No information available for this product. The product is a hydrocarbon mixture of which some ingredients can evaporate into the air while others present a medium to low mobility in soil. The estimated Koc value of 0.83 suggests that 2-Butoxyethanol is expected to have high mobility in soil (TOXNET). The Koc values of <650 suggest that naphthalene is expected to have high to no mobility in soil (TOXNET).
Other adverse effects	This chemical does not deplete the ozone layer. Uncontrolled release of the product may result in contamination of air, ground, waterways and/or sewers. *Data from Gemini Coatings safety data sheet.

13. Disposal considerations

Container 	Important! Prevent waste generation. Use in full. DO NOT dispose of residue in sewers, streams or drinking water supply. DO NOT puncture, cut, heat or burn container, even after use. Paint residues, including lacquers, stains, shellac, varnish, solvents and paint thinners, can be reprocessed (recycle) anywhere there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.
---	---

14. Transport information

UN Number	UN 1263
UN Proper Shipping Name	PAINT
Environmental hazards	Contains an ingredient which is a marine pollutant.
Special precautions for user	Permit required for transportation with proper placards displayed on vehicle.
TDG - Transportation of Dangerous Goods (Canada)	
Transport hazard class(es)	 Class 3
Packing group	III
IMO/IMDG - International Maritime Transport	
Classification	UN 1263. PAINT. Class 3, PG III. Emergency schedules (EmS-No) F-E, S-E
IATA - International Air Transport Association	
Classification	UN 1263. PAINT. Class 3, PG III.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.

15. Regulatory information

CANADA

Common name	CAS	CEPA	DSL	NDSL	NPRI
Solvent naphtha (petroleum), heavy aromatic (C9-C16)	64742-94-5	X	X		X
Stoddard solvent (Mineral Spirits)	8052-41-3	X	X		X
2-Butoxyethanol	111-76-2	X	X		X
Naphthalene	91-20-3	X	X		X
1,2,4-Trimethylbenzene	95-63-6	X	X		X
Solvent naphtha (petroleum), light aromatic (C8 to C10)	64742-95-6	X	X		X
Synthetic Amorphous Fumed Silica	112945-52-5		X		
Naphtha (petroleum), hydrotreated heavy (C6-C13)	64742-48-9	X	X		X
Carbon black	1333-86-4		X		
Xylene	1330-20-7	X	X		X

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act
- DSL: Domestic Substances List Inventory
- NDSL: Non-Domestic Substances List Inventory
- NPRI: National Pollutant Release Inventory Substances

UNITED STATE OF AMERICA




Common name	CAS	TSCA	CERCLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Priority
Solvent naphtha (petroleum), heavy aromatic (C9-C16)	64742-94-5	X								
Stoddard solvent (Mineral Spirits)	8052-41-3	X								
2-Butoxyethanol	111-76-2	X								
Naphthalene	91-20-3	X	X	X		X	X		X	X
1,2,4-Trimethylbenzene	95-63-6	X		X	X					
Solvent naphtha (petroleum), light aromatic (C8 to C10)	64742-95-6	X								
Synthetic Amorphous Fumed Silica	112945-52-5	X								
Naphtha (petroleum), hydrotreated heavy (C6-C13)	64742-48-9	X								
Carbon black	1333-86-4	X								
Xylene	1330-20-7	X	X	X		X	X		X	

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act - Hazardous Organic National Emission Standard for Hazardous Air Pollutant
- CAA 112(b) HAP: Clean Air Act - Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act - Regulated Chemicals for Accidental Release Prevention
- CWA 311: Clean Water Act - List of Hazardous Substances
- CWA Priority: Clean Water Act - Priority Pollutant list

California Proposition 65

Common name	CAS	Cancer	Reproductive and Developmental Toxicity
-------------	-----	--------	---

Naphthalene	91-20-3	X	
Carbon black	1333-86-4	X	

Other regulations	<p>WHMIS 1988</p>  <p>B3 D1A D2A D2B</p> <p>Class B3 : Combustible Liquid Class D1A : Very toxic material causing immediate and serious toxic effects Class D2A : Very toxic material causing other toxic effects Class D2B : Toxic material causing other toxic effects</p>
	<p>HMIS</p>  <p>NFPA</p> 

16. Other information

Date (YYYY-MM-DD)	GEMINI INDUSTRIES, INC. 2016-02-09
Version	02
Other information	<p>REFERENCES:</p> <ul style="list-style-type: none"> - Original safety data sheet (product code CC007) from Gemini Coatings. Date prepared: 2015-10-20. - Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, http://hazmap.nlm.nih.gov/index.php - TOXNET Databases, Toxicology Data Network, NIH U.S. National Library of Medicine, http://toxnet.nlm.nih.gov/ - Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), http://www.reptox.csst.qc.ca - NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, http://www.cdc.gov/niosh/npg/npg.html - IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), http://www.inchem.org - OECD Existing Chemicals Database, Chemicals Screening Information DataSet (SIDS) for High Volume Chemicals, UNEP publications, http://webnet.oecd.org/HPV/UI/Search.aspx <p>DATE OF FIRST VERSION OF SDS: 2015-12-10</p> <p>CHANGES MADE IN THE VERSION 02: sections 2, 3, 8, 9 and 11.</p> <p>ACGIH: American Conference of Governmental Industrial Hygienists AIHA: American Industrial Hygiene Association HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association OSHA: Occupational Safety and Health Administration (USA) NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program RSST: Règlement sur la santé et la sécurité du travail (Québec) GHS: Globally Harmonized System IARC: International Agency for Research on Cancer</p>

IDLH: Immediately Dangerous to Life or Health
STEL: Short Term Exposure Limit (15 min)
TWA: Time Weighted Averages
WHMIS: Workplace Hazardous Materials Information System

To the best of our knowledge, the information contained herein is accurate. However, neither Préventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.