



SAFETY DATA SHEET

SECTION 1 - Chemical Product and Company Information

Product Name: HYDRO-PURE SEALER Product Code: HPURE-0100

Manufactured by:

Gemini Coatings
2300 Holloway Drive
El Reno, OK 73036
800-262-5710

24- Hour Emergency (Spill, Leak, Exposure or Accident):
INFOTRAC 800-535-5053
Outside USA, Call Collect 1-352-323-3500

24- Hour Emergency HAZMAT Response and MSDS Help:
EMI 800-510-8510

Product Use: A protective and/or decorative finish or accompanying product (reference label or product data sheet for more information).

Not recommended for: Any other use not detailed on product data sheet or label .

SECTION 2 - Hazards Identification

GHS Ratings:

Flammable liquid	3	Flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$ (140°F)
Oral Toxicity	Acute Tox. 3	Oral $>50 + \leq 300\text{mg/kg}$
Skin corrosive	3	Reversible adverse effects in dermal tissue, Draize score: $\geq 1.5 < 2.3$
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Reproductive toxin	1A	Based on human evidence

GHS Hazards

H226	Flammable liquid and vapour
H301	Toxic if swallowed
H316	Causes mild skin irritation
H319	Causes serious eye irritation
H360	May damage fertility or the unborn child

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/mixers/equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P264	Wash any exposed skin thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P321	Specific treatment (see First Aid section on this label)
P330	Rinse mouth

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	Get medical advice/attention
P370+P378	In case of fire: Use the NFPA Class B extinguisher for extinction
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool
P501	Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations.

Signal Word: Warning



SECTION 3 - Composition/Information on Ingredients

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
2-Propanol, 1-(2-butoxy-1-methylethoxy)- 29911-28-2 1% - 5%			
2-BUTOXYETHANOL 111-76-2 1% - 5%	50 ppm TWA; 240 mg/m3 TWA	20 ppm TWA	NIOSH: 5 ppm TWA; 24 mg/m3 TWA

SECTION 4 - First Aid Measures

Inhalation:

Remove exposed individual to fresh air and assist breathing if necessary. Vapor or mist can cause headache, nausea and irritation of the nose, throat and lungs in poorly ventilated areas.

Eye Contact:

Direct contact may cause eye irritation. Flush eyes with lukewarm water for 15 minutes. Seek medical attention immediately.

Skin:

Irritating to the skin on repeated or prolonged contact. Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

Ingestion:

Can cause gastrointestinal irritation. Rinse mouth out immediately. DO NOT induce vomiting. Contact physician or poison control center immediately.

SECTION 5 - Fire Fighting Measures

Alcohol Foam, CO2, Dry Chemical

Closed containers exposed to extreme heat may rupture due to pressure buildup. Product will not burn but may spatter if temperature exceeds boiling point of product.

Dried finish can burn, giving off oxides of carbon.

None known. However, fire fighters should wear self-contained breathing apparatus to avoid inhalation if material is involved in a general fire.

SECTION 6 - Accidental Release Measures

Keep out of sewers. Dike spill area and add absorbent earth, sand or sawdust to spilled liquid. Collect absorbent/spilled liquid into metal containers. Dispose of in accordance with local, state and federal regulations. DO NOT incinerate closed containers. Incinerate in approved facilities. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned and destroyed.

SECTION 7- Handling and Storage

Handling:

Bond and ground metal containers when transferring liquid. Avoid free fall of liquid in excess of a few inches. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this sheet must be observed.

** Keep temperature above 32 Degrees F.

Storage:

Keep containers tightly closed when not in use. Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas. KEEP FROM FREEZING.

SECTION 8 - Exposure Controls/Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
2-Propanol, 1-(2-butoxy-1-methylethoxy)- 29911-28-2			
2-BUTOXYETHANOL 111-76-2	50 ppm TWA; 240 mg/m3 TWA	20 ppm TWA	NIOSH: 5 ppm TWA; 24 mg/m3 TWA

Provide general clean air dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below applicable exposure limits.

Avoid prolonged or repeated breathing of vapors.

Respiratory Protection:

If exposure exceeds TLV or PELs, use NIOSH approved respirator to prevent overexposure.

Skin Protection:

Polyethylene handling gloves for skin protection. Must be impervious to water and soap.

Eye Protection:

Wear splash proof goggles and face shield if there is a likelihood of contact with eyes. Provide eyewash station and emergency shower. Use of protective creams, head caps, etc. is recommended.

Hygienic Practices

Wash hands thoroughly before eating or using the restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

SECTION 9 - Physical and Chemical Properties

Vapor Density Heavier Than Air Boiling range: 100 - 168°C Freezing point: N/A Flammability: N/A Autoignition temperature: 189°C Relative Density: N/A Odor threshold: N/A SPECIFIC GRAVITY 1.0386 Partition coefficient (n- octanol/water): N/A Grams VOC less water: N/A % WT. VOLATILE (VOC) 3.4510 Lbs VOC/Gallon Solids 1.1619 SOLIDS VOL% 25.6856 SPREAD @ 1 MIL 411.9976 Appearance Colored Liquid Physical State Liquid Coating VOC (g/l) 120.3887 Coating VOC (Lb/Gl) 1.0047	Evaporation Rate Slower than Butyl Acetate Melting point: N/A Flash point: 140°F, 60°C Explosive Limits: N/A Decomposition temperature: N/A Vapor Pressure N/A pH: N/A Solubility: N/A Viscosity: N/A % VOLUME VOLATILE (VOC) 4.0203 % Pig. by wt. 0.0000 VOLATILE WT% 71.3344 DENSITY (Lb/Gal) 8.6480 HAPS (lbs/gl) 0.0000 Odor N/A Material VOC (g/l) 35.7625 Material VOC (Lb/Gl) 0.2984
---	--

SECTION 10 - Stability and Reactivity

Stability: Stable under normal conditions.

Materials to Avoid: None known.

Conditions to avoid: Excessive heat, poor ventilation, excessive aging.

Hazardous Decomposition: Thermal decomposition or combustion can produce fumes of carbon dioxide and carbon monoxide.

Hazardous polymerization will not occur.

SECTION 11 - Toxicological Information**Mixture Toxicity**

Oral Toxicity LD50: 84mg/kg

Inhalation Toxicity LC50: 2,018mg/L

Component Toxicity

111-76-2

2-BUTOXYETHANOL

Oral LD50: 470 mg/kg (Rat) Dermal LD50: 99 mg/kg (Rabbit) Inhalation LC50: 486 ppm (Rat)

Primary Routes of Entry: Inhalation, Skin Contact, Eyes, Ingestion

Skin:

Skin contact can cause redness, dryness or rash. Prolonged contact can cause irritation, dry skin, cracks, and dermatitis.

Ingestion:

Can cause vomiting, nausea, diarrhea, and gastrointestinal irritation.

Inhalation:

Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Breathing high vapor concentrations may produce narcosis. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentration and inhaling the contents may be harmful or fatal.

Eyes:

Can cause irritation, redness, tearing and blurred vision.

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
None			N/A

SECTION 12 - Ecological Information
--

Ecological Information:

Uncontrolled release of the product may result in contamination of air, ground, waterways and/or sewers.

Component Ecotoxicity

2-Propanol, 1-(2-butoxy-1-methylethoxy)-	LC50 96 h Poecilia reticulata 841 mg/L [static]
2-BUTOXYETHANOL	LC50 96 h Lepomis macrochirus 1490 mg/L [static] (EPA); LC50 96 h Lepomis macrochirus 2950 mg/L (IUCLID) EC50 48 h Daphnia magna >1000 mg/L (EPA)

SECTION 13 - Disposal Considerations

Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations. See Section 8 for information on exposure control and necessary personal protective equipment.

SECTION 14 - Transportation Information
--

Ship according to the Department of Transportation (DOT) 49 CFR regulations.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
---------------	-----------------------------	------------------	----------------------	---------------------

Freight Class:

SECTION 15 - Regulatory Information
--

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This product contains the following listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

- None

The following ingredients are listed in the TSCA Section 8(b) Inventory (Hydrated forms of chemical substances are exempt from the inventory as mixtures; the anhydrous chemical substances, however, are reportable for the inventory):

111-76-2 2-BUTOXYETHANOL
29911-28-2 2-Propanol, 1-(2-butoxy-1-methylethoxy)-
7732-18-5 Water

US CAA Section 112 Hazardous Air Pollutants (HAPs) List

- None

US EPCRA (SARA Title III) Section 313 - Toxic Chemical:

- None

Hazardous Material Information System (HMIS)

HEALTH	<input type="text" value="3"/>
FLAMMABILITY	<input type="text" value="2"/>
PHYSICAL HAZARD	<input type="text" value="0"/>
PERSONAL PROTECTION	<input checked="" type="checkbox"/>

HMIS & NFPA Hazard Rating
Legend
 * = Chronic Health Hazard
 0 = INSIGNIFICANT
 1 = SLIGHT
 2 = MODERATE
 3 = HIGH

SECTION 16 - Disclaimer

Date Prepared: 8/2/2018

Date revised: 2018-04-05

Reviewer Revision 1

THIS DOCUMENT SUPERSEDES ANY PROVISION CONTAINED IN THE FORMS, LETTERS, AND PAPERS OF YOUR COMPANY. THIS PRODUCT IS DESIGNED AND INTENDED FOR PROFESSIONAL APPLICATION ONLY. ALL PRODUCTS SHOULD BE THOROUGHLY TESTED UNDER APPLICATION CONDITIONS PRIOR TO USE. THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE RELIABLE. HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED. INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OR WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.