



Safety Data Sheet

GEM VAR CONV. VARNISH, GLOSS, WHITE



1. Identification

Product identifier	GEM VAR CONV. VARNISH, GLOSS, WHITE		
Product code	UCV-1090		
Other means of identification	None.		
Recommended use of the chemical and restrictions on use	A protective and/or decorative finish or accompanying paint product. Not recommended for any other use not detailed on product data sheet or label.		
Manufacturer	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 USA Tel. 1-800-262-5710 Fax 1-405-262-9310 www.geminicoatings.com	Distributor	Gemini Industries, Inc. 850 Flint Road Toronto, Ontario Canada M3J 2T7 Tel. 1-800-262-5710
Emergency phone number	24-hour Emergency (Spill, Leak, Exposure or accident) INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English) HAZMAT Response and MSDS Help: EMI 800-510-8510		

2. Hazard identification

Summary	Highly flammable liquid and vapour. Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved.
----------------	---

WHMIS 2015/OSHA HCS 2012/GHS

Flammable liquids (Category 2)
 Skin corrosion/irritation (Category 2)
 Serious eye damage/eye irritation (Category 1)
 Respiratory sensitizer (Category 1)
 Skin sensitizer (Category 1)
 Germ cell mutagenicity (Category 1)
 Carcinogenicity (Category 1)
 Reproductive toxicity (Category 1)
 Specific target organ toxicity, single exposure (Category 3)
 Specific target organ toxicity, repeated exposure (Category 2)

Other hazards which do not result in classification :
 Acute hazard to the aquatic environment (Category 2).



DANGER

H225: Highly flammable liquid and vapour
 H318: Causes serious eye damage
 H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled

H350: May cause cancer
H340: May cause genetic defects
H360: May damage fertility or the unborn child
H315: Causes skin irritation
H317: May cause an allergic skin reaction
H335: May cause respiratory irritation
H336: May cause drowsiness or dizziness
H373: May cause damage to organs through prolonged or repeated exposure by inhalation
H401: Toxic to aquatic life
P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.
P240: Ground or bond container and receiving equipment.
P241: Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe mist, vapours and spray.
P264: Wash face, hands and any exposed skin thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.
P273: Avoid release to the environment.
P280: Wear protective gloves, protective clothing and eye protection.
P284: In case of inadequate ventilation, wear respiratory protection.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or take a shower if necessary.
P333+313: If skin irritation or a rash occurs: Get medical advice/attention.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P342+311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor/physician.
P308+313: IF exposed or concerned: Get medical advice/attention.
P321: Specific treatment (see section 4 of SDS or on this label).
P362+364: Take off contaminated clothing and wash before reuse.
P370+378: In case of fire: Use the National Fire Protection Association Class B extinguisher for extinction.
P403+P235+P233: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P405: Store locked up.
P501: Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

3. Composition/information on ingredients

Common name	CAS	Weight % content
Titanium dioxide	13463-67-7	18 - 20 %
n-Butyl Alcohol	71-36-3	13 - 15 %
Butyl acetate (normal)	123-86-4	9.5 - 10.5 %
Ethyl Alcohol	64-17-5	9.5 - 10.5 %
Xylene	1330-20-7	5.5 - 6.5 %
Propylene glycol monomethyl ether	107-98-2	4.5 - 5.5 %
Cellulose acetate butyrate	9004-36-8	3.5 - 4.5 %
Ethylene glycol monopropyl ether	2807-30-9	1.5 - 2.5 %
Methyl Propyl Ketone	107-87-9	0.5 - 1.5 %
Amorphous silica	7631-86-9	0.5 - 1.5 %
Aluminium hydroxide	21645-51-2	0.5 - 1.5 %

Ethylbenzene	100-41-4	0.5 - 1.5 %
Formaldehyde	50-00-0	0.1 - 0.5 %

4. First-aid measures

Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
Skin contact	Wash skin with warm water and mild soap for at least 15 minutes. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.
Eye contact	IMMEDIATELY! Flush with water for at least 15 minutes. Remove contact lenses. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If victim is conscious wash out mouth with water and give 1-2 glasses of water to drink. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.
Other	No information available.
Symptoms	May cause severe eye irritation or eye damage. May cause redness, dryness, rash and skin irritation. May cause irritation to nose, throat and respiratory tract. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. May cause an allergic reaction of the skin. May cause an allergic respiratory reaction with symptoms similar to asthma such as wheezing and chest tightness.
Notes to the physician	Treat symptomatically. If gastric lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire-fighting measures

Suitable extinguishing media	Class B extinguishers. Dry chemicals, alcohol resistant foam, carbon dioxide (CO ₂). Do not use direct water jet.
Specific hazards arising from the chemical	Highly flammable liquid and vapour. Vapours are heavier than air and may travel to an ignition source distant from the material handling point. May be ignited by heat, sparks, flame or static electricity. Do not apply to hot surfaces. Contact with strong oxidizers may cause fire. In a fire or if heated, a pressure increase will occur and the container may burst.
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
Special protective actions for fire-fighters	Use water spray to cool fire-exposed containers. Water spray can reduce the intensity of the flames. However, the water jets can spread the fire. If water is used, fog nozzles are preferable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
Environmental precautions	Prevent entry in sewer and other enclosed area. For a large spill, consult the Department of Environment or the relevant authorities.

Methods and materials for containment and cleaning up	Remove sources of ignition. Ventilate the area well. Stop leak, if it's possible to do so without risk. Absorb with inert material (soil, sand, vermiculite) and place in an appropriate waste disposal clearly identified. Use non-sparking and antistatic tools. Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water. PS: Rags and others materials soaked with paint or solvent may spontaneously catch fire if improperly store or discarded. Immediately after each use place rags and paper towels in a sealed water-filled metal container to prevent spontaneous combustion.
--	---

7. Handling and storage

Precautions for safe handling	Keep away from heat, sparks and open flame. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Use non-sparking and antistatic tools. Ground/bond all containers when transferring large quantities (5 gallons US or 20 L and more). Use only in well ventilated area. Avoid prolonged or repeated breathing of vapour or mists. Avoid contact with skin, eyes and clothing. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. Keep containers tightly closed when not in use. Containers of this material may be hazardous even when empty. Since empty containers retain product residues (vapour, liquid), all hazard precautions given in this sheet must be observed. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse. Rags, steel wool and paper towels soaked with this product may overheat and spontaneously ignite if piled in a heap. After use immediately store them in water-filled metal can with tight fitting lid.
Conditions for safe storage, including any incompatibilities	Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10). Keep away from direct sunlight and heat.
Storage temperature	10 to 25°C (50 to 77°F)

8. Exposure controls/personal protection

Immediately Dangerous to Life or Health	Titanium dioxide: 5000 mg/m ³ . Ethyl alcohol: 3300 ppm. n-Butyl Alcohol: 1400 ppm. Synthetic Amorphous Fumed Silica: 3000 mg/m ³ . Methyl Propyl Ketone: 1500 ppm. Xylenes: 900 ppm. Ethylbenzene: 800 ppm. n-Butyl acetate: 1700 ppm. Formaldehyde: 20 ppm.				
Titanium dioxide	TWA (8h)	Total Dust		10 mg/m ³	ACGIH , BC, ON, RSST
n-Butyl Alcohol	Ceiling		30 ppm		BC
			50 ppm	152 mg/m ³	RSST (Pc, RP)
	TWA (8h)		15 ppm		BC
			20 ppm		ACGIH , ON
Ethyl Alcohol	STEL		1000 ppm		ACGIH , BC, ON
	TWA (8h)		1000 ppm	1880 mg/m ³	RSST
Butyl acetate (normal)	STEL		200 ppm		ACGIH , ON
			200 ppm	950 mg/m ³	RSST
	TWA (8h)		20 ppm		BC
			150 ppm		ACGIH , ON
			150 ppm	713 mg/m ³	RSST
Xylene	STEL		150 ppm		ACGIH , BC, ON

Propylene glycol monomethyl ether	TWA (8h)	150 ppm	651 mg/m ³	RSST
		100 ppm		ACGIH , BC, ON
		100 ppm	434 mg/m ³	RSST
	STEL	75 ppm		BC
		100 ppm		ACGIH
		150 ppm		ON
Amorphous silica	TWA (8h)	150 ppm	553 mg/m ³	RSST
		50 ppm		ACGIH , BC
		100 ppm		ON
	Respirable Dust	100 ppm	369 mg/m ³	RSST
		3 mg/m ³		ACGIH , BC
Ethylbenzene	STEL	Respirable Dust	6 mg/m ³	RSST
		Total Dust	10 mg/m ³	ACGIH , BC, ON
		125 ppm	543 mg/m ³	RSST
Aluminium hydroxide	TWA (8h)	20 ppm		ACGIH , BC, ON
		100 ppm	434 mg/m ³	RSST
		Respirable Dust	1 mg/m ³	ACGIH , BC, ON
Methyl Propyl Ketone	Ceiling	Total Dust	10 mg/m ³	RSST
		150 ppm		ACGIH , ON
		250 ppm		BC
Formaldehyde	TWA (8h)	150 ppm		BC
		0.3 ppm	530 mg/m ³	RSST
		0.37 mg/m ³		ACGIH
	STEL	1 ppm		BC
		1.5 ppm		ON
		2 ppm	3 mg/m ³	RSST (C2, EM, RP)
TWA (8h)	0.3 ppm		BC	

Appropriate engineering controls	Provide sufficient mechanical ventilation (general and/or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.
Individual protection measures	
Eye	Wear chemical splash goggles.
Hands	Wear nitrile or neoprene gloves. Disposable nitrile gloves can also be used, but discard after single use. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly.
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. If necessary, wear an apron or long-sleeve protective coverall suit.
Respiratory	Respiratory protection is not required for normal use. Where the conditions in the workplace require a respirator, it is necessary to follow a respiratory protection program. Moreover, respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and standard 29 CFR 1910.134 (OSHA), ANSI Z88.2 or CSA Z 94.11 (Canada) and approved by NIOSH/MSHA. In case of insufficient ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times the exposure limit, wear a half mask respirator with organic vapour cartridges fitted with P100 filters. For an APF until maximum 100 times of exposure limit, wear a full face respirator mask with organic vapour cartridges and P100 filters.
Feet	Wear rubber boots to clean up a spill.

9. Physical and chemical properties

Physical state	Liquid	Flammability	Flammable
Colour	White	Flammability limits	N/Av.
Odour	Solvent	Flash point	21 °C (69.8 °F)
Odour threshold	N/Av.	Auto-ignition temperature	287 °C (548.6 °F)
pH	N/Av.	Sensibility to electrostatic charges	Yes
Melting point	N/Av.	Sensibility to sparks and/or friction	No
Freezing point	N/Av.	Vapour density	>1 (Air = 1)
Boiling point	78 to 132 °C (172.4 to 269.6 °F)	Relative density	1.127 kg/L (Water = 1)
Solubility	Partially soluble in water.	Partition coefficient n-octanol/water	N/Av.
Evaporation rate	> Butyl Acetate	Decomposition temperature	N/Av.
Vapour pressure	N/Av.	Viscosity	N/Av.
Percent Volatile	51.7%	Molecular mass	N/Av.
N/Av.: Not Available N/Av.: Not Applicable Und.: Undetermined N/E: Not Established			

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions (including polymerizations)	A dangerous reaction will not occur.
Conditions to avoid	Avoid heat, flame and sparks. Avoid contact with incompatible materials.
Incompatible materials	Strong bases, mineral acids, strong oxidizing agents (e.g. nitric acid, perchloric acid, peroxides, chlorates and perchlorates).
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Numerical measures of toxicity	Titanium dioxide	Ingestion	>10000 mg/kg	Rat	LD50
		Inhalation	>6.82 mg/l/4h	Rat	LC50
		Skin	>10000 mg/kg	Rabbit	LD50
	n-Butyl Alcohol	Ingestion	790 mg/kg	Rat	LD50
		Inhalation	24.2 mg/l/4h	Rat	LC50
		Skin	3400 mg/kg	Rabbit	LD50
	Butyl acetate (normal)	Ingestion	10768 mg/kg	Rat	LD50
		Inhalation	>32.5 mg/l/4h	Rat	LC50
		Skin	>17600 mg/kg	Rabbit	LD50
	Ethyl Alcohol	Ingestion	7060 mg/kg	Rat	LD50

	Xylene	Inhalation	39 mg/l/4h	Mouse	LC50
		Skin	20000 mg/kg	Rabbit	LD50
		Ingestion	3523 mg/kg	Rat	LD50
	Propylene glycol monomethyl ether	Inhalation	27.6 mg/l/4h	Rat	LC50
		Skin	3200 mg/kg	Rabbit	LD50
		Ingestion	6600 mg/kg	Rat	LD50
	Cellulose acetate butyrate	Inhalation	36.4 mg/l/4h	Rat	LC50
		Skin	13000 mg/kg	Rabbit	LD50
		Ingestion	>3200 mg/kg	Rat	LD50
	Ethylene glycol monopropyl ether	Skin	>1000 mg/kg	Guinea pig	LD50
		Ingestion	3089 mg/kg	Rat	LD50
		Inhalation	>11.13 mg/l/4h	Rat	LC50
	Ethylbenzene	Skin	883 mg/kg	Rabbit	LD50
		Ingestion	3500 mg/kg	Rat	LD50
		Inhalation	17.3 mg/l/4h	Rat	LC50
	Aluminium hydroxide	Skin	15380 mg/kg	Rabbit	LD50
		Ingestion	>5000 mg/kg	Rat	LD50
		Skin	>2000 mg/kg	Rabbit	LD50
	Methyl Propyl Ketone	Ingestion	3730 mg/kg	Rat	LD50
			1600 mg/kg	Mouse	LD50
		Inhalation	11 mg/l/4h	Rat	LC50
Amorphous silica	Skin	6472 mg/kg	Rabbit	LD50	
	Ingestion	>3300 mg/kg	Rat	LD50	
	Inhalation	>2 mg/l/4h	Rat	LC50	
Formaldehyde	Skin	>5000 mg/kg	Rabbit	LD50	
	Ingestion	42 mg/kg	Mouse	LD50	
	Inhalation	250 ppm/4h	Rat	LC50	
		414 ppm/4h	Mouse	LC50	
	Skin	270 mg/kg	Rabbit	LD50	

Likely routes of exposure

Skin, eyes, inhalation, ingestion.

Delayed, immediate and chronic effects

Eye contact	May cause severe eye irritation or eye damage. Butyl Alcohol instilled in rabbit eyes resulted in severe corneal irritation and eye damage (OECD 405). Application in excess of 5% dilution solution gave irritating effect. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with the other ingredients of this mixture gave not irritating to irritating results.
Skin contact	May cause redness, dryness, rash and skin irritation. Prolonged and repeated contact may cause dry skin, irritation or dermatitis. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient of this mixture gave not irritating to irritating results. Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed.
Inhalation	May cause irritation to nose, throat and respiratory tract. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. May cause an allergic respiratory reaction with symptoms similar to asthma such as wheezing and chest tightness. The severity of symptoms may vary depending on exposure conditions. Repeated and prolonged occupational overexposure to solvents may cause brain and nervous system damage.
Ingestion	Ingestion of large amounts may cause depression of the central nervous system characterized by headache, dizziness, convulsions and loss of consciousness.
Respiratory or skin sensitization	Aqueous formaldehyde solutions cause skin sensitization. However, free formaldehyde gas does not cause skin sensitization. Formaldehyde can cause asthma attacks due to allergic sensitization of the respiratory tract.
IARC/NTP Classification	Common name IARC NTP Titanium dioxide 2B - Ethylbenzene 2B - Amorphous silica - -


	<p>Formaldehyde 1 R IARC : 1- Carcinogenic; 2A- Probably carcinogenic; 2B- Possibly carcinogenic. NTP : K- Known to be carcinogens; R- Reasonably anticipated to be carcinogens.</p>
Carcinogenicity	<p>Contains material which can cause cancer. Titanium dioxide in dust form can cause cancer based on animal data. Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint and caulk. There is sufficient evidence for the carcinogenicity of alcoholic (Ethanol) beverages in humans (IARC). The occurrence of malignant tumors of the oral cavity, pharynx, larynx, oesophagus, liver, breast and colorectal is causally related to the excessive consumption of alcoholic beverages. However, the possibility of such effects occurring is for chronic consumers of ethyl alcohol. The risk of cancer depends on duration and level of exposure. There is sufficient evidence in humans for the carcinogenicity of occupational exposure as a painter (IARC Group 1). Occupational exposure as a painter causes mesothelioma, and cancers of the urinary bladder and lung (IARC Monographs, Volume 100F (2012)).</p>
Mutagenicity	<p>Ethyl Alcohol has showed positive results in dominant lethal tests by oral and intraperitoneal administration to mice and oral administration to rats (in vivo heritable germ cell mutagenicity tests) (SIDS (2009), IARC (1988)). There are also reports of negative Ames tests from in vitro mutagenicity tests SIDS (2009). Formaldehyde has positive data on somatic cell mutagenicity tests in vivo (SIDS).</p>
Reproductive toxicity	<p>Possible effects on reproduction (ethanol). A significant and prolonged consumption of ethyl alcohol during pregnancy can cause an increased risk of developmental abnormalities fetus humans. Xylene overexposure may affect fetal development in laboratory animals by inhalation during pregnancy.</p>
Specific target organ toxicity - single exposure	<p>Central nervous system, respiratory system.</p>
Specific target organ toxicity - repeated exposure	<p>Hearing organs, central nervous system, liver, kidneys.</p>
Interactive effects	<p>No information available for this product.</p>
Other information	<p>The oral and skin acute toxicity estimates (ATE) of the mixture were calculated to be greater than 2000 mg/kg. The acute toxicity estimate (ATE) by inhalation of the mixture was calculated to be greater than 20 mg/L/4h. These values are not classified according to WHMIS 2015 and OSHA HCS 2012.</p>

12. Ecological information

Ecological toxicity	<p>Fish - Pimephales promelas [flow-through] LC50 13400-15100 mg/L; 96 h (ethyl alcohol) Aquatic Invertebrate - Daphnia magna EC50 9268-14221 mg/L; 48 h (ethyl alcohol) Fish - Pimephales promelas - Fresh water LC50 >500 mg/L; 96 h (Titanium dioxide) Aquatic Invertebrates - Daphnia pulex EC50 9.2 mg/L; 48 h (Titanium dioxide) Fish - Pimephales promelas [static] LC50 376 mg/L; 96h (n-Butyl Alcohol) OECD 203 Aquatic Invertebrate - Daphnia magna EC50 1983 mg/L; 48 h (n-Butyl alcohol) Algae - Desmodesmus subspicatus EC50 >500 mg/L; 72 h (n-Butyl alcohol) Fish - Pimephales promelas [flow-through] LC50 18 mg/L; 96h (Butyl acetate) Algae, Desmodesmus subspicatus EC50 675 mg/L; 72h (Butyl acetate) Fish - Pimephales promelas [static] LC50 20800 mg/L; 96h (CAS no 107-98-2) Aquatic Invertebrate - Daphnia magna EC50 23300 mg/L; 48h (CAS no 107-98-2) Algae, Selenastrum capricornutum EC50 >1000 mg/L; 96h (CAS no 107-98-2) Fish - Oncorhynchus mykiss - Rainbow trout LC50 13.5-17.3 mg/L; 96 h (Xylene) Aquatic Invertebrate - Daphnia magna EC50 3.82 mg/L; 48 h (Xylene) Fish - Pimephales promelas [flow-through] LC50 1190-1290 mg/L; 96 h (methyl propyl ketone) Aquatic Invertebrate - Daphnia magna EC50 >110 mg/L; 96 h (methyl propyl ketone) OECD 202 Fish - Oncorhynchus mykiss - Rainbow trout LC50 4.2 mg/L; 96 h (Ethylbenzene)</p>
----------------------------	--

	<p>Aquatic invertebrate - Crangon franciscorum EC50 0.49 mg/L; 48 h (Ethylbenzene)</p> <p>Fish - Pimephales promelas - Fresh water LC50 20800 mg/L; 96 h (Ethylene glycol monopropyl ether)</p> <p>Aquatic Invertebrate - Daphnia magna EC50 23300 mg/L; 48 h (Ethylene glycol monopropyl ether)</p>
Persistence	The product contains components that may persist in the environment.
Degradability	The term biodegradability, as such, is not applicable to inorganic compounds like Titanium dioxide. n-Butyl Alcohol is readily biodegradable. Degradation by Biochemical Oxygen Demand BOD (O ₂ consumption) was reported as 92% after 20 days. Ethanol is readily biodegradable under aerobic and anaerobic conditions (OECD Test Guideline 301D). n-Butyl acetate is readily biodegradable (96% in 28 days) OECD Guideline 301D. Propylene glycol monomethyl ether is ready biodegradable, 73%-91% during 28 days (OECD TG 301F). Xylene in air is rapidly decomposed by photochemical processes, mainly through oxidation by hydroxyle free radicals as well as some decomposition by direct photolysis. The half-life time in air is estimated to be from 9.5 to 19.7 hours depending to the isomer. Xylene is readily biodegradable at 68% in 10 days and at 88% in 28 days (OECD Guideline 301F) with BOD ₅ /COD ratio of 0.97 (IUCLID). Methyl propyl ketone (CAS no 107-87-9) has been shown to readily biodegrade at 70% under aerobic and conditions (OCDE TG 301D). Ethylbenzene is biodegraded fairly rapidly by sewage or activated sludge (TOXNET).
Bioaccumulative potential	N-Butyl alcohol has a Bioconcentration Factor (BCF) value of 3, and its Log Kow value is from 0.8 to 1, indicating its potential to bioaccumulate is very low. Ethanol has a Bioconcentration Factor (BCF) value of <10, and its Log Kow value is <0, indicating its potential to bioaccumulate is low. n-Butyl acetate has a low potential for bioaccumulation based on estimated bioconcentration factors (BCF) of 15.3 and low partition coefficient (Log Kow 2.3). Propylene glycol monomethyl ether has a Bioconcentration Factor (BCF) of 2.2 and a partition factor Log Kow of -0.49, indicating no potential for bioconcentration in aquatic organisms (TOXNET). Xylene has Bioconcentration Factor (BCF) of of 6 to 23.4 and a partition factor Log Kow of 3.1 to 3.2, depending to the isomer. These values suggest a low potential of bioaccumulation (TOXNET). Methyl propyl ketone (CAS no 107-87-9) is soluble in water and has a low Bioconcentration Factor (BCF) of 3 and a log Kow of 0,93. Methyl propyl ketone is not be expected to accumulate in food chains. Ethylbenzene has a low potential for bioaccumulation (BCF) of 1.1 to 15 were measured in four species of fish. It has low water solubility and a moderate partition coefficient (Log Kow of 3.15).
Mobility in soil	N-Butyl alcohol is soluble in water. The estimated Koc value of 3.2 suggests that it is expected to have very high mobility in soil. Ethanol is very soluble in water. The resultant Koc of 1 indicates that ethanol released in soil would move quickly through the soil. It will be distributed mainly in the atmosphere (57%) and water (34%). n-Butyl acetate will be distributed to air (93.4%), water (5.78%), soil (0.792%), and sediment (<0.1%). The Koc value of n-butyl acetate can be estimated to be 19, suggesting that it is expected to have very high mobility in soil. Propylene glycol monomethyl ether is very soluble is water. Then, it is expected to have very high mobility in soil. Xylene will rapidly evaporate into the atmosphere because of its low soil absorption and its low solubility in water. Koc values range from 39-365 for the individual isomers. These values suggest that xylenes are expected to have high to moderate mobility in soil (TOXNET). Methyl propyl ketone (CAS no 107-87-9) can be volatilized from moist soil surfaces (SRC). The estimated Koc value of 75 indicates that it is expected to have high mobility in soil. Ethylbenzene is expected to have a moderate mobility in soil with an estimated Koc value of 520 (TOXNET).
Other adverse effects	This chemical does not deplete the ozone layer.

13. Disposal considerations

	<p>Container Important! Prevent waste generation. Use in full. DO NOT dispose residue in sewers, streams or drinking water supply. Paint residues, including lacquers, stains, shellac, varnish, solvents and paint thinners, can be reprocessed (recycle) anywhere there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.</p>
--	--

			CER CLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Prio.
Titanium dioxide	13463-67-7	X								
n-Butyl Alcohol	71-36-3	X	X	X					X	
Butyl acetate (normal)	123-86-4	X	X						X	
Ethyl Alcohol	64-17-5	X								
Xylene	1330-20-7	X	X	X		X	X		X	
Propylene glycol monomethyl ether	107-98-2	X				X				
Cellulose acetate butyrate	9004-36-8	X								
Ethylene glycol monopropyl ether	2807-30-9	X				X				
Methyl Propyl Ketone	107-87-9	X								
Amorphous silica	7631-86-9	X								
Aluminium hydroxide	21645-51-2	X								
Ethylbenzene	100-41-4	X	X	X		X	X		X	X
Formaldehyde	50-00-0	X	X	X	X	X	X	X	X	

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act - Hazardous Organic National Emission Standard for Hazardous Air Pollutant
- CAA 112(b) HAP: Clean Air Act - Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act - Regulated Chemicals for Accidental Release Prevention
- CWA 311: Clean Water Act - List of Hazardous Substances
- CWA Priority: Clean Water Act - Priority Pollutant list

California Proposition 65

Common name	CAS	Cancer	Reproductive and Developmental Toxicity
Titanium dioxide	13463-67-7	X	
Ethyl Alcohol	64-17-5	X	X
Ethylbenzene	100-41-4	X	
Formaldehyde	50-00-0	X	

Other regulations

WHMIS 1988



B2 D2A D2B

Class B2 : Flammable Liquid

Class D2A : Very toxic material causing other toxic effects

Class D2B : Toxic material causing other toxic effects

HMIS



NFPA



16. Other information

Date (YYYY-MM-DD)	GEMINI INDUSTRIES, INC. 2016-07-04
Version	01
Other information	<p>- The GHS hazards classification in this SDS is from the original SDS provided by the manufacturer.</p> <p>REFERENCES:</p> <ul style="list-style-type: none">- Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, http://hazmap.nlm.nih.gov/index.php- TOXNET Databases, Toxicology Data Network, NIH U.S. National Library of Medicine, http://toxnet.nlm.nih.gov/- Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), http://www.reptox.csst.qc.ca- NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, http://www.cdc.gov/niosh/npg/npg.html- IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), http://www.inchem.org- OECD Existing Chemicals Database, Chemicals Screening Information DataSet (SIDS) for High Volume Chemicals, UNEP publications, http://webnet.oecd.org/HPV/UI/Search.aspx <p>ACGIH: American Conference of Governmental Industrial Hygienists AIHA: American Industrial Hygiene Association HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association OSHA: Occupational Safety and Health Administration (USA) NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program RSST: Règlement sur la santé et la sécurité du travail (Québec) GHS: Globally Harmonized System IARC: International Agency for Research on Cancer IDLH: Immediately Dangerous to Life or Health STEL: Short Term Exposure Limit (15 min) TWA: Time Weighted Averages WHMIS: Workplace Hazardous Materials Information System</p> <p>To the best of our knowledge, the information contained herein is accurate. However, neither Préventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.</p>