



# Safety Data Sheet

## WHITE GLOSS LACQUER



### 1. Identification

<b>Product identifier</b>	WHITE GLOSS LACQUER		
<b>Product code</b>	400-0210		
<b>Other means of identification</b>	N/Av.		
<b>Recommended use of the chemical and restrictions on use</b>	PAINT.		
<b>Manufacturer</b>	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 USA  Tel. 1-800-262-5710 Fax 1-405-262-9310 <a href="http://www.gemini-coatings.com">www.gemini-coatings.com</a>		
<b>Emergency phone number</b>	INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English) 24-hour  HAZMAT Response and MSDS help: EMI 800-510-8510		

### 2. Hazard identification

<b>Summary</b>	DANGER! FLAMMABLE LIQUID! TOXIC! Skin, eyes and respiratory tracts irritant. Harmful if inhaled. May be harmful by skin contact. May cause an allergic reaction of the skin. Contains a substance that can cause target organ damage, according to data obtained on animals. Contains a substance that can cause cancer based on animal data. Reproductive effects in animal. Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet. After use, wash hands with soap and water. Wash contaminated clothing before reuse.
----------------	---

#### WHMIS 2015/OSHA HCS 2012/GHS



- Flammable liquids (Category 2)
- Acute toxicity, inhalation (Category 4)
- Skin irritation (Category 2)
- Eye irritation (Category 2A)
- Skin sensitizer (Category 1)
- Carcinogenicity (Category 2)
- Reproductive toxicity (Category 2)
- Specific target organ toxicity, single exposure, Narcotic effects (Category 3)
- Specific target organ toxicity, repeated exposure (Category 2)
- Aspiration hazard (Category 1)

#### DANGER

- H225: Highly flammable liquid and vapour
- H304: May be fatal if swallowed and enters airways
- H332: Harmful if inhaled
- H319: Causes serious eye irritation
- H315: Causes skin irritation

H317: May cause an allergic skin reaction  
H336: May cause drowsiness or dizziness  
H351: Suspected of causing lung cancer by inhalation of dust  
H361D: Suspected of damaging the unborn child  
H373: May cause damage to organs through prolonged or repeated exposure  
P201: Obtain special instructions before use.  
P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.  
P240: Ground or bond container and receiving equipment.  
P241: Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P260: Do not breathe mist, vapours and spray.  
P264: Wash skin thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P271: Use only outdoors or in a well-ventilated area.  
P272: Contaminated work clothing should not be allowed out of the workplace.  
P280: Wear protective gloves, protective clothing and eye protection.  
P308+313: IF exposed or concerned: Get medical advice/attention.  
P301+310+331: IF SWALLOWED: Immediately call a POISON CENTER or a physician. Do NOT induce vomiting.  
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or take a shower if necessary.  
P333+313: If skin irritation or a rash occurs: Get medical advice or attention.  
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P312: Call a POISON CENTER or doctor/physician if you feel unwell.  
P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.  
P337+313: If eye irritation persists: Get medical advice or attention.  
P321: Specific treatment (see section 4 of SDS or on this label).  
P362+364: Take off contaminated clothing and wash before reuse.  
P370+378: In case of fire: Use the National Fire Protection Association Class B extinguisher to extinguish.  
P403+P235+P233: Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
P405: Store locked up.  
P501: Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

### 3. Composition/information on ingredients

Common name	CAS	Weight % content
Toluene	108-88-3	30 - 60 %
Rosin, maleated, polymer with glycerol	68038-41-5	10 - 20 %
Butyl acetate (normal)	123-86-4	7 - 13 %
Titanium dioxide	13463-67-7	7 - 13 %
Bis(2-Ethylhexyl) adipate	103-23-1	5 - 10 %
Acetone	67-64-1	5 - 10 %
Methanol	67-56-1	3 - 7 %
Nitrocellulose	9004-70-0	3 - 7 %
Isopropyl alcohol	67-63-0	1 - 5 %
2-Butoxyethanol	111-76-2	1 - 5 %
Ethyl Alcohol	64-17-5	0.1 - 1 %

## 4. First-aid measures

<b>Inhalation</b>	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
<b>Skin contact</b>	Wash skin with warm water and mild soap. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.
<b>Eye contact</b>	IMMEDIATELY flush with plenty of water. Remove contact lenses. Flush with water for at least 15 minutes. Hold eyelids apart to rinse properly. Seek medical attention immediately.
<b>Ingestion</b>	DO NOT induce vomiting, unless recommended by medical personnel. If victim is conscious wash out mouth with water. Never give anything by mouth if victim is unconscious or convulsing. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.
<b>Other</b>	No information available.
<b>Symptoms</b>	May cause redness and irritation of the skin and to eyes. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. May cause an allergic reaction of the skin.
<b>Notes to the physician</b>	Treat symptomatically. If gastric lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	dried powder, carbon dioxide (CO <sub>2</sub> ), alcohol resistant foam, Do not use a heavy water jet.
<b>Specific hazards arising from the chemical</b>	NFPA: Class IB Flammable liquid. Vapours are heavier than air and may travel to an ignition source distant from the material handling point. May be ignited by heat, sparks, flame or static electricity. Do not apply to hot surfaces. Contact with strong oxidizers may cause fire. In a fire or if heated, a pressure increase will occur and the container may burst. Emits toxic fumes under fire conditions.
<b>Special protective equipment</b>	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
<b>Special protective actions for fire-fighters</b>	Water stream can scatter and spread fire. If water is used, fog nozzles are preferable. Use water spray to cool fire-exposed containers.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
<b>Environmental precautions</b>	Prevent entry in sewer and other enclosed area. For a large spill, consult the Department of Environment or the relevant authorities.
<b>Methods and materials for containment and cleaning up</b>	Remove sources of ignition. Ventilate the area well. Stay against the wind spill. Make sure you have a fire extinguisher near you. Stop leak, if it's possible to do so without risk. Use non-sparking and antistatic tools. Absorb with inert material (soil, sand, vermiculite) or wipe up or scrape up and place in an appropriate waste disposal container clearly identified. Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Keep away from heat, sparks and open flame. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Use non-sparking and antistatic tools. Ground/bond all containers when transferring large quantities (5 gallons US or 20 L and more). Use only in well ventilated area. Avoid prolonged or repeated breathing of vapour or mists. Avoid contact with skin, eyes and clothing. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet. Keep containers tightly closed when not in use. Containers of this material may be hazardous even when empty. Since empty containers retain product residues (vapour, liquid), all hazard precautions given in this sheet must be observed. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse.
<b>Conditions for safe storage, including any incompatibilities</b>	Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). NFPA: Class IB Flammable liquid. Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10).
<b>Storage temperature</b>	10 to 25°C (50 to 77°F)

## 8. Exposure controls/personal protection

<b>Immediately Dangerous to Life or Health</b>	Isopropyl alcohol: 2000 ppm. Toluene : 500 ppm. Titanium dioxide: 5000 mg/m <sup>3</sup> . n-Butyl acetate: 1700 ppm. 2-Butoxyethanol: 700 ppm. Methanol : 6000 ppm. Ethyl alcohol: 3300 ppm. Acetone: 2500 ppm.			
Toluene	STEL	150 ppm	560 mg/m <sup>3</sup>	OSHA
	TWA (8h)	20 ppm		ACGIH , BC, ON
		50 ppm	188 mg/m <sup>3</sup>	AB , RSST
		100 ppm	375 mg/m <sup>3</sup>	OSHA
Titanium dioxide	TWA (8h) Total Dust		10 mg/m <sup>3</sup>	AB , ACGIH, BC, ON, RSST
Butyl acetate (normal)	STEL	200 ppm		ACGIH , ON
		200 ppm	950 mg/m <sup>3</sup>	AB , OSHA, RSST
	TWA (8h)	20 ppm		BC
		150 ppm		ACGIH , ON
		150 ppm	710 mg/m <sup>3</sup>	OSHA
		150 ppm	713 mg/m <sup>3</sup>	AB , RSST
Acetone	STEL	500 ppm		ACGIH , BC
		750 ppm		ON
		1000 ppm	2380 mg/m <sup>3</sup>	RSST
		1000 ppm	2400 mg/m <sup>3</sup>	OSHA
	TWA (8h)	250 ppm		ACGIH , BC
		500 ppm		ON
		500 ppm	1190 mg/m <sup>3</sup>	RSST
		750 ppm	1782 mg/m <sup>3</sup>	OSHA
Methanol	STEL	250 ppm		ACGIH , BC, ON
		250 ppm	328 mg/m <sup>3</sup>	AB , RSST
	TWA (8h)	200 ppm		ACGIH , BC, ON
		200 ppm	260 mg/m <sup>3</sup>	OSHA
		200 ppm	262 mg/m <sup>3</sup>	AB , RSST
Isopropyl alcohol	STEL	400 ppm		ACGIH , BC, ON
		400 ppm	984 mg/m <sup>3</sup>	AB

2-Butoxyethanol	TWA (8h)	500 ppm	1230 mg/m <sup>3</sup>	RSST
		200 ppm		ACGIH , BC, ON
		200 ppm	492 mg/m <sup>3</sup>	AB
	TWA (8h)	400 ppm	980 mg/m <sup>3</sup>	OSHA
		400 ppm	983 mg/m <sup>3</sup>	RSST
		20 ppm		ACGIH , BC, ON
Ethyl Alcohol	TWA (8h)	20 ppm		AB , RSST
		50 ppm	240 mg/m <sup>3</sup>	OSHA
	STEL	1000 ppm		ACGIH , BC, ON
	TWA (8h)	1000 ppm	1880 mg/m <sup>3</sup>	AB , RSST
		1000 ppm	1900 mg/m <sup>3</sup>	OSHA
<b>Appropriate engineering controls</b>	Provide sufficient mechanical ventilation (general or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.			
<b>Individual protection measures</b>				
<b>Eye</b>	Wear safety glasses. If there is a risk of contact with eyes, wear chemical splash goggles.			
<b>Hands</b>	Wear nitrile or neoprene gloves. Disposable nitrile gloves can also be used, but discard after single use. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly.			
<b>Skin</b>	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. If necessary, wear an apron or long-sleeve protective coverall suit.			
<b>Respiratory</b>	Where the conditions in the workplace require a respirator, it is necessary to follow a respiratory protection program. Moreover, respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and standard 29 CFR 1910.134 (OSHA), ANSI Z88.2 or CSA Z 94.11 (Canada) and approved by NIOSH/MSHA. In case of insufficient ventilation or in enclosed area until maximum 10 times of exposure limit, wear half mask respirator with organic vapors cartridges and fitted with a particulate filter. Use a dust particle mask when sanding.			
<b>Feet</b>	Wear rubber boots to clean up a spill.			

## 9. Physical and chemical properties

<b>Physical state</b>	Liquid	<b>Flammability</b>	Flammable.
<b>Colour</b>	White or colored	<b>Flammability limits</b>	1.2 to 36%
<b>Odour</b>	Solvent odor	<b>Flash point</b>	4.4°C (39.9°F)
<b>Odour threshold</b>	N/Av.	<b>Auto-ignition temperature</b>	N/Av.
<b>pH</b>	N/Av.	<b>Sensibility to electrostatic charges</b>	Yes
<b>Melting point</b>	N/Av.	<b>Sensibility to sparks and/or friction</b>	N/Av.
<b>Freezing point</b>	N/Av.	<b>Vapour density</b>	>1 (Air = 1)
<b>Boiling point</b>	64°C (147.2°F)	<b>Relative density</b>	1.012 kg/L (Water = 1)
<b>Solubility</b>	No	<b>Partition coefficient n-octanol/water</b>	N/Av.
<b>Evaporation rate</b>	> Butyl Acetate		N/Av.

		<b>Decomposition temperature</b>	
<b>Vapour pressure</b>	N/Av.	<b>Viscosity</b>	N/Av.
<b>Percent Volatile</b>	73.94%	<b>Molecular mass</b>	N/Ap.
N/Av.: Not Available    N/Ap.: Not Applicable    Und.: Undetermined    N/E: Not Established			

## 10. Stability and reactivity

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under recommended storage conditions.
<b>Possibility of hazardous reactions (including polymerizations)</b>	A dangerous reaction will not occur.
<b>Conditions to avoid</b>	Avoid heat, flame and sparks. Avoid contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidants, strong bases, mineral acids, strong acids.
<b>Hazardous decomposition products</b>	In combustion: nitrogen oxides, carbon oxides (CO, CO <sub>2</sub> ).

## 11. Toxicological information

<b>Numerical measures of toxicity</b>	Toluene	Ingestion 5600 mg/kg	Rat	LD50
		Inhalation 30.2 mg/l/4h	Rat	LC50
		Skin 12600 mg/kg	Rabbit	LD50
	Rosin, maleated, polymer with glycerol	Ingestion >5000 mg/kg	Rat	LD50
		Skin >2000 mg/kg	Rabbit	LD50
	Butyl acetate (normal)	Ingestion 10768 mg/kg	Rat	LD50
		Inhalation >32.5 mg/l/4h	Rat	LC50
		Skin >17600 mg/kg	Rabbit	LD50
	Titanium dioxide	Ingestion >10000 mg/kg	Rat	LD50
		Inhalation >6.82 mg/l/4h	Rat	LC50
		Skin >10000 mg/kg	Rabbit	LD50
	Acetone	Ingestion 5800 mg/kg	Rat	LD50
		Inhalation 71.4 mg/l/4h	Rat	LC50
		Skin 15800 mg/kg	Rabbit	LD50
	Bis(2-Ethylhexyl) adipate	Ingestion 9100 mg/kg	Rat	LD50
		Inhalation >5.7 mg/l/4h	Rat	LC50
		Skin 17297 mg/kg	Rabbit	LD50
	Methanol	Ingestion 5600 mg/kg	Rat	LD50
		183 mg/kg	Human	
		Inhalation 83.8 mg/l/4h	Rat	LC50
		Skin 15800 mg/kg	Rabbit	LD50
	Nitrocellulose	Ingestion >5000 mg/kg	Rat	LD50
	Isopropyl alcohol	Ingestion 5045 mg/kg	Rat	LD50
		Inhalation 66.1 mg/l/4h	Rat	LC50
	Skin 6280 mg/kg	Rat	LD50	
2-Butoxyethanol	Ingestion 560 mg/kg	Rat	LD50	
	Inhalation 2.21 mg/l/4h	Rat	LC50	
	Skin 220 mg/kg	Rabbit	LD50	
Ethyl Alcohol	Ingestion 7060 mg/kg	Rat	LD50	
	Inhalation 39 mg/l/4h	Mouse	LC50	
	Skin 20000 mg/kg	Rabbit	LD50	

<b>Likely routes of exposure</b>	Skin, eyes, inhalation, ingestion.
<b>Delayed, immediate and chronic effects</b>	<p><b>Eye contact</b> May cause eye irritation.</p> <p><b>Skin contact</b> May cause slight irritation of the skin. Prolonged and repeated contact may cause drying and cracking of the skin. Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed.</p> <p><b>Inhalation</b> Excessive inhalation is harmful. May cause slight upper respiratory tract irritation. High concentrations may cause central nervous system depression characterized by headache, dizziness, nausea, fatigue, drowsiness, The severity of symptoms may vary depending on exposure conditions. Prolonged exposure may cause damage to liver, kidneys, lungs and blood forming organs.</p> <p><b>Ingestion</b> May cause gastro-intestinal irritation with nausea and vomiting. Contains a substance that can cause target organ damage, according to data obtained on animals. Harmful or fatal if inhaled into the lungs (ingestion/vomiting).</p> <p><b>Respiratory or skin sensitization</b> Rosin, maleated, polymer with glycerol (CAS no 68038-41-5) may be a skin sensitizer (guinea pigs; EPA - TSCATS, OECD 429). Rosin and some rosin derivatives have been reported to cause allergic skin reaction (sensitization) in susceptible individuals after repeated or prolonged contact.</p> <p><b>IARC/NTP Classification</b>  <b>Common name IARC NTP</b>  Titanium dioxide 2B -  IARC : 1- Carcinogenic; 2A- Probably carcinogenic; 2B- Possibly carcinogenic.  NTP : K- Known to be carcinogens; R- Reasonably anticipated to be carcinogens.</p> <p><b>Carcinogenicity</b> Contains an ingredient possibly carcinogenic to humans (Group 2B, IARC). The risk of cancer depends on duration and level of exposure. If material is to be dried and sanded by users, the risk of inhalation of dust will be increased, together with the risk of cancer hazard.</p> <p><b>Mutagenicity</b> Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause mutagenic effects.</p> <p><b>Reproductive toxicity</b> Toluene present a risk of toxicity on development based on animal study. An epidemiological study (1992) has been done with women exposed only to toluene in a factory. The first group was exposed to ambient concentrations from 50 to 150 ppm and the second at concentrations from 0 to 25 ppm. Comparison with a control group demonstrated a higher spontaneous abortions rates significantly in women exposed to higher concentrations than those of little or no exposure group.</p>
<b>Interactive effects</b>	No information available for this product.
<b>Other information</b>	Target organs: central nervous system, kidneys, liver, lungs. blood forming organs. The acute toxicity estimate (ATE) by inhalation of the mixture was calculated to be greater than 10 mg/L/4h but lower than 20 mg/L/4h. This value is classified according to GHS: Acute toxicity, inhalation (Category 4). The oral and skin acute toxicity estimates (ATE) of the mixture were calculated to be greater than 2000 mg/kg. These values are not classified according to WHMIS 2015 and OSHA HCS 2012.

## 12. Ecological information

<b>Ecological toxicity</b>	N/Av. LC50 N/Av.
<b>Persistence</b>	No information available for this product.
<b>Degradability</b>	No information available for this product.
<b>Bioaccumulative potential</b>	No information available for this product.
<b>Mobility in soil</b>	No information available for this product.
<b>Other adverse effects</b>	No information available for this product.

## 13. Disposal considerations

<b>Container</b> 	Important! Prevent waste generation. Use in full. DO NOT dispose residue in sewers, streams or drinking water supply. Paint residues including lacquer, thinner, stain, shellac, varnish, polish can be reprocessed everywhere there is a recycling program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.
--	---

## 14. Transport information

<b>UN Number</b>	UN 1263
<b>UN Proper Shipping Name</b>	PAINT
<b>Environmental hazards</b>	This material is not listed as a marine pollutant.
<b>Special precautions for user</b>	No information available.
<b>TDG - Transportation of Dangerous Goods (Canada)</b>	
<b>Transport hazard class(es)</b>	 Class 3
<b>Packing group</b>	II
<b>IMO/IMDG - International Maritime Transport</b>	
<b>Classification</b>	Regulated UN 1263. Class 3, PG II.
<b>IATA - International Air Transport Association</b>	
<b>Classification</b>	Regulated UN 1263. Class 3, PG II.
These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.	

## 15. Regulatory information

### CANADA

Common name	CAS	CEPA	DSL	NDSL	NPRI
Toluene	108-88-3	X	X		X
Rosin, maleated, polymer with glycerol	68038-41-5		X		
Butyl acetate (normal)	123-86-4	X	X		X
Titanium dioxide	13463-67-7		X		
Bis(2-Ethylhexyl) adipate	103-23-1		X		X
Acetone	67-64-1		X		
Methanol	67-56-1	X	X		X
Nitrocellulose	9004-70-0		X		
Isopropyl alcohol	67-63-0	X	X		X
2-Butoxyethanol	111-76-2	X	X		X
Ethyl Alcohol	64-17-5	X	X		X

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act
- DSL: Domestic Substances List Inventory
- NDSL: Non-Domestic Substances List Inventory
- NPRI: National Pollutant Release Inventory Substances

**UNITED STATE OF AMERICA**

Common name	CAS	TSCA	CER CLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Prio.
Toluene	108-88-3	X	X	X		X	X		X	X
Rosin, maleated, polymer with glycerol	68038-41-5	X								
Butyl acetate (normal)	123-86-4	X	X						X	
Titanium dioxide	13463-67-7	X								
Bis(2-Ethylhexyl) adipate	103-23-1	X								
Acetone	67-64-1	X	X	X		X				
Methanol	67-56-1	X	X	X		X	X			
Nitrocellulose	9004-70-0	X								
Isopropyl alcohol	67-63-0	X		X					X	
2-Butoxyethanol	111-76-2	X								
Ethyl Alcohol	64-17-5	X								

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act - Hazardous Organic National Emission Standard for Hazardous Air Pollutant
- CAA 112(b) HAP: Clean Air Act - Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act - Regulated Chemicals for Accidental Release Prevention
- CWA 311: Clean Water Act - List of Hazardous Substances
- CWA Priority: Clean Water Act - Priority Pollutant list

**California Proposition 65**

Common name	CAS	Cancer	Reproductive and Developmental Toxicity
Toluene	108-88-3		X
Titanium dioxide	13463-67-7	X	
Methanol	67-56-1		X
Ethyl Alcohol	64-17-5	X	X

**Other regulations**

**WHMIS 1988**



B2 D1A D2A D2B

Class B2 : Flammable Liquid

Class D1A : Very toxic material causing immediate and serious toxic effects


Class D2A : Very toxic material causing other toxic effects

Class D2B : Toxic material causing other toxic effects

**HMIS**



**NFPA**



## 16. Other information

<b>Date (YYYY-MM-DD)</b>	GEMINI INDUSTRIES, INC. 2016-03-21
<b>Version</b>	02
<b>Other information</b>	<p>REFERENCES:</p> <ul style="list-style-type: none"><li>- NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, <a href="http://www.cdc.gov/niosh/npg/npg.html">http://www.cdc.gov/niosh/npg/npg.html</a></li><li>- IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), <a href="http://www.inchem.org">http://www.inchem.org</a></li><li>- Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), <a href="http://www.reptox.csst.qc.ca">http://www.reptox.csst.qc.ca</a></li><li>- IUCLID Chemical Dataset, European Chemical Substances Information System (ESIS), Joint Research Centre, <a href="http://esis.jrc.ec.europa.eu">http://esis.jrc.ec.europa.eu</a></li></ul> <p>DATE OF FIRST VERSION OF SDS: 2014-03-21.</p> <p>CHANGES MADE IN THE VERSION 02: sections 3, 8, 11 and 15.</p> <p>ACGIH: American Conference of Governmental Industrial Hygienists AIHA: American Industrial Hygiene Association HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association OSHA: Occupational Safety and Health Administration (USA) NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program RSST: Règlement sur la santé et la sécurité du travail (Québec) GHS: Globally Harmonized System IARC: International Agency for Research on Cancer IDLH: Immediately Dangerous to Life or Health STEL: Short Term Exposure Limit (15 min) TWA: Time Weighted Averages WHMIS: Workplace Hazardous Materials Information System</p> <p>To the best of our knowledge, the information contained herein is accurate. However, neither Préventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.</p>