



Safety Data Sheet

275 VOC PRECAT LACQUER SATIN CLEAR






1. Identification

Product identifier	275 VOC PRECAT LACQUER SATIN CLEAR		
Product code	510-0276		
Other means of identification	None.		
Recommended use of the chemical and restrictions on use	A protective and/or decorative finish or accompanying paint product. Not recommended for: Any other use not detailed on product data sheet or label.		
Manufacturer	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 USA Tel. 1-800-262-5710 Fax 1-405-262-9310 www.geminicoatings.com		
Emergency phone number	24-hour Emergency (Spill, Leak, Exposure or accident) INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English) HAZMAT Response and MSDS Help: EMI 800-510-8510		

2. Hazard identification

Summary	FLAMABLE LIQUID! Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved.
----------------	--

WHMIS 2015/OSHA HCS 2012/GHS

  	<p>Flammable liquids (Category 2) Skin irritation (Category 2) Serious eye damage/eye irritation (Category 2A) Skin sensitizer (Category 1B) Reproductive toxicity (Category 2) Specific target organ toxicity, single exposure (Category 3)</p> <p>Other hazards which do not result in classification : Acute hazard to the aquatic environment (Category 2). Long-term hazard to the aquatic environment (Category 2)</p>
--	--

DANGER

- H225: Highly Flammable liquid and vapour
- H319: Causes serious eye irritation
- H315: Causes skin irritation
- H317: May cause an allergic skin reaction
- H335: May cause respiratory irritation
- H336: May cause drowsiness or dizziness

H361: Suspected of damaging fertility or the unborn child
H411: Toxic to aquatic life with long lasting effects
P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.
P240: Ground or bond container and receiving equipment.
P241: Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P261: Avoid breathing mist, vapours and spray.
P264: Wash skin thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.
P273: Avoid release to the environment.
P280: Wear protective gloves, protective clothing and eye protection.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or take a shower if necessary.
P333+313: If skin irritation or a rash occurs: Get medical advice/attention.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337+313: If eye irritation persists: Get medical advice or attention.
P308+313: IF exposed or concerned: Get medical advice/attention.
P321: Specific treatment (see section 4 of SDS).
P362+364: Take off contaminated clothing and wash before reuse.
P370+378: In case of fire: Use the National Fire Protection Association Class B extinguisher for extinction.
P391: Collect spillage.
P403+P235+P233: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P405: Store locked up.
P501: Dispose of contents and container to an approved waste disposal plant.

3. Composition/information on ingredients

Common name	CAS	Weight % content
Acetone	67-64-1	54 - 56 %
1-Chloro-4-(trifluoromethyl)benzene	98-56-6	13 - 15 %
Nitrocellulose	9004-70-0	5 - 7 %
Urea, polymer with formaldehyde, butylated	68002-19-7	3 - 5 %
Methyl n-amyl ketone	110-43-0	2 - 4 %
Isopropyl alcohol	67-63-0	1.5 - 2.5 %
Bis(2-Ethylhexyl) adipate	103-23-1	1.5 - 2.5 %
n-Butyl Alcohol	71-36-3	1.5 - 2.5 %

4. First-aid measures

Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
Skin contact	Wash skin with warm water and mild soap for at least 15 minutes. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.
Eye contact	IMMEDIATELY! Flush with water for at least 15 minutes. Remove contact lenses. Hold eyelids apart to

	rinse properly. If a problem develops or persists, seek medical attention.
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If victim is conscious wash out mouth with water and give 2-4 glasses of water to drink. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.
Other	No information available.
Symptoms	May cause severe irritation to eyes. May cause redness, dryness or rash of the skin. May cause an allergic reaction of the skin. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue.
Notes to the physician	Treat symptomatically. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire-fighting measures

Suitable extinguishing media	Class B extinguishers. Dry chemicals, alcohol resistant foam, carbon dioxide (CO ₂). Do not use direct water jet.
Specific hazards arising from the chemical	Very flammable liquid and vapours. Vapours are heavier than air and may travel to an ignition source distant from the material handling point. May be ignited by heat, sparks, flame or static electricity. Do not apply to hot surfaces. Contact with strong oxidizers may cause fire. In a fire or if heated, a pressure increase will occur and the container may burst. Emits toxic fumes under fire conditions.
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
Special protective actions for fire-fighters	Use water spray to cool fire-exposed containers. Water spray can reduce the intensity of the flames. However, the water jets can spread the fire. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
Environmental precautions	Prevent entry in sewer and other enclosed area. For a large spill, consult the Department of Environment or the relevant authorities.
Methods and materials for containment and cleaning up	Remove sources of ignition. Ventilate the area well. Stop leak, if it's possible to do so without risk. Absorb with inert material (soil, sand, vermiculite) and place in an appropriate waste disposal clearly identified. Use non-sparking and antistatic tools. Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water. PS: Rags and others materials soaked with paint or solvent may spontaneously catch fire if improperly store or discarded. Immediately after each use place rags and paper towels in a sealed water-filled metal container to prevent spontaneous combustion.

7. Handling and storage

Precautions for safe handling	Keep away from heat, sparks and open flame. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Use non-sparking and antistatic tools. Ground/bond all containers when transferring large quantities (5 gallons US or 20 L and more). Use only in well ventilated area. Avoid prolonged or repeated breathing of vapour or mists. Avoid contact with skin, eyes and clothing. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. Keep containers tightly closed when not
--------------------------------------	--

in use. Containers of this material may be hazardous even when empty. Since empty containers retain product residues (vapour, liquid), all hazard precautions given in this sheet must be observed. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse. Rags, steel wool and paper towels soaked with this product may overheat and spontaneously ignite if piled in a heap. After use immediately store them in water-filled metal can with tight fitting lid.

Conditions for safe storage, including any incompatibilities

Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10).

Storage temperature

10 to 25°C (50 to 77°F)

8. Exposure controls/personal protection

Immediately Dangerous to Life or Health

Acetone: 2500 ppm.
Methyl n-amyl ketone: 800 ppm.
Isopropyl alcohol: 2000 ppm.
n-Butyl Alcohol: 1400 ppm.

Acetone	STEL	500 ppm		ACGIH , BC
		750 ppm	1782 mg/m ³	ON
		1000 ppm	2380 mg/m ³	RSST
		TWA (8h)	250 ppm	
Methyl n-amyl ketone	TWA (8h)	500 ppm	1188 mg/m ³	ON
		500 ppm	1190 mg/m ³	RSST
		25 ppm	115 mg/m ³	ON
		50 ppm		ACGIH , BC
Isopropyl alcohol	STEL	50 ppm	233 mg/m ³	RSST
		400 ppm		ACGIH , BC, ON
		500 ppm	1230 mg/m ³	RSST
		TWA (8h)	200 ppm	
n-Butyl Alcohol	Ceiling	400 ppm	983 mg/m ³	RSST
		30 ppm		BC
		50 ppm	152 mg/m ³	RSST (Pc, RP)
		TWA (8h)	15 ppm	
		20 ppm		ACGIH , ON

Appropriate engineering controls

Provide sufficient mechanical ventilation (general and/or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.

Individual protection measures

Eye

Wear chemical splash goggles.

Hands

Wear Neoprene gloves. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly.

Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. Wear an apron or long-sleeve protective coverall suit.

Respiratory

Respiratory protection is not required for normal use. Respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and CSA Standard Z 94.4 and approved by NIOSH / MSHA. In case of insufficient ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times the exposure limit, wear a half

mask respirator with organic vapour cartridges fitted with P100 filters. For an APF until maximum 100 times of exposure limit, wear a full face respirator mask with organic vapour cartridges and P100 filters.

Feet Wear rubber boots to clean up a spill.

9. Physical and chemical properties

Physical state	Liquid	Flammability	Flammable
Colour	Clear	Flammability limits	N/Av.
Odour	Solvent	Flash point	0°C (32°F)
Odour threshold	N/Av.	Auto-ignition temperature	N/Av.
pH	N/Av.	Sensibility to electrostatic charges	Yes
Melting point	N/Av.	Sensibility to sparks and/or friction	No
Freezing point	N/Av.	Vapour density	>1 (Air = 1)
Boiling point	56°C (132.8°F)	Relative density	0.9217 kg/L (Water = 1)
Solubility	Partially soluble in water.	Partition coefficient n-octanol/water	N/Av.
Evaporation rate	> Butyl Acetate	Decomposition temperature	N/Av.
Vapour pressure	N/Av.	Viscosity	N/Av.
Percent Volatile	77.01%	Molecular mass	N/Av.
N/Av.: Not Available N/Av.: Not Applicable Und.: Undetermined N/E: Not Established			

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions (including polymerizations)	A dangerous reaction will not occur.
Conditions to avoid	Avoid heat, flame and sparks. Avoid contact with incompatible materials.
Incompatible materials	Strong bases, mineral acids, strong oxidizing agents (such as nitric acid, perchloric acid, peroxides, chlorates and perchlorates).
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Numerical measures of toxicity	<table border="0"> <tr> <td data-bbox="289 113 711 218">Acetone</td> <td data-bbox="719 113 833 142">Ingestion</td> <td data-bbox="841 113 995 142">5800 mg/kg</td> <td data-bbox="1003 113 1060 142">Rat</td> <td data-bbox="1068 113 1157 142">LD50</td> </tr> <tr> <td></td> <td data-bbox="719 153 833 182">Inhalation</td> <td data-bbox="841 153 995 182">71.4 mg/l/4h</td> <td data-bbox="1003 153 1060 182">Rat</td> <td data-bbox="1068 153 1157 182">LC50</td> </tr> <tr> <td></td> <td data-bbox="719 193 776 222">Skin</td> <td data-bbox="841 193 995 222">15800 mg/kg</td> <td data-bbox="1003 193 1092 222">Rabbit</td> <td data-bbox="1101 193 1157 222">LD50</td> </tr> <tr> <td data-bbox="289 228 711 365">1-Chloro-4-(trifluoromethyl)benzene</td> <td data-bbox="719 228 833 258">Ingestion</td> <td data-bbox="841 228 995 258">5546 mg/kg</td> <td data-bbox="1003 228 1060 258">Rat</td> <td data-bbox="1068 228 1157 258">LD50</td> </tr> <tr> <td></td> <td data-bbox="719 268 833 298">Inhalation</td> <td data-bbox="841 268 995 298">20 mg/l/4h</td> <td data-bbox="1003 268 1092 298">Mouse</td> <td data-bbox="1101 268 1157 298">LC50</td> </tr> <tr> <td></td> <td></td> <td data-bbox="841 308 995 338">22 mg/l/4h</td> <td data-bbox="1003 308 1060 338">Rat</td> <td data-bbox="1068 308 1157 338">LC50</td> </tr> <tr> <td></td> <td data-bbox="719 348 776 378">Skin</td> <td data-bbox="841 348 995 378">>2000 mg/kg</td> <td data-bbox="1003 348 1092 378">Rabbit</td> <td data-bbox="1101 348 1157 378">LD50</td> </tr> <tr> <td data-bbox="289 388 711 417">Nitrocellulose</td> <td data-bbox="719 388 833 417">Ingestion</td> <td data-bbox="841 388 995 417">>5000 mg/kg</td> <td data-bbox="1003 388 1060 417">Rat</td> <td data-bbox="1068 388 1157 417">LD50</td> </tr> <tr> <td data-bbox="289 428 711 533">Methyl n-amyl ketone</td> <td data-bbox="719 428 833 457">Ingestion</td> <td data-bbox="841 428 995 457">1670 mg/kg</td> <td data-bbox="1003 428 1060 457">Rat</td> <td data-bbox="1068 428 1157 457">LD50</td> </tr> <tr> <td></td> <td data-bbox="719 468 833 497">Inhalation</td> <td data-bbox="841 468 995 497"><18.7 mg/l/4h</td> <td data-bbox="1003 468 1060 497">Rat</td> <td data-bbox="1068 468 1157 497">LC50</td> </tr> <tr> <td></td> <td></td> <td data-bbox="841 508 995 537">>9.34 mg/l/4h</td> <td data-bbox="1003 508 1060 537">Rat</td> <td data-bbox="1068 508 1157 537">LC50</td> </tr> <tr> <td></td> <td data-bbox="719 548 776 577">Skin</td> <td data-bbox="841 548 995 577">10220 mg/kg</td> <td data-bbox="1003 548 1092 577">Rabbit</td> <td data-bbox="1101 548 1157 577">LD50</td> </tr> <tr> <td data-bbox="289 588 711 646">Bis(2-Ethylhexyl) adipate</td> <td data-bbox="719 588 833 617">Ingestion</td> <td data-bbox="841 588 995 617">9100 mg/kg</td> <td data-bbox="1003 588 1060 617">Rat</td> <td data-bbox="1068 588 1157 617">LD50</td> </tr> <tr> <td></td> <td data-bbox="719 627 833 657">Inhalation</td> <td data-bbox="841 627 995 657">>5.7 mg/l/4h</td> <td data-bbox="1003 627 1060 657">Rat</td> <td data-bbox="1068 627 1157 657">LC50</td> </tr> <tr> <td></td> <td data-bbox="719 667 776 697">Skin</td> <td data-bbox="841 667 995 697">17297 mg/kg</td> <td data-bbox="1003 667 1092 697">Rabbit</td> <td data-bbox="1101 667 1157 697">LD50</td> </tr> <tr> <td data-bbox="289 707 711 766">n-Butyl Alcohol</td> <td data-bbox="719 707 833 737">Ingestion</td> <td data-bbox="841 707 995 737">2510 mg/kg</td> <td data-bbox="1003 707 1060 737">Rat</td> <td data-bbox="1068 707 1157 737">LD50</td> </tr> <tr> <td></td> <td data-bbox="719 747 833 777">Inhalation</td> <td data-bbox="841 747 995 777">24.2 mg/l/4h</td> <td data-bbox="1003 747 1060 777">Rat</td> <td data-bbox="1068 747 1157 777">LC50</td> </tr> <tr> <td></td> <td data-bbox="719 787 776 816">Skin</td> <td data-bbox="841 787 995 816">3400 mg/kg</td> <td data-bbox="1003 787 1092 816">Rabbit</td> <td data-bbox="1101 787 1157 816">LD50</td> </tr> <tr> <td data-bbox="289 827 711 869">Isopropyl alcohol</td> <td data-bbox="719 827 833 856">Ingestion</td> <td data-bbox="841 827 995 856">5045 mg/kg</td> <td data-bbox="1003 827 1060 856">Rat</td> <td data-bbox="1068 827 1157 856">LD50</td> </tr> <tr> <td></td> <td data-bbox="719 867 833 896">Inhalation</td> <td data-bbox="841 867 995 896">66.1 mg/l/4h</td> <td data-bbox="1003 867 1060 896">Rat</td> <td data-bbox="1068 867 1157 896">LC50</td> </tr> <tr> <td></td> <td data-bbox="719 907 776 936">Skin</td> <td data-bbox="841 907 995 936">6280 mg/kg</td> <td data-bbox="1003 907 1060 936">Rat</td> <td data-bbox="1068 907 1157 936">LD50</td> </tr> </table>	Acetone	Ingestion	5800 mg/kg	Rat	LD50		Inhalation	71.4 mg/l/4h	Rat	LC50		Skin	15800 mg/kg	Rabbit	LD50	1-Chloro-4-(trifluoromethyl)benzene	Ingestion	5546 mg/kg	Rat	LD50		Inhalation	20 mg/l/4h	Mouse	LC50			22 mg/l/4h	Rat	LC50		Skin	>2000 mg/kg	Rabbit	LD50	Nitrocellulose	Ingestion	>5000 mg/kg	Rat	LD50	Methyl n-amyl ketone	Ingestion	1670 mg/kg	Rat	LD50		Inhalation	<18.7 mg/l/4h	Rat	LC50			>9.34 mg/l/4h	Rat	LC50		Skin	10220 mg/kg	Rabbit	LD50	Bis(2-Ethylhexyl) adipate	Ingestion	9100 mg/kg	Rat	LD50		Inhalation	>5.7 mg/l/4h	Rat	LC50		Skin	17297 mg/kg	Rabbit	LD50	n-Butyl Alcohol	Ingestion	2510 mg/kg	Rat	LD50		Inhalation	24.2 mg/l/4h	Rat	LC50		Skin	3400 mg/kg	Rabbit	LD50	Isopropyl alcohol	Ingestion	5045 mg/kg	Rat	LD50		Inhalation	66.1 mg/l/4h	Rat	LC50		Skin	6280 mg/kg	Rat	LD50
Acetone	Ingestion	5800 mg/kg	Rat	LD50																																																																																																						
	Inhalation	71.4 mg/l/4h	Rat	LC50																																																																																																						
	Skin	15800 mg/kg	Rabbit	LD50																																																																																																						
1-Chloro-4-(trifluoromethyl)benzene	Ingestion	5546 mg/kg	Rat	LD50																																																																																																						
	Inhalation	20 mg/l/4h	Mouse	LC50																																																																																																						
		22 mg/l/4h	Rat	LC50																																																																																																						
	Skin	>2000 mg/kg	Rabbit	LD50																																																																																																						
Nitrocellulose	Ingestion	>5000 mg/kg	Rat	LD50																																																																																																						
Methyl n-amyl ketone	Ingestion	1670 mg/kg	Rat	LD50																																																																																																						
	Inhalation	<18.7 mg/l/4h	Rat	LC50																																																																																																						
		>9.34 mg/l/4h	Rat	LC50																																																																																																						
	Skin	10220 mg/kg	Rabbit	LD50																																																																																																						
Bis(2-Ethylhexyl) adipate	Ingestion	9100 mg/kg	Rat	LD50																																																																																																						
	Inhalation	>5.7 mg/l/4h	Rat	LC50																																																																																																						
	Skin	17297 mg/kg	Rabbit	LD50																																																																																																						
n-Butyl Alcohol	Ingestion	2510 mg/kg	Rat	LD50																																																																																																						
	Inhalation	24.2 mg/l/4h	Rat	LC50																																																																																																						
	Skin	3400 mg/kg	Rabbit	LD50																																																																																																						
Isopropyl alcohol	Ingestion	5045 mg/kg	Rat	LD50																																																																																																						
	Inhalation	66.1 mg/l/4h	Rat	LC50																																																																																																						
	Skin	6280 mg/kg	Rat	LD50																																																																																																						
Likely routes of exposure	Skin, eyes, inhalation, ingestion.																																																																																																									
Delayed, immediate and chronic effects	<table border="0"> <tr> <td data-bbox="289 968 532 1129"> Eye contact </td> <td data-bbox="540 968 1565 1129"> May cause irritation, redness, tearing and blurred vision. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with each ingredient of this mixture gave from mild irritating to corrosive results. Butyl Alcohol instilled in rabbit eyes resulted in severe corneal irritation and eye damage (OECD 405). Application in excess of 5% dilution solution gave irritating effect. </td> </tr> <tr> <td data-bbox="289 1140 532 1262"> Skin contact </td> <td data-bbox="540 1140 1565 1262"> May cause redness and slight irritation of the skin. Prolonged and repeated contact may cause dry skin, irritation or dermatitis. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient of this mixture gave not irritating to irritating results. </td> </tr> <tr> <td data-bbox="289 1272 532 1488"> Inhalation </td> <td data-bbox="540 1272 1565 1488"> Excessive inhalation is harmful. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. Inhalation of high vapour concentrations or prolonged breathing of lower concentrations may result in damage to the liver, kidneys, lungs and blood forming organs. The severity of symptoms may vary depending on exposure conditions. Repeated and prolonged occupational overexposure to solvents may cause brain and nervous system damage. </td> </tr> <tr> <td data-bbox="289 1499 532 1621"> Ingestion </td> <td data-bbox="540 1499 1565 1621"> Swallowing will causes digestive tract disturbances resulting in nausea, vomiting, cramps and diarrhea. Ingestion of large amounts may cause depression of the central nervous system characterized by headache, dizziness, convulsions and loss of consciousness. </td> </tr> <tr> <td data-bbox="289 1631 532 1690"> Respiratory or skin sensitization </td> <td data-bbox="540 1631 1565 1690"> 1-Chloro-4-(trifluoromethyl)benzene is a skin sensitizer (mouse, OECD TG 429). This product is not a respiratory sensitizer. </td> </tr> <tr> <td data-bbox="289 1701 532 1759"> IARC/NTP Classification </td> <td data-bbox="540 1701 1565 1759"> No ingredients listed. </td> </tr> <tr> <td data-bbox="289 1770 532 1829"> Carcinogenicity </td> <td data-bbox="540 1770 1565 1829"> Ingredients present at levels greater than or equal to 0.1% of this product are not listed as a carcinogen by IARC, ACGIH, NIOSH, NTP or OSHA. </td> </tr> <tr> <td data-bbox="289 1839 532 1898"> Mutagenicity </td> <td data-bbox="540 1839 1565 1898"> Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause mutagenic effects. </td> </tr> <tr> <td data-bbox="289 1908 532 2055"> Reproductive toxicity </td> <td data-bbox="540 1908 1565 2055"> Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause reproduction effects. Isopropyl alcohol does not show specific reproductive or developmental toxicity. Any reproductive and developmental effects were only observed secondary to maternal toxicity. However, reproductive toxicity, such as decline in a pregnancy rate, an increase in embryo absorption, and an </td> </tr> </table>	Eye contact	May cause irritation, redness, tearing and blurred vision. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with each ingredient of this mixture gave from mild irritating to corrosive results. Butyl Alcohol instilled in rabbit eyes resulted in severe corneal irritation and eye damage (OECD 405). Application in excess of 5% dilution solution gave irritating effect.	Skin contact	May cause redness and slight irritation of the skin. Prolonged and repeated contact may cause dry skin, irritation or dermatitis. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient of this mixture gave not irritating to irritating results.	Inhalation	Excessive inhalation is harmful. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. Inhalation of high vapour concentrations or prolonged breathing of lower concentrations may result in damage to the liver, kidneys, lungs and blood forming organs. The severity of symptoms may vary depending on exposure conditions. Repeated and prolonged occupational overexposure to solvents may cause brain and nervous system damage.	Ingestion	Swallowing will causes digestive tract disturbances resulting in nausea, vomiting, cramps and diarrhea. Ingestion of large amounts may cause depression of the central nervous system characterized by headache, dizziness, convulsions and loss of consciousness.	Respiratory or skin sensitization	1-Chloro-4-(trifluoromethyl)benzene is a skin sensitizer (mouse, OECD TG 429). This product is not a respiratory sensitizer.	IARC/NTP Classification	No ingredients listed.	Carcinogenicity	Ingredients present at levels greater than or equal to 0.1% of this product are not listed as a carcinogen by IARC, ACGIH, NIOSH, NTP or OSHA.	Mutagenicity	Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause mutagenic effects.	Reproductive toxicity	Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause reproduction effects. Isopropyl alcohol does not show specific reproductive or developmental toxicity. Any reproductive and developmental effects were only observed secondary to maternal toxicity. However, reproductive toxicity, such as decline in a pregnancy rate, an increase in embryo absorption, and an																																																																																							
Eye contact	May cause irritation, redness, tearing and blurred vision. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with each ingredient of this mixture gave from mild irritating to corrosive results. Butyl Alcohol instilled in rabbit eyes resulted in severe corneal irritation and eye damage (OECD 405). Application in excess of 5% dilution solution gave irritating effect.																																																																																																									
Skin contact	May cause redness and slight irritation of the skin. Prolonged and repeated contact may cause dry skin, irritation or dermatitis. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient of this mixture gave not irritating to irritating results.																																																																																																									
Inhalation	Excessive inhalation is harmful. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. Inhalation of high vapour concentrations or prolonged breathing of lower concentrations may result in damage to the liver, kidneys, lungs and blood forming organs. The severity of symptoms may vary depending on exposure conditions. Repeated and prolonged occupational overexposure to solvents may cause brain and nervous system damage.																																																																																																									
Ingestion	Swallowing will causes digestive tract disturbances resulting in nausea, vomiting, cramps and diarrhea. Ingestion of large amounts may cause depression of the central nervous system characterized by headache, dizziness, convulsions and loss of consciousness.																																																																																																									
Respiratory or skin sensitization	1-Chloro-4-(trifluoromethyl)benzene is a skin sensitizer (mouse, OECD TG 429). This product is not a respiratory sensitizer.																																																																																																									
IARC/NTP Classification	No ingredients listed.																																																																																																									
Carcinogenicity	Ingredients present at levels greater than or equal to 0.1% of this product are not listed as a carcinogen by IARC, ACGIH, NIOSH, NTP or OSHA.																																																																																																									
Mutagenicity	Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause mutagenic effects.																																																																																																									
Reproductive toxicity	Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause reproduction effects. Isopropyl alcohol does not show specific reproductive or developmental toxicity. Any reproductive and developmental effects were only observed secondary to maternal toxicity. However, reproductive toxicity, such as decline in a pregnancy rate, an increase in embryo absorption, and an																																																																																																									

	<p>increase in fetus death, were observed at the dose in which a fall of the increasing weight, and toxicity such as an anesthesia action to parental animals were observed. Central nervous system, respiratory system.</p> <p>Specific target organ toxicity - single exposure</p> <p>Specific target organ toxicity - repeated exposure</p> <p>No target organ is listed.</p>
Interactive effects	No information available for this product.
Other information	The oral and skin acute toxicity estimates (ATE) of the mixture were calculated to be greater than 2000 mg/kg. The acute toxicity estimate (ATE) by inhalation of the mixture was calculated to be greater than 20 mg/L/4h. These values are not classified according to WHMIS 2015 and OSHA HCS 2012.

12. Ecological information

Ecological toxicity	<p>Fish - Oncorhynchus mykiss - Rainbow trout LC50 4.74-6.33 mg/L; 96 h (acetone)</p> <p>Aquatic Invertebrate - Daphnia magna EC50 12600-12700 mg/L; 48 h (acetone)</p> <p>Fish - Fathead minnow, Pimephales promelas - fresh water LC50 9640 mg/L; 96 h (Isopropyl alcohol)</p> <p>Aquatic Invertebrate - Crustaceans, Daphnia Magna EC50 3644 mg/L; 48 hr (Isopropyl alcohol)</p> <p>Plant - Lettuce seed germination, Lactuca Sativa EC50 2100 mg/L; 72 hr (Isopropyl alcohol)</p> <p>Algae, Pseudokirchneriella subcapitata EC50 579 mg/L; 96h (Nitrocellulose)</p> <p>Fish - Danio rerio LC50 3 mg/L; 96h (CAS no 98-56-6) OECD 203</p> <p>Aquatic Invertebrate - Daphnia magna (semi-static) EC50 2 mg/L; 48h (CAS no 98-56-6)</p> <p>Fish - Pimephales promelas [flow-through] LC50 126-137 mg/L; 96 h (Methyl n-amyl ketone)</p> <p>Fish - Pimephales promelas [static] LC50 1376 mg/L; 96 h (n-Butyl alcohol)</p> <p>Aquatic Invertebrate - Daphnia magna EC50 1983 mg/L; 48 h (n-Butyl alcohol)</p> <p>Algae - Desmodesmus subspicatus EC50 >500 mg/L; 72 h (n-Butyl alcohol)</p> <p>Fish - Lepomis macrochirus [static] LC50 0.48-0.85 mg/L; 96 h (CAS no 103-23-1)</p> <p>Aquatic Invertebrate - Daphnia magna EC50 >1.6 mg/L; 48 h (CAS no 103-23-1)</p> <p>Algae - Desmodesmus subspicatus EC50 >500 mg/L; 72 h (CAS no 103-23-1)</p>
Persistence	Contains an or many ingredients that may be persistent in aquatic environment.
Degradability	Acetone undergoes slow photolysis in air (half-life time T _{1/2} = 80 h) and in water (T _{1/2} >43 h). 1-Chloro-4-(trifluoromethyl)benzene is not degraded by photolysis in water. It has also showed to be not ready biodegradable, 19.2% during 28 days (OECD TG 301D). Degradation of Nitrocellulose involves complex dissociation into a wide variety of products. Since it is not soluble in water, the biodegradation by a sludge-soil mixture will be done over a long period of time (TOXNET). Isopropyl alcohol is biodegradable, 49% in 5 days and 70% in 20 days (TOXNET). It does not undergo photolysis. Its atmospheric degradation (OH radical attack) in air has a half-time T _{1/2} of 18 to 25 hours. Bis(2-Ethylhexyl) adipate is readily biodegradable >90% in 28 days (OECD Guideline 301F). n-Butyl Alcohol is readily biodegradable. Degradation by Biochemical Oxygen Demand BOD (O ₂ consumption) was reported as 92% after 20 days.
Bioaccumulative potential	Acetone has a Bioconcentration Factor (BCF) of 0.65 and a partition factor Log Kow of -0.24, indicating no bioaccumulation. According to an estimated Bioconcentration Factors (BCF) of 110 in fish and an estimated partition coefficient log Kow of 3.6 suggest that 1-Chloro-4-(trifluoromethyl)benzene has a potential for bioaccumulation in aquatic organisms is high (TOXNET). The Log Kow value <0.4 and bioconcentration factor (BCF) value <1 for isopropyl alcohol show no potential to bioaccumulate (IUCLID). Bis(2-Ethylhexyl) adipate has a Bioconcentration Factor (BCF) of 27, indicating no bioaccumulation. n-Butyl alcohol has a Bioconcentration Factor (BCF) value of 3, and its Log Kow value is from 0.8 to 1, indicating its potential to bioaccumulate is very low.
Mobility in soil	Acetone evaporates very rapidly from dry soil surfaces. It is very soluble in water and it is expected to have very high mobility in soil with no adsorption to sediment. The Koc value of 1600 suggest that 1-Chloro-4-(trifluoromethyl)benzene is expected to have low mobility in soil (TOXNET). Isopropyl alcohol is

soluble in water and will quickly evaporate into the air. There is no partition in the ground. Bis(2-Ethylhexyl) adipate has an estimated Koc value of 49000 which suggests that it is expected to be immobile in soil. n-Butyl alcohol is soluble in water. The estimated Koc value of 3.2 suggests that it is expected to have very high mobility in soil.

Other adverse effects

This chemical does not deplete the ozone layer.

13. Disposal considerations

Container



Important! Prevent waste generation. Use in full. DO NOT dispose of residue in sewers, streams or drinking water supply. Paint residues, including lacquers, stains, shellac, varnish, solvents and paint thinners, can be reprocessed (recycle) anywhere there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.

14. Transport information

UN Number	UN 1263
UN Proper Shipping Name	PAINT
Environmental hazards	This material does not contain marine pollutant.
Special precautions for user	Permit required for transportation with proper placards displayed on vehicle.

TDG - Transportation of Dangerous Goods (Canada)

Transport hazard class(es)	 Class 3
Packing group	II

IMO/IMDG - International Maritime Transport

Classification	UN 1263. PAINT. Class 3, PG II. Emergency schedules (EmS-No) F-E, S-E
-----------------------	---

IATA - International Air Transport Association

Classification	UN 1263. PAINT. Class 3, PG II.
-----------------------	---------------------------------

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.

15. Regulatory information

CANADA

Common name	CAS	CEPA	DSL	NDSL	NPRI
Acetone	67-64-1		X		
1-Chloro-4-(trifluoromethyl)benzene	98-56-6		X		
Nitrocellulose	9004-70-0		X		
Urea, polymer with formaldehyde, butylated	68002-19-7		X		
Methyl n-amyl ketone	110-43-0		X		
Isopropyl alcohol	67-63-0	X	X		X
Bis(2-Ethylhexyl) adipate	103-23-1		X		X

n-Butyl Alcohol	71-36-3	X	X		X
-----------------	---------	---	---	--	---

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act
- DSL: Domestic Substances List Inventory
- NDSL: Non-Domestic Substances List Inventory
- NPRI: National Pollutant Release Inventory Substances

UNITED STATE OF AMERICA

Common name	CAS	TSCA	CERCLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Priority
Acetone	67-64-1	X	X			X				
1-Chloro-4-(trifluoromethyl)benzene	98-56-6	X								
Nitrocellulose	9004-70-0	X								
Urea, polymer with formaldehyde, butylated	68002-19-7	X								
Methyl n-amyl ketone	110-43-0	X								
Isopropyl alcohol	67-63-0	X		X					X	
Bis(2-Ethylhexyl) adipate	103-23-1	X								
n-Butyl Alcohol	71-36-3	X	X	X					X	

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act - Hazardous Organic National Emission Standard for Hazardous Air Pollutant
- CAA 112(b) HAP: Clean Air Act - Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act - Regulated Chemicals for Accidental Release Prevention
- CWA 311: Clean Water Act - List of Hazardous Substances
- CWA Priority: Clean Water Act - Priority Pollutant list

California Proposition 65

No ingredients listed.

Other regulations

WHMIS 1988



B2

D2B

Class B2 : Flammable Liquid

Class D2B : Toxic material causing other toxic effects

HMIS



NFPA



16. Other information

Date (YYYY-MM-DD)	GEMINI INDUSTRIES, INC. 2016-02-18
Version	01

**Other
information**

- This SDS and the GHS hazards classification is a French translation of the original English version (SDS) from the manufacturer.

REFERENCES:

- Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, <http://hazmap.nlm.nih.gov/index.php>
- TOXNET Databases, Toxicology Data Network, NIH U.S. National Library of Medicine, <http://toxnet.nlm.nih.gov/>
- Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), <http://www.reptox.csst.qc.ca>
- NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, <http://www.cdc.gov/niosh/npg/npg.html>
- IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), <http://www.inchem.org>
- OECD Existing Chemicals Database, Chemicals Screening Information DataSet (SIDS) for High Volume Chemicals, UNEP publications, <http://webnet.oecd.org/HPV/UI/Search.aspx>

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

HMIS: Hazardous Materials Identification System

NFPA: National Fire Protection Association

OSHA: Occupational Safety and Health Administration (USA)

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

RSST: Règlement sur la santé et la sécurité du travail (Québec)

GHS: Globally Harmonized System

IARC: International Agency for Research on Cancer

IDLH: Immediately Dangerous to Life or Health

STEL: Short Term Exposure Limit (15 min)

TWA: Time Weighted Averages

WHMIS: Workplace Hazardous Materials Information System

To the best of our knowledge, the information contained herein is accurate. However, neither Préventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.