



Safety Data Sheet

GEMVAR H/C CAT. SEMI GLOSS VARNISH



1. Identification

Product identifier	GEMVAR H/C CAT. SEMI GLOSS VARNISH		
Product code	550-0011		
Other means of identification	N/Av.		
Recommended use of the chemical and restrictions on use	Varnish.		
Manufacturer	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 USA Tel. 1-800-262-5710 Fax 1-405-262-9310 www.gemini-coatings.com		
Emergency phone number	INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English) 24-hour HAZMAT Response and MSDS help: EMI 800-510-8510		

2. Hazard identification

Summary	DANGER! FLAMMABLE LIQUID! TOXIC! Skin, eyes and respiratory tracts irritant. Harmful by inhalation, if swallowed and if absorbed through the skin. May cause central nervous system effects. May cause an allergic respiratory reaction. May cause cancer if inhaled. Contains a substance that can cause target organ damage, according to data obtained on animals. Reproductive effects in animal. Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet. Keep containers tightly closed when not in use. After use, wash hands with soap and water. Wash contaminated clothing before reuse.
----------------	---

WHMIS 2015/OSHA HCS 2012/GHS



Flammable liquids (Category 2)
 Acute toxicity, oral (Category 4)
 Acute toxicity, inhalation (Category 4)
 Skin irritation (Category 2)
 Eye irritation (Category 2A)
 Respiratory sensitizer (Category 1)
 Carcinogenicity (Category 1A)
 Reproductive toxicity (Category 2)
 Specific target organ toxicity, single exposure, Narcotic effects (Category 3)
 Specific target organ toxicity, repeated exposure (Category 2)

DANGER

H225: Highly flammable liquid and vapour

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled

H350: May cause cancer

H302 + H332: Harmful if swallowed or if inhaled

H319: Causes serious eye irritation
H315: Causes skin irritation
H336: May cause drowsiness or dizziness
H361D: Suspected of damaging the unborn child
H373: May cause damage to organs through prolonged or repeated exposure
P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe mist, vapours and spray.
P264: Wash skin thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P281: Use personal protective equipment as required.
P301+330+331+P310: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or physician.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or take a shower if necessary.
P332+313: If skin irritation occurs: Get medical advice or attention.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P342+311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337+313: If eye irritation persists: Get medical advice or attention.
P321: Specific treatment (see on this label).
P362+364: Take off contaminated clothing and wash before reuse.
P370+378: In case of fire: Use chemical foam, dry chemical or carbon dioxide to extinguish.
P403+P235+P233: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P501: Dispose of contents and container to an approved waste disposal plant.

3. Composition/information on ingredients

Common name	CAS	Weight % content
Ethyl alcohol	64-17-5	10 - 30 %
n-Butyl Alcohol	71-36-3	10 - 30 %
Toluene	108-88-3	7 - 13 %
Propylene glycol monomethyl ether	107-98-2	5 - 10 %
Xylene	1330-20-7	5 - 10 %
Synthetic Amorphous Fumed Silica	112945-52-5	1 - 5 %
Butyl acetate (normal)	123-86-4	1 - 5 %
Ethylene glycol monopropyl ether	2807-30-9	1 - 5 %
Methyl Propyl Ketone	107-87-9	1 - 5 %
Ethylbenzene	100-41-4	0.5 - 1.5 %
Formaldehyde	50-00-0	0.1 - 1 %
1,2,4-Trimethylbenzene	95-63-6	0.1 - 1 %

4. First-aid measures

Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
Skin contact	Wash skin with warm water and mild soap. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.
Eye contact	IMMEDIATELY flush with plenty of water. Remove contact lenses if easy to do. Flush with water for at least 15 minutes. Hold eyelids apart to rinse properly. Seek medical attention immediately.
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. If victim is conscious wash out mouth with water and give 1-2 glasses of water to drink. Never give anything by mouth if victim is unconscious or convulsing. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.
Other	No information available.
Symptoms	No information available.
Notes to the physician	Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media	Class B extinguishers. Powder carbon dioxide (CO ₂), alcohol resistant foam, Do not use a heavy water jet.
Specific hazards arising from the chemical	NFPA: Class IB Flammable liquid. Vapours are heavier than air and may travel to an ignition source distant from the material handling point. May be ignited by heat, sparks, flame or static electricity. Do not apply to hot surfaces. Contact with strong oxidizers may cause fire. In a fire or if heated, a pressure increase will occur and the container may burst. Emits toxic fumes under fire conditions.
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
Special protective actions for fire-fighters	Water stream can scatter and spread fire. If water is used, fog nozzles are preferable. Use water spray to cool fire-exposed containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
Environmental precautions	Prevent entry in sewer and other enclosed area. For a large spill, consult the Department of Environment or the relevant authorities.
Methods and materials for containment and cleaning up	Remove sources of ignition. Ventilate the area well. Stay against the wind spill. Make sure you have a fire extinguisher near you. Stop leak, if it's possible to do so without risk. Use non-sparking and antistatic tools. Absorb with inert material (soil, sand, vermiculite) or wipe up or scrape up and place in an appropriate waste disposal container clearly identified. Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water.

7. Handling and storage

Precautions for safe handling	Keep away from heat, sparks and open flame. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Use non-sparking and antistatic tools. Ground/bond all containers when transferring large quantities (5 gallons US or 20 L and more). Use
--------------------------------------	---

only in well ventilated area. Do not breathe vapours, mists or aerosols. Avoid contact with skin, eyes and clothing. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet. Keep containers tightly closed when not in use. Containers of this material may be hazardous even when empty. Since empty containers retain product residues (vapour, liquid), all hazard precautions given in this sheet must be observed. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). NFPA: Class IB Flammable liquid. Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10).

Storage temperature

10 to 25°C (50 to 77°F)

8. Exposure controls/personal protection

Immediately Dangerous to Life or Health

Ethylbenzene: 800 ppm.
 Xylenes: 900 ppm.
 Formaldehyde: 20 ppm.
 Ethyl alcohol: 3300 ppm.
 Toluene : 500 ppm.
 Methyl Propyl Ketone: 1500 ppm.
 n-Butyl acetate: 1700 ppm.
 n-Butyl Alcohol: 1400 ppm.
 Synthetic Amorphous Fumed Silica: 3000 mg/m³.

Ethyl alcohol	STEL		1000 ppm		ACGIH , BC, ON
	TWA (8h)		1000 ppm	1880 mg/m ³	AB , RSST
n-Butyl Alcohol	Ceiling		30 ppm		BC
			50 ppm	152 mg/m ³	RSST (Pc, RP)
	TWA (8h)		15 ppm		BC
			20 ppm		ACGIH , ON
Toluene			20 ppm	60 mg/m ³	AB
	TWA (8h)		20 ppm		ACGIH , BC, ON
Xylene			50 ppm	188 mg/m ³	AB , RSST
	STEL		150 ppm		ACGIH , BC, ON
Propylene glycol monomethyl ether			150 ppm	651 mg/m ³	AB , RSST
	TWA (8h)		100 ppm		ACGIH , BC, ON
			100 ppm	434 mg/m ³	AB , RSST
	STEL		100 ppm		ACGIH
Synthetic Amorphous Fumed Silica			150 ppm		ON
			150 ppm	553 mg/m ³	RSST
	TWA (8h)		50 ppm		ACGIH
			100 ppm		ON
			100 ppm	369 mg/m ³	RSST
	TWA (8h)	Respirable Dust		1.5 mg/m ³	BC
Butyl acetate (normal)		Respirable Dust		3 mg/m ³	ACGIH , ON
		Total Dust		4 mg/m ³	BC
		Respirable Dust		6 mg/m ³	NIOSH , RSST
		Total Dust		10 mg/m ³	ACGIH , ON
Butyl acetate (normal)	STEL		200 ppm		ACGIH , ON
			200 ppm	950 mg/m ³	AB , RSST
	TWA (8h)		20 ppm		BC
			150 ppm		ACGIH , ON
			150 ppm	713 mg/m ³	AB , RSST

Methyl Propyl Ketone	Ceiling	150 ppm		ACGIH , ON
	STEL	250 ppm		BC
Ethylbenzene	TWA (8h)	250 ppm	881 mg/m ³	AB
		150 ppm		BC
	STEL	150 ppm	530 mg/m ³	RSST
	TWA (8h)	200 ppm	705 mg/m ³	AB
1,2,4-Trimethylbenzene	TWA (8h)	125 ppm	543 mg/m ³	AB , RSST
		100 ppm	434 mg/m ³	ACGIH , BC, ON
Formaldehyde	Ceiling	25 ppm		ACGIH , BC, ON
		25 ppm	123 mg/m ³	AB , RSST
		0.1 ppm		NIOSH
		0.3 ppm	0.37 mg/m ³	ACGIH
	STEL	1 ppm		BC
		1 ppm	1.3 mg/m ³	AB
		1.5 ppm		ON
		2 ppm	3 mg/m ³	RSST (C2, EM, RP)
TWA (8h)	1 ppm		ON	
	0.016 ppm		NIOSH	
	0.3 ppm		BC	
		0.75 ppm	0.9 mg/m ³	AB
Appropriate engineering controls	Provide sufficient mechanical ventilation (general or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.			
Individual protection measures				
Eye	Wear safety glasses. If there is a risk of contact with eyes, wear chemical splash goggles.			
Hands	Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. If risk of contact with the liquid, use gloves nitrile or neoprene. Disposable nitrile gloves can also be used, but discard after single use.			
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear a long-sleeved shirt. Wear synthetic apron, if necessary, to prevent repeated or prolonged contact with skin.			
Respiratory	Where the conditions in the workplace require a respirator, it is necessary to follow a respiratory protection program. Moreover, respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and standard 29 CFR 1910.134 (OSHA), ANSI Z88.2 or CSA Z 94.11 (Canada) and approved by NIOSH/MSHA. In case of insufficient ventilation or in enclosed area until maximum 10 times of exposure limit, wear half mask respirator with organic vapors cartridges.			
Feet	Wear rubber boots to clean up a spill.			

9. Physical and chemical properties

Physical state	Liquid	Flammability	Flammable.
Colour	Clear or coloured	Flammability limits	1.5 to 10.9%
Odour	Solvent odor	Flash point	5.6°C (42.1°F)
Odour threshold	N/Av.	Auto-ignition temperature	N/Av.
pH	N/Av.		Yes

		Sensibility to electrostatic charges	
Melting point	N/Av.	Sensibility to sparks and/or friction	N/Av.
Freezing point	N/Av.	Vapour density	>1 (Air = 1)
Boiling point	120°C (248°F)	Relative density	0.948 kg/L (Water = 1)
Solubility	No	Partition coefficient n-octanol/water	N/Av.
Evaporation rate	> Butyl Acetate	Decomposition temperature	N/Av.
Vapour pressure	N/Av.	Viscosity	N/Av.
Percent Volatile	73.45%	Molecular mass	N/Av.
N/Av.: Not Available N/Av.: Not Available Und.: Undetermined N/E: Not Established			

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions (including polymerizations)	A dangerous reaction will not occur.
Conditions to avoid	Avoid heat, flame and sparks. Avoid contact with incompatible materials.
Incompatible materials	Strong oxidants, strong bases, mineral acids, strong acids.
Hazardous decomposition products	In combustion: nitrogen oxides, carbon oxides (CO, CO ₂).

11. Toxicological information

Numerical measures of toxicity	n-Butyl Alcohol	Ingestion	790 mg/kg	Rat	LD50
		Inhalation	24.2 mg/l/4h	Rat	LC50
		Skin	3400 mg/kg	Rabbit	LD50
	Ethyl alcohol	Ingestion	7060 mg/kg	Rat	LD50
		Inhalation	39 mg/l/4h	Mouse	LC50
		Skin	20000 mg/kg	Rabbit	LD50
	Toluene	Ingestion	5600 mg/kg	Rat	LD50
		Inhalation	30.2 mg/l/4h	Rat	LC50
		Skin	12600 mg/kg	Rabbit	LD50
	Propylene glycol monomethyl ether	Ingestion	6600 mg/kg	Rat	LD50
		Inhalation	36.4 mg/l/4h	Rat	LC50
		Skin	13000 mg/kg	Rabbit	LD50
	Xylene	Ingestion	3523 mg/kg	Rat	LD50
		Inhalation	27.6 mg/l/4h	Rat	LC50
		Skin	3200 mg/kg	Rabbit	LD50
	Butyl acetate (normal)	Ingestion	10768 mg/kg	Rat	LD50
		Inhalation	>32.5 mg/l/4h	Rat	LC50
		Skin	>17600 mg/kg	Rabbit	LD50
Ethylene glycol monopropyl ether	Ingestion	3089 mg/kg	Rat	LD50	
	Inhalation	>11.13 mg/l/4h	Rat	LC50	
	Skin	883 mg/kg	Rabbit	LD50	


	Methyl Propyl Ketone	Ingestion 3730 mg/kg 1600 mg/kg	Rat LD50 Mouse LD50
		Inhalation 11 mg/l/4h	Rat LC50
		Skin 6472 mg/kg	Rabbit LD50
	Synthetic Amorphous Fumed Silica	Ingestion >5000 mg/kg	Rat LD50
		Inhalation >2.08 mg/l/4h	Rat LC50
		Skin >5000 mg/kg	Rabbit LD50
	Ethylbenzene	Ingestion 3500 mg/kg	Rat LD50
		Inhalation 17.3 mg/l/4h	Rat LC50
		Skin 15380 mg/kg	Rabbit LD50
	1,2,4-Trimethylbenzene	Ingestion 5000 mg/kg	Rat LD50
		Inhalation 18 mg/l/4h	Rat LC50
		Skin >3160 mg/kg	Rabbit LD50
	Formaldehyde	Ingestion 42 mg/kg	Mouse LD50
		Inhalation 250 ppm/4h	Rat LC50
		414 ppm/4h	Mouse LC50
		Skin 270 mg/kg	Rabbit LD50
Likely routes of exposure	Skin, eyes, inhalation, ingestion.		
Delayed, immediate and chronic effects	Eye contact	May cause eye irritation. May cause a burning sensation.	
	Skin contact	May cause skin irritation. Prolonged and repeated contact may cause drying and cracking of the skin. Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed. Aqueous formaldehyde solutions cause skin sensitization. However, free formaldehyde gas does not cause skin sensitization.	
	Inhalation	Excessive inhalation is harmful. May cause slight upper respiratory tract irritation. High concentrations may cause central nervous system depression characterized by headache, dizziness, nausea, fatigue, drowsiness, unconsciousness. asphyxia. The severity of symptoms may vary depending on exposure conditions. Formaldehyde can cause asthma attacks due to allergic sensitization of the respiratory tract. Prolonged and repeated exposure may cause damage to liver, kidneys, lungs and blood forming organs.	
	Ingestion	Harmful if swallowed. May cause gastrointestinal irritation with nausea and vomiting. Contains a substance that can cause target organ damage, according to data obtained on animals.	
	IARC/NTP Classification	Common name IARC NTP Ethylbenzene 2B - Formaldehyde 1 R IARC : 1- Carcinogenic; 2A- Probably carcinogenic; 2B- Possibly carcinogenic. NTP : K- Known to be carcinogens; R- Reasonably anticipated to be carcinogens.	
	Carcinogenicity	Contains trace amounts (>0.1%) of free formaldehyde (CAS no. 50-00-0) which is classified as carcinogenic to humans (IARC, Group 1). Contains an ingredient possibly carcinogenic to humans (Group 2B, IARC). Ethylbenzene (CAS no. 100-41-4). The risk of cancer depends on duration and level of exposure.	
	Teratogenicity	This material is not known to cause teratogenic effect.	
	Mutagenicity	This material is not known to cause mutagenic effect.	
	Reproductive toxicity	Toluene present a risk of toxicity on development based on animal study. An epidemiological study (1992) has been done with women exposed only to toluene in a factory. The first group was exposed to ambient concentrations from 50 to 150 ppm and the second at concentrations from 0 to 25 ppm. Comparison with a control group demonstrated a higher spontaneous abortions rates significantly in women exposed to higher concentrations than those of little or no exposure group. Xylene overexposure may affect fetal development in laboratory animals by inhalation during pregnancy.	
	Immunotoxicity	No information available.	
Interactive effects	No information available for this product.		
Other information	Target organs: central nervous system, kidneys, liver, lungs. respiratory system, blood forming organs. The acute toxicity estimate (ATE) by inhalation of the mixture was calculated to be greater than 10 mg/L/4h but		

lower than 20 mg/L/4h. This value is classified according to GHS: Acute toxicity, inhalation (Category 4). The oral acute toxicity estimate (ATE) of the mixture was calculated to be greater than 300 mg/Kg but lower than 2000 mg/kg. This value is classified according to GHS: Acute toxicity, oral (Category 4). The skin acute toxicity estimate (ATE) of the mixture was calculated to be greater than 2000 mg/kg. This value is not classified according to WHMIS and OSHA HCS 2012.


12. Ecological information

Ecological toxicity	N/Av. LC50 N/Av.
Persistence	No information available for this product.
Degradability	No information available for this product.
Bioaccumulative potential	No information available for this product.
Mobility in soil	No information available for this product.
Other adverse effects	No information available for this product.

13. Disposal considerations

	<p>Important! Prevent waste generation. Use in full. DO NOT dispose residue in sewers, streams or drinking water supply. Paint residues, including lacquers, dyes, shellacs, varnishes, paint solvents and thinners, can be reprocessed where there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.</p>
---	---

14. Transport information

UN Number	UN 1263
UN Proper Shipping Name	PAINT
Environmental hazards	This material is not listed as a marine pollutant.
Special precautions for user	No information available.
TDG - Transportation of Dangerous Goods (Canada)	
Transport hazard class(es)	 Class 3
Packing group	II
IMO/IMDG - International Maritime Transport	
Classification	Regulated UN 1263. Class 3, PG II.
IATA - International Air Transport Association	
Classification	Regulated UN 1263. Class 3, PG II.

15. Regulatory information

Other regulations

UNITED STATE OF AMERICA:

- Toxic Substance Control Act (TSCA) :

All ingredients are listed in the TSCA Inventory.

- EPCRA Section 313 Toxic Chemicals:

n-Butyl Alcohol (CAS no. 71-36-3).

Ethylbenzene (CAS no. 100-41-4).

Xylenes (CAS no. 1330-20-7).

1,2,4-Trimethylbenzene (CAS no. 95-63-6).

Toluene (CAS no. 108-88-3).

Formaldehyde (CAS no. 50-00-0).

- California Proposition 65:

Contains ingredients that can cause cancer according to the state of California.

Formaldehyde (CAS no. 50-00-0).

Ethylbenzene (CAS no. 100-41-4).

This product contains chemicals known to the State of California to cause birth defects or other reproductive harm.

Toluene (CAS no. 108-88-3).

CANADA :

- Canada DSL and NDSL:

All ingredients are listed in the Domestic Substances List (DSL).

- Canadian National Pollutant Release Inventory Substances (NPRI):

Ethylbenzene (CAS no. 100-41-4).

Xylenes (CAS no. 1330-20-7).

Ethyl alcohol (CAS no. 64-17-5).

Formaldehyde (CAS no. 50-00-0).

Toluene (CAS no. 108-88-3).

n-Butyl acetate (CAS no. 123-86-4).

1,2,4-Trimethylbenzene (CAS no. 95-63-6).

n-Butyl Alcohol (CAS no. 71-36-3).

WHMIS 1988



B2 D2A D2B

Class B2 : Flammable Liquid

Class D2A : Very toxic material causing other toxic effects

Class D2B : Toxic material causing other toxic effects

HMIS



① Protective Equipment

NFPA



16. Other information

Date
(YYYY-MM-DD)

GEMINI INDUSTRIES, INC. 2014-04-14

Version

01

**Other
information**

REFERENCES:

- NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, <http://www.cdc.gov/niosh/npg/npg.html>
- IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), <http://www.inchem.org>
- Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), <http://www.reptox.csst.qc.ca>
- IUCLID Chemical Dataset, European Chemical Substances Information System (ESIS), Joint Research Centre, <http://esis.jrc.ec.europa.eu>

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

HMIS: Hazardous Materials Identification System

NFPA: National Fire Protection Association

OSHA: Occupational Safety and Health Administration (USA)

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

RSST: Règlement sur la santé et la sécurité du travail (Québec)

GHS: Globally Harmonized System

IARC: International Agency for Research on Cancer

IDLH: Immediately Dangerous to Life or Health

STEL: Short Term Exposure Limit (15 min)

TWA: Time Weighted Averages

WHMIS: Workplace Hazardous Materials Information System

To the best of our knowledge, the information contained herein is accurate. However, neither Priziventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.