



Safety Data Sheet

HC GEM COAT PRECAT SATIN



1. Identification

Product identifier	HC GEM COAT PRECAT SATIN		
Product code	PC-0030		
Other means of identification	None.		
Recommended use of the chemical and restrictions on use	A protective and/or decorative finish or accompanying paint product. Not recommended for any other use not detailed on product data sheet or label.		
Manufacturer	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 USA Tel. 1-800-262-5710 Fax 1-405-262-9310 www.geminicoatings.com		
Emergency phone number	24-hour Emergency (Spill, Leak, Exposure or accident) INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English) HAZMAT Response and MSDS Help: EMI 800-510-8510		

2. Hazard identification

Summary	FLAMABLE LIQUID! Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved.
----------------	--

WHMIS 2015/OSHA HCS 2012/GHS

Flammable liquids (Category 2)
 Skin corrosion/irritation (Category 2)
 Serious eye damage/eye irritation (Category 1)
 Germ cell mutagenicity (Category 1)
 Carcinogenicity (Category 1)
 Reproductive toxicity (Category 1)
 Specific target organ toxicity, single exposure (Category 3)
 Specific target organ toxicity, repeated exposure (Category 2)
 Aspiration hazard (Category 1)



Other hazards which do not result in classification :

Acute hazard to the aquatic environment (Category 2).

DANGER

H225: Highly flammable liquid and vapour
 H318: Causes serious eye damage
 H350: May cause cancer
 H340: May cause genetic defects

H360: May damage fertility or the unborn child
H304: May be fatal if swallowed and enters airways
H315: Causes skin irritation
H335: May cause respiratory irritation
H336: May cause drowsiness or dizziness
H373: May cause damage to organs through prolonged or repeated exposure by inhalation
H401: Toxic to aquatic life
P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.
P240: Ground or bond container and receiving equipment.
P241: Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe mist, vapours and spray.
P264: Wash skin thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves, protective clothing and eye protection.
P301+310+331: IF SWALLOWED: Immediately call a POISON CENTER or a physician. Do NOT induce vomiting.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or take a shower if necessary.
P332+313: If skin irritation occurs: Get medical advice or attention.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P310: Immediately call a doctor/physician.
P308+313: IF exposed or concerned: Get medical advice/attention.
P321: Specific treatment (see section 4 of SDS or on this label).
P362+364: Take off contaminated clothing and wash before reuse.
P370+378: In case of fire: Use the National Fire Protection Association Class B extinguisher for extinction.
P403+P235+P233: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P405: Store locked up.
P501: Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

3. Composition/information on ingredients

Common name	CAS	Weight % content
Toluene	108-88-3	15 - 17 %
Butyl acetate (normal)	123-86-4	12 - 14 %
n-Butyl Alcohol	71-36-3	10 - 12 %
Ethyl Alcohol	64-17-5	9 - 11 %
Nitrocellulose	9004-70-0	7.5 - 8.5 %
Acetone	67-64-1	5.5 - 6.5 %
Isobutyl isobutyrate	97-85-8	5.5 - 6.5 %
Urea, polymer with formaldehyde, isobutylated	68002-18-6	5.5 - 6.5 %
Isopropyl alcohol	67-63-0	2.5 - 3.5 %
Bis(2-Ethylhexyl) adipate	103-23-1	2.5 - 3.5 %
Isobutyl alcohol	78-83-1	1.5 - 2.5 %
Xylene	1330-20-7	1.5 - 2.5 %

Ethylbenzene	100-41-4	0.1 - 1 %
--------------	----------	-----------

4. First-aid measures

Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
Skin contact	Wash skin with warm water and mild soap for at least 15 minutes. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.
Eye contact	IMMEDIATELY! Flush with water for at least 15 minutes. Remove contact lenses. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If victim is conscious wash out mouth with water. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.
Other	No information available.
Symptoms	May cause severe eye irritation or eye damage. May cause skin irritation. May cause respiratory tract irritation. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. Aspiration hazard for the lungs (ingestion/vomiting). Can enter lungs and cause damage. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking and gagging are often noted at the time of aspiration.
Notes to the physician	Treat symptomatically. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire-fighting measures

Suitable extinguishing media	Class B extinguishers. Dry chemicals, alcohol resistant foam, carbon dioxide (CO ₂). Do not use direct water jet.
Specific hazards arising from the chemical	Very flammable liquid and vapours. May be ignited by heat, sparks, flame or static electricity. Vapours are heavier than air and may travel to an ignition source distant from the material handling point. Do not apply to hot surfaces. Contact with strong oxidizers may cause fire. In a fire or if heated, a pressure increase will occur and the container may burst. Emits toxic fumes under fire conditions.
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
Special protective actions for fire-fighters	Use water spray to cool fire-exposed containers. Water spray can reduce the intensity of the flames. However, the water jets can spread the fire. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
Environmental precautions	Prevent entry in sewer and other enclosed area. For a large spill, consult the Department of Environment or the relevant authorities.
Methods and materials for	Remove sources of ignition. Ventilate the area well. Absorb with inert material (soil, sand, vermiculite) and place in an appropriate waste disposal clearly identified. Use non-sparking and antistatic tools.

containment and cleaning up	Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water. PS: Rags and others materials soaked with paint or solvent may spontaneously catch fire if improperly store or discarded. Immediately after each use place rags and paper towels in a sealed water-filled metal container to prevent spontaneous combustion.
------------------------------------	--

7. Handling and storage

Precautions for safe handling	Keep away from heat, sparks and open flame. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Use non-sparking and antistatic tools. Use only in well ventilated area. Avoid prolonged or repeated breathing of vapour or mists. Avoid contact with skin, eyes and clothing. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. Keep containers tightly closed when not in use. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse. Rags, steel wool and paper towels soaked with this product may overheat and spontaneously ignite if piled in a heap. After use immediately store them in water-filled metal can with tight fitting lid.
Conditions for safe storage, including any incompatibilities	Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10). Keep away from direct sunlight and heat.
Storage temperature	10 to 25°C (50 to 77°F)

8. Exposure controls/personal protection

Immediately Dangerous to Life or Health	Toluene: 500 ppm n-Butyl acetate: 1700 ppm. Ethyl alcohol: 3300 ppm. n-Butyl Alcohol: 1400 ppm. Acetone: 2500 ppm. Isopropyl alcohol: 2000 ppm. Isobutyl alcohol: 1600 ppm. Xylenes: 900 ppm. Ethylbenzene: 800 ppm.		
--	--	--	--

Toluene	TWA (8h)	20 ppm		ACGIH , BC, ON
		50 ppm	188 mg/m ³	RSST (Pc)
Butyl acetate (normal)	STEL	200 ppm		ACGIH , ON
		200 ppm	950 mg/m ³	RSST
	TWA (8h)	20 ppm		BC
		150 ppm		ACGIH , ON
		150 ppm	713 mg/m ³	RSST
n-Butyl Alcohol	Ceiling	30 ppm		BC
		50 ppm	152 mg/m ³	RSST (Pc, RP)
	TWA (8h)	15 ppm		BC
		20 ppm		ACGIH , ON
Ethyl Alcohol	STEL	1000 ppm		ACGIH , ON
		1000 ppm	1880 mg/m ³	RSST
Acetone	STEL	500 ppm		ACGIH , BC
		750 ppm	1782 mg/m ³	ON
		1000 ppm	2380 mg/m ³	RSST
	TWA (8h)	250 ppm		ACGIH , BC
		500 ppm	1188 mg/m ³	ON
		500 ppm	1190 mg/m ³	RSST

Isopropyl alcohol	STEL	400 ppm		ACGIH , BC, ON
		500 ppm	1230 mg/m ³	RSST
Xylene	TWA (8h)	200 ppm		ACGIH , BC, ON
		400 ppm	983 mg/m ³	RSST
	STEL	150 ppm		ACGIH , BC, ON
		150 ppm	651 mg/m ³	RSST
TWA (8h)	100 ppm		ACGIH , BC, ON	
	100 ppm	434 mg/m ³	RSST	
Isobutyl alcohol	TWA (8h)	50 ppm		ACGIH , BC, ON
		50 ppm	152 mg/m ³	RSST
Ethylbenzene	STEL	125 ppm	543 mg/m ³	RSST
		20 ppm		ACGIH , BC, ON
		100 ppm	434 mg/m ³	RSST

Appropriate engineering controls	Provide sufficient mechanical ventilation (general and/or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.
---	---

Individual protection measures

Eye	Wear chemical splash goggles.
Hands	Wear nitrile or neoprene gloves. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly.
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. If necessary, wear an apron or long-sleeve protective coverall suit.
Respiratory	Respiratory protection is not required for normal use. Respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and CSA Standard Z 94.4 and approved by NIOSH / MSHA. In case of insufficient ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times the exposure limit, wear a half mask respirator with organic vapour cartridges fitted with P100 filters. For an APF until maximum 100 times of exposure limit, wear a full face respirator mask with organic vapour cartridges and P100 filters.
Feet	Wear rubber boots to clean up a spill.

9. Physical and chemical properties

Physical state	Liquid	Flammability	Flammable
Colour	Clear or coloured	Flammability limits	N/Av.
Odour	Solvent odor	Flash point	0°C (32°F)
Odour threshold	N/Av.	Auto-ignition temperature	170°C (338°F)
pH	N/Av.	Sensibility to electrostatic charges	Yes
Melting point	N/Av.	Sensibility to sparks and/or friction	N/Av.
Freezing point	N/Av.	Vapour density	>1 (Air = 1)
Boiling point	56 to 214°C (132.8 to 417.2°F)	Relative density	0.922 kg/L (Water = 1)
Solubility	Partially soluble in water.	Partition coefficient n-octanol/water	N/Av.

Evaporation rate	> Butyl Acetate	Decomposition temperature	N/Av.
Vapour pressure	N/Av.	Viscosity	N/Av.
Percent Volatile	72.69%	Molecular mass	N/Av.
N/Av.: Not Available N/Av.: Not Applicable Und.: Undetermined N/E: Not Established			

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions (including polymerizations)	A dangerous reaction will not occur.
Conditions to avoid	Avoid heat, flame and sparks. Avoid electro-static discharge. Avoid contact with incompatible materials.
Incompatible materials	Strong bases, mineral acids, strong oxidizing agents (such as nitric acid, perchloric acid, peroxides, chlorates and perchlorates).
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Numerical measures of toxicity	Toluene	Ingestion 5600 mg/kg	Rat	LD50
		Inhalation 30.2 mg/l/4h	Rat	LC50
		Skin 12600 mg/kg	Rabbit	LD50
	Butyl acetate (normal)	Ingestion 10768 mg/kg	Rat	LD50
		Inhalation >32.5 mg/l/4h	Rat	LC50
		Skin >17600 mg/kg	Rabbit	LD50
	n-Butyl Alcohol	Ingestion 790 mg/kg	Rat	LD50
		Inhalation 24.2 mg/l/4h	Rat	LC50
		Skin 3400 mg/kg	Rabbit	LD50
	Ethyl Alcohol	Ingestion 7060 mg/kg	Rat	LD50
		Inhalation 39 mg/l/4h	Mouse	LC50
		Skin 20000 mg/kg	Rabbit	LD50
	Nitrocellulose	Ingestion >5000 mg/kg	Rat	LD50
	Acetone	Ingestion 5800 mg/kg	Rat	LD50
		Inhalation 71.4 mg/l/4h	Rat	LC50
		Skin 15800 mg/kg	Rabbit	LD50
	Isobutyl isobutyrate	Ingestion 12800 mg/kg	Rat	LD50
		Inhalation >5000 ppm/6h	Rat	LC50
		48.2 mg/l/4h	Rat	LC50
		Skin >8600 mg/kg	Rabbit	LD50
	Urea, polymer with formaldehyde, isobutylated	Ingestion >5000 mg/kg	Rat	LD50
		Skin >5000 mg/kg	Rabbit	LD50
	Bis(2-Ethylhexyl) adipate	Ingestion 9100 mg/kg	Rat	LD50
		Inhalation >5.7 mg/l/4h	Rat	LC50
	Skin 17297 mg/kg	Rabbit	LD50	
Isopropyl alcohol	Ingestion 5045 mg/kg	Rat	LD50	
	Inhalation 66.1 mg/l/4h	Rat	LC50	
	Skin 6280 mg/kg	Rat	LD50	
Isobutyl alcohol	Ingestion 2460 mg/kg	Rat	LD50	

		<p>Inhalation 19.2 mg/l/4h Rat LC50</p> <p>Skin 3400 mg/kg Rabbit LD50</p> <p>Xylene Ingestion 3523 mg/kg Rat LD50</p> <p>Inhalation 27.6 mg/l/4h Rat LC50</p> <p>Ethylbenzene Skin 3200 mg/kg Rabbit LD50</p> <p>Ingestion 3500 mg/kg Rat LD50</p> <p>Inhalation 17.3 mg/l/4h Rat LC50</p> <p>Skin 15380 mg/kg Rabbit LD50</p>
Likely routes of exposure	Skin, eyes, inhalation, ingestion.	
Delayed, immediate and chronic effects	<p>Eye contact May cause severe eye irritation or eye damage. Butyl Alcohol instilled in rabbit eyes resulted in severe corneal irritation and eye damage (OECD 405). Application in excess of 5% dilution solution gave irritating effect. Isobutyl alcohol is a severe eye irritant in rabbits (OECD 405). Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with the other ingredients of this mixture gave not irritating to irritating results.</p> <p>Skin contact May cause redness, dryness, rash and skin irritation. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient of this mixture gave not irritating to irritating results. Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed.</p> <p>Inhalation Excessive inhalation is harmful. May cause respiratory tract irritation. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. The severity of symptoms may vary depending on exposure conditions. Prolonged or repeated exposure may cause capable of damaging the target organ.</p> <p>Ingestion Ingestion of large amounts may cause depression of the central nervous system characterized by headache, dizziness, convulsions and loss of consciousness. Harmful or fatal if inhaled into the lungs (ingestion/vomiting). Can enter lungs and cause damage. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discolouration of the skin. Coughing, choking and gagging are often noted at the time of aspiration.</p> <p>Respiratory or skin sensitization Ingredients present at levels greater than or equal to 0.1% of this product are not skin or respiratory sensitizers.</p> <p>IARC/NTP Classification Common name IARC NTP Ethylbenzene 2B - IARC : 1- Carcinogenic; 2A- Probably carcinogenic; 2B- Possibly carcinogenic. NTP : K- Known to be carcinogens; R- Reasonably anticipated to be carcinogens.</p> <p>Carcinogenicity Contains material which can cause cancer. There is sufficient evidence for the carcinogenicity of alcoholic (Ethanol) beverages in humans (IARC). The occurrence of malignant tumors of the oral cavity, pharynx, larynx, oesophagus, liver, breast and colorectal is causally related to the excessive consumption of alcoholic beverages.</p> <p>Mutagenicity Ethyl Alcohol has showed positive results in dominant lethal tests by oral and intraperitoneal administration to mice and oral administration to rats (in vivo heritable germ cell mutagenicity tests) (SIDS (2009), IARC (1988)). There are also reports of negative Ames tests from in vitro mutagenicity tests SIDS (2009).</p> <p>Reproductive toxicity Toluene has an embryotoxic and/or fetotoxic hazard in humans (US EPA, 2005). A significant and prolonged consumption of ethyl alcohol during pregnancy can cause an increased risk of developmental abnormalities fetus humans.</p> <p>Specific target organ toxicity - single exposure Central nervous system, respiratory system.</p> <p>Specific target organ toxicity - repeated exposure Central nervous system, respiratory system, hearing organs, kidneys, liver.</p>	
Interactive effects	No information available for this product.	
Other information	The acute toxicity estimate (ATE) by inhalation of the mixture was calculated to be greater than 20 mg/L/4h. This value is not classified according to GHS. The oral and skin acute toxicity estimates (ATE) of the mixture	

were calculated to be greater than 2000 mg/kg. These values are not classified according to WHMIS 2015 and OSHA HCS 2012.

12. Ecological information

Ecological toxicity	<table border="0"> <tbody> <tr> <td>Fish - Pimephales promelas [flow-through]</td> <td>LC50 18 mg/L; 96h (Butyl acetate)</td> </tr> <tr> <td>Aquatic Plant - Algae, Desmodesmus subspicatus</td> <td>EC50 675 mg/L; 72h (Butyl acetate)</td> </tr> <tr> <td>Fish - Pimephales promelas - Fresh water</td> <td>LC50 1370-1670 mg/L; 96 h (Isobutyl alcohol)</td> </tr> <tr> <td>Aquatic Invertebrate - Daphnia magna</td> <td>EC50 1300 mg/L; 48 h (Isobutyl alcohol)</td> </tr> <tr> <td>Fish - Oncorhynchus mykiss - Rainbow trout</td> <td>LC50 13.5-17.3 mg/L; 96 h (Xylene)</td> </tr> <tr> <td>Aquatic Invertebrate - Daphnia magna</td> <td>EC50 3.82 mg/L; 48 h (Xylene)</td> </tr> <tr> <td>Fish - Oncorhynchus mykiss - Rainbow trout</td> <td>LC50 5.8 mg/L; 96 h (Toluene)</td> </tr> <tr> <td>Aquatic Invertebrate - Daphnia magna</td> <td>EC50 5.46-9.83 mg/L; 48 h (Toluene)</td> </tr> <tr> <td>Aquatic Invertebrate - Daphnia magna</td> <td>EC50 1983 mg/L; 48h (n-Butyl Alcohol) OECD 202</td> </tr> <tr> <td>Fish - Pimephales promelas [static]</td> <td>LC50 376 mg/L; 96h (n-Butyl Alcohol) OECD 203</td> </tr> <tr> <td>Algae - Desmodesmus subspicatus</td> <td>EC50 >500mg/L; 72h (n-Butyl Alcohol)</td> </tr> <tr> <td>Fish - Oncorhynchus mykiss - Rainbow trout</td> <td>LC50 4740 mg/L; 96 h (acetone)</td> </tr> <tr> <td>Aquatic Invertebrate - Daphnia magna</td> <td>EC50 12600-12700 mg/L; 48 h (acetone)</td> </tr> <tr> <td>Fish - Pimephales promelas [flow-through]</td> <td>LC50 13400-15100 mg/L; 96 h (ethyl alcohol)</td> </tr> <tr> <td>Aquatic Invertebrate - Daphnia magna</td> <td>EC50 9268-14221 mg/L; 48 h (ethyl alcohol)</td> </tr> <tr> <td>Algae, Pseudokirchneriella subcapitata</td> <td>EC50 579 mg/L; 96h (Nitrocellulose)</td> </tr> <tr> <td>Fish - Fathead minnow, Pimephales promelas - fresh water</td> <td>LC50 12.54 mg/L; 96h (Isobutyl isobutyrate)</td> </tr> <tr> <td>Crustacea - Water Flea (Daphnia magna)</td> <td>EC50 55.8 mg/L; 96h (Isobutyl isobutyrate)</td> </tr> <tr> <td>Fish - Fathead minnow, Pimephales promelas - fresh water</td> <td>LC50 9640 mg/L; 96 h (Isopropyl alcohol)</td> </tr> <tr> <td>Aquatic Invertebrate - Crustaceans, Daphnia Magna</td> <td>EC50 3644 mg/L; 48 h (Isopropyl alcohol)</td> </tr> <tr> <td>Plant - Lettuce seed germination, Lactuca Sativa</td> <td>EC50 2100 mg/L; 72 h (Isopropyl alcohol)</td> </tr> <tr> <td>Fish - Oryzias latipes</td> <td>LC50 >100 mg/L; 96h (Bis(2-Ethylhexyl) adipate) OECD 203</td> </tr> <tr> <td>Aquatic Invertebrate - Daphnia magna</td> <td>EC50 >500 mg/L; 48h (Bis(2-Ethylhexyl) adipate) OECD 202</td> </tr> </tbody> </table>	Fish - Pimephales promelas [flow-through]	LC50 18 mg/L; 96h (Butyl acetate)	Aquatic Plant - Algae, Desmodesmus subspicatus	EC50 675 mg/L; 72h (Butyl acetate)	Fish - Pimephales promelas - Fresh water	LC50 1370-1670 mg/L; 96 h (Isobutyl alcohol)	Aquatic Invertebrate - Daphnia magna	EC50 1300 mg/L; 48 h (Isobutyl alcohol)	Fish - Oncorhynchus mykiss - Rainbow trout	LC50 13.5-17.3 mg/L; 96 h (Xylene)	Aquatic Invertebrate - Daphnia magna	EC50 3.82 mg/L; 48 h (Xylene)	Fish - Oncorhynchus mykiss - Rainbow trout	LC50 5.8 mg/L; 96 h (Toluene)	Aquatic Invertebrate - Daphnia magna	EC50 5.46-9.83 mg/L; 48 h (Toluene)	Aquatic Invertebrate - Daphnia magna	EC50 1983 mg/L; 48h (n-Butyl Alcohol) OECD 202	Fish - Pimephales promelas [static]	LC50 376 mg/L; 96h (n-Butyl Alcohol) OECD 203	Algae - Desmodesmus subspicatus	EC50 >500mg/L; 72h (n-Butyl Alcohol)	Fish - Oncorhynchus mykiss - Rainbow trout	LC50 4740 mg/L; 96 h (acetone)	Aquatic Invertebrate - Daphnia magna	EC50 12600-12700 mg/L; 48 h (acetone)	Fish - Pimephales promelas [flow-through]	LC50 13400-15100 mg/L; 96 h (ethyl alcohol)	Aquatic Invertebrate - Daphnia magna	EC50 9268-14221 mg/L; 48 h (ethyl alcohol)	Algae, Pseudokirchneriella subcapitata	EC50 579 mg/L; 96h (Nitrocellulose)	Fish - Fathead minnow, Pimephales promelas - fresh water	LC50 12.54 mg/L; 96h (Isobutyl isobutyrate)	Crustacea - Water Flea (Daphnia magna)	EC50 55.8 mg/L; 96h (Isobutyl isobutyrate)	Fish - Fathead minnow, Pimephales promelas - fresh water	LC50 9640 mg/L; 96 h (Isopropyl alcohol)	Aquatic Invertebrate - Crustaceans, Daphnia Magna	EC50 3644 mg/L; 48 h (Isopropyl alcohol)	Plant - Lettuce seed germination, Lactuca Sativa	EC50 2100 mg/L; 72 h (Isopropyl alcohol)	Fish - Oryzias latipes	LC50 >100 mg/L; 96h (Bis(2-Ethylhexyl) adipate) OECD 203	Aquatic Invertebrate - Daphnia magna	EC50 >500 mg/L; 48h (Bis(2-Ethylhexyl) adipate) OECD 202
Fish - Pimephales promelas [flow-through]	LC50 18 mg/L; 96h (Butyl acetate)																																														
Aquatic Plant - Algae, Desmodesmus subspicatus	EC50 675 mg/L; 72h (Butyl acetate)																																														
Fish - Pimephales promelas - Fresh water	LC50 1370-1670 mg/L; 96 h (Isobutyl alcohol)																																														
Aquatic Invertebrate - Daphnia magna	EC50 1300 mg/L; 48 h (Isobutyl alcohol)																																														
Fish - Oncorhynchus mykiss - Rainbow trout	LC50 13.5-17.3 mg/L; 96 h (Xylene)																																														
Aquatic Invertebrate - Daphnia magna	EC50 3.82 mg/L; 48 h (Xylene)																																														
Fish - Oncorhynchus mykiss - Rainbow trout	LC50 5.8 mg/L; 96 h (Toluene)																																														
Aquatic Invertebrate - Daphnia magna	EC50 5.46-9.83 mg/L; 48 h (Toluene)																																														
Aquatic Invertebrate - Daphnia magna	EC50 1983 mg/L; 48h (n-Butyl Alcohol) OECD 202																																														
Fish - Pimephales promelas [static]	LC50 376 mg/L; 96h (n-Butyl Alcohol) OECD 203																																														
Algae - Desmodesmus subspicatus	EC50 >500mg/L; 72h (n-Butyl Alcohol)																																														
Fish - Oncorhynchus mykiss - Rainbow trout	LC50 4740 mg/L; 96 h (acetone)																																														
Aquatic Invertebrate - Daphnia magna	EC50 12600-12700 mg/L; 48 h (acetone)																																														
Fish - Pimephales promelas [flow-through]	LC50 13400-15100 mg/L; 96 h (ethyl alcohol)																																														
Aquatic Invertebrate - Daphnia magna	EC50 9268-14221 mg/L; 48 h (ethyl alcohol)																																														
Algae, Pseudokirchneriella subcapitata	EC50 579 mg/L; 96h (Nitrocellulose)																																														
Fish - Fathead minnow, Pimephales promelas - fresh water	LC50 12.54 mg/L; 96h (Isobutyl isobutyrate)																																														
Crustacea - Water Flea (Daphnia magna)	EC50 55.8 mg/L; 96h (Isobutyl isobutyrate)																																														
Fish - Fathead minnow, Pimephales promelas - fresh water	LC50 9640 mg/L; 96 h (Isopropyl alcohol)																																														
Aquatic Invertebrate - Crustaceans, Daphnia Magna	EC50 3644 mg/L; 48 h (Isopropyl alcohol)																																														
Plant - Lettuce seed germination, Lactuca Sativa	EC50 2100 mg/L; 72 h (Isopropyl alcohol)																																														
Fish - Oryzias latipes	LC50 >100 mg/L; 96h (Bis(2-Ethylhexyl) adipate) OECD 203																																														
Aquatic Invertebrate - Daphnia magna	EC50 >500 mg/L; 48h (Bis(2-Ethylhexyl) adipate) OECD 202																																														
Persistence	May be persistent in the environment.																																														
Degradability	<p>Toluene in air is rapidly decomposed by photochemical processes, mainly through oxidation by hydroxyl free radicals as well as some decomposition by direct photolysis. The half-life time in air is estimated to be from 1 to 2 days. Toluene is Biodegradable (100% in 10 days, OECD 301C). Its Biochemical Oxygen Demand (BOD) is 2150 mg O₂/L (IUCLID) and its Chemical Oxygen Demand (COD) is 2520 mg O₂/g (IUCLID). n-Butyl acetate is readily biodegradable (96% in 28 days) OECD Guideline 301D. n-Butyl Alcohol is readily biodegradable. Degradation by Biochemical Oxygen Demand BOD (O₂ consumption) was reported as 92% after 20 days. Ethanol is readily biodegradable under aerobic and anaerobic conditions (OECD Test Guideline 301D). Degradation of Nitrocellulose involves complex dissociation into a wide variety of products. Since it is not soluble in water, the biodegradation by a sludge-soil mixture will be done over a long period of time (TOXNET). Acetone is readily biodegradable at 91% in 28 days (OECD 301B). Data specific to the biodegradation of Isobutyl isobutyrate were not located; however, based on similar aliphatic esters, Isobutyl isobutyrate is expected to biodegrade readily (SRC). Isopropyl alcohol is biodegradable, 49% in 5 days and 70% in 20 days (TOXNET). It does not undergo photolysis. Its atmospheric degradation (OH radical attack) in air has a half-time T_{1/2} of 18 to 25 hours. Bis(2-Ethylhexyl) adipate is readily biodegradable >90% in 28 days (OECD Guideline 301F). Isobutyl alcohol is readily biodegradable, 74% in 28 days (OCDE 301D). Xylene in air is rapidly decomposed by photochemical processes, mainly through oxidation by hydroxyle free radicals as well as some decomposition by direct photolysis. The half-life time in air is estimated to be from 9.5 to 19.7 hours depending to the isomer. Xylene is readily biodegradable at 68% in 10 days and at 88% in 28 days (OECD Guideline 301F) with BOD₅/COD ratio of 0.97 (IUCLID).</p>																																														
Bioaccumulative potential	Toluene has Bioconcentration Factor (BCF) in two fish species of 13 and 90, and its partition factor Log Kow of 2,65. These values suggest a low to moderate potential of bioaccumulation. n-Butyl acetate has a low																																														

	<p>potential for bioaccumulation based on estimated bioconcentration factors (BCF) of 15.3 and low partition coefficient (Log Kow 2.3). Ethanol has a Bioconcentration Factor (BCF) value of <10, and its Log Kow value is <0, indicating its potential to bioaccumulate is low. n-Butyl alcohol has a Bioconcentration Factor (BCF) value of 3, and its Log Kow value is from 0.8 to 1, indicating its potential to bioaccumulate is very low. Acetone has a Bioconcentration Factor (BCF) of 0.65 and a partition factor Log Kow of -0.24, indicating no bioaccumulation. This estimated Bioconcentration Factor (BCF) of 12.2 indicates that Isobutyl isobutyrate will not accumulate in aquatic organisms (TOXNET). The Log Kow value <0.4 and bioconcentration factor (BCF) value <1 for isopropyl alcohol show no potential to bioaccumulate (IUCLID). Bis(2-Ethylhexyl) adipate has a Bioconcentration Factor (BCF) of 27, indicating no bioaccumulation. Isobutyl alcohol has a low potential to bioaccumulate with a bioconcentration factor (BCF) of 3 (TOXNET). Xylene has Bioconcentration Factor (BCF) of 6 to 23.4 and a partition factor Log Kow of 3.1 to 3.2, depending to the isomer. These values suggest a low potential of bioaccumulation (TOXNET).</p>
Mobility in soil	<p>Toluene will rapidly evaporate into the atmosphere because of its low soil absorption and its low solubility in water. Its Koc values range from 37 to 178 in a sandy soil suggest that toluene is expected to have high to moderate mobility in soil (TOXNET Data). n-Butyl acetate will be distributed to air (93.4%), water (5.78%), soil (0.792%), and sediment (<0.1%). The Koc value of n-butyl acetate can be estimated to be 19, suggesting that it is expected to have very high mobility in soil. n-Butyl alcohol is soluble in water. The estimated Koc value of 3.2 suggests that it is expected to have very high mobility in soil. Ethanol is very soluble in water. The resultant Koc of 1 indicates that ethanol released in soil would move quickly through the soil. It will be distributed mainly in the atmosphere (57%) and water (34%). Acetone evaporates very rapidly from dry soil surfaces. It is very soluble in water and it is expected to have very high mobility in soil with no adsorption to sediment. Isobutyl isobutyrate has a relatively high vapor pressure which suggests that evaporation from dry surfaces will occur. The estimation of Koc for Isobutyl isobutyrate can be estimated to be 98. This Koc indicates high soil mobility (TOXNET). Isopropyl alcohol is soluble in water and will quickly evaporate into the air. There is no partition in the ground. Bis(2-Ethylhexyl) adipate has an estimated Koc value of 49000 which suggests that it is expected to be immobile in soil. Isobutyl alcohol should have a very high mobility in soil with an estimated Koc value of 2.9 (TOXNET) and it distributes itself into the atmosphere (32.02%), water (67.92%), soil (0.03%), and sediments (0.03%). Xylene will rapidly evaporate into the atmosphere because of its low soil absorption and its low solubility in water. Koc values range from 39-365 for the individual isomers. These values suggest that xylenes are expected to have high to moderate mobility in soil (TOXNET).</p>
Other adverse effects	<p>This chemical does not deplete the ozone layer.</p>

13. Disposal considerations

	<p>Container Important! Prevent waste generation. Use in full. DO NOT dispose of residue in sewers, streams or drinking water supply. DO NOT puncture or burn even after use. Paint residues, including lacquers, stains, shellac, varnish, solvents and paint thinners, can be reprocessed (recycle) anywhere there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.</p>
--	---

14. Transport information

UN Number	UN 1263
UN Proper Shipping Name	PAINT
Environmental hazards	This material does not contain marine pollutant.
Special precautions for user	Permit required for transportation with proper placards displayed on vehicle.
TDG - Transportation of Dangerous Goods (Canada)	

Bis(2-Ethylhexyl) adipate										
Isobutyl alcohol	78-83-1	X	X							
Xylene	1330-20-7	X	X	X		X	X		X	
Ethylbenzene	100-41-4	X	X	X		X	X		X	X

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act - Hazardous Organic National Emission Standard for Hazardous Air Pollutant
- CAA 112(b) HAP: Clean Air Act - Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act - Regulated Chemicals for Accidental Release Prevention
- CWA 311: Clean Water Act - List of Hazardous Substances
- CWA Priority: Clean Water Act - Priority Pollutant list

California Proposition 65

Common name	CAS	Cancer	Reproductive and Developmental Toxicity
Toluene	108-88-3		X
Ethyl Alcohol	64-17-5	X	X
Ethylbenzene	100-41-4	X	

Other regulations

WHMIS 1988



B2 D2A D2B

Class B2 : Flammable Liquid

Class D2A : Very toxic material causing other toxic effects

Class D2B : Toxic material causing other toxic effects

HMIS



② Health

③ Flammability

① Reactivity

① Protective Equipment

NFPA



16. Other information

Date (YYYY-MM-DD)	GEMINI INDUSTRIES, INC. 2016-04-14
-------------------	------------------------------------

Version	01
---------	----

Other information	<p>- This SDS and the GHS hazards classification is a French translation of the original English version (SDS) from the manufacturer.</p> <p>REFERENCES:</p> <ul style="list-style-type: none"> - Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, http://hazmap.nlm.nih.gov/index.php - TOXNET Databases, Toxicology Data Network, NIH U.S. National Library of Medicine, http://toxnet.nlm.nih.gov/ - Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), http://www.reptox.csst.qc.ca - NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, http://www.cdc.gov/niosh/npg/npg.html - IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for
-------------------	---

Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), <http://www.inchem.org>

- OECD Existing Chemicals Database, Chemicals Screening Information DataSet (SIDS) for High Volume Chemicals, UNEP publications, <http://webnet.oecd.org/HPV/UI/Search.aspx>

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

HMIS: Hazardous Materials Identification System

NFPA: National Fire Protection Association

OSHA: Occupational Safety and Health Administration (USA)

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

RSST: Règlement sur la santé et la sécurité du travail (Québec)

GHS: Globally Harmonized System

IARC: International Agency for Research on Cancer

IDLH: Immediately Dangerous to Life or Health

STEL: Short Term Exposure Limit (15 min)

TWA: Time Weighted Averages

WHMIS: Workplace Hazardous Materials Information System

To the best of our knowledge, the information contained herein is accurate. However, neither Préventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.