

# Safety Data Sheet HAPS FREE INDUSTRIAL RETARDER



1. Identification		
Product identifier	HAPS FREE INDUSTRIAL RETARDER	
Product code	SOL-9012	
Other means of identification	N.Av.	
Recommended use of the chemical and restrictions on use	Paint thinner.	
Manufacturer	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 USA  Tel. 1-800-262-5710 Fax 1-405-262-9310 www.gemini-coatings.com	
Emergency phone number	INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English) 24-hour HAZMAT Response and MSDS help: EMI 800-510-8510	

## 2. Hazard identification

### Summary

WARNING! COMBUSTIBLE LIQUID! May cause slight irritation to skin and eyes. Harmful by inhalation and if swallowed. Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet. Keep containers tightly closed when not in use. After use, wash hands with soap and water. Wash contaminated clothing before reuse.

#### WHMIS 2015/OSHA HCS 2012/GHS





Flammable liquids (Category 3) Acute toxicity, oral (Category 4)

Acute toxicity, trai (Gategory 4)

Acute toxicity, inhalation (Category 4)

Eye irritation (Category 2B)

#### **WARNING**

H226: Flammable liquid and vapour

H302 + H332: Harmful if swallowed or if inhaled

H320: Causes eye irritation

P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.

P240: Ground or bond container and receiving equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing vapours.

P264: Wash skin thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P301+330+331+P310: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or physician.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or take a shower if necessary.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical advice or attention.

P370+378: In case of fire: Use chemical foam, dry chemical or carbon dioxide to extinguish.

P403+P235+P233: Store in a well-ventilated place. Keep container tightly closed. Keep cool.

P501: Dispose of contents and container to an approved waste disposal plant.

3. Composition/information on ingredients		
Common name	CAS	Weight % content
Methyl n-amyl ketone	110-43-0	60 - 100 %

4. First-aid measures		
Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.	
Skin contact	Wash skin with warm water and mild soap. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.	
Eye contact	IMMEDIATELY flush with plenty of water. Remove contact lenses if easy to do. Flush with water for at least 15 minutes. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.	
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. If victim is conscious wash out mouth with water and give 1-2 glasses of water to drink. Never give anything by mouth if victim is unconscious or convulsing. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.	
Other	No information available.	
Symptoms	No information available.	
Notes to the physician	Treat symptomatically.	

5. Fire-fighting measures			
Suitable extinguishing media	Powder carbon dioxide (CO2), alcohol resistant foam, Do not use a heavy water jet.		
Specific hazards arising from the chemical	NFPA: Class II Combustible liquid. Vapours are heavier than air and may travel to an ignition source distant from the material handling point. May be ignited by heat, sparks, flame or static electricity. Do not apply to hot surfaces. Contact with strong oxidizers may cause fire. In a fire or if heated, a pressure increase will occur and the container may burst. Emits toxic fumes under fire conditions.		
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.		
Special protective actions for fire-fighters	Water stream can scatter and spread fire. If water is used, fog nozzles are preferable. Use water spray to cool fire-exposed containers.		

6. Accidental release measures		
Personal precautions, protective equipment and emergency procedures	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.	
Environmental precautions	Prevent entry in sewer and other enclosed area. For a large spill, consult the Department of Environment or the relevant authorities.	
Methods and materials for containment and cleaning up	Remove sources of ignition. Ventilate the area well. Stay against the wind spill. Make sure you have a fire extinguisher near you. Stop leak, if it's possible to do so without risk. Use non-sparking and antistatic tools. Absorb with inert material (soil, sand, vermiculite) or wipe up or scrape up and place in an appropriate waste disposal container clearly identified. Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water.	

7. Handling and storage		
Precautions for safe handling	Keep away from heat, sparks and open flame. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Use non-sparking and antistatic tools. Ground/bond all containers when transfering large quantities (5 gallons US or 20 L and more). Use only in well ventilated area. Avoid prolonged or repeated breathing of vapour or mists. Avoid contact with skin, eyes and clothing. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet. Keep containers tightly closed when not in use. Containers of this material may be hazardous even when empty. Since empty containers retain product residues (vapour, liquid), all hazard precautions given in this sheet must be observed. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse.	
Conditions for safe storage, including any incompatibilities	Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). NFPA: Class II Combustible liquid. Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10).	
Storage temperature	10 to 25°C (50 to 77°F)	

Immediately Dangerous to Life or Health	Methyl n-amyl ketone: 80	00 ppm.		
Methyl n-amyl ketone	TWA (8h)	25 ppm 50 ppm 50 ppm	115 mg/m <sup>3</sup> 233 mg/m <sup>3</sup>	ON ACGIH , BC AB , RSST
engineering controls  Individual protection r	limits.	rs, mists, aerosols or	dust below their respectiv	e occupational exposure
Eye	Wear safety glasses. If the	here is a risk of conta	ct with eyes, wear chemic	cal splash goggles.
Hands	In case of prolonged contact wear neoprene or nitrile gloves. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly.			
	clean hands. Wash glove		emoving them. After using	g gloves, hands should be

	repeated or prolonged contact with skin.
Respiratory	Where the conditions in the workplace require a respirator, it is necessary to follow a respiratory protection program. Moreover, respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and standard 29 CFR 1910.134 (OSHA), ANSI Z88.2 or CSA Z 94.11 (Canada) and approved by NIOSH/MSHA. In case of insufficient ventilation or in enclosed area until maximum 10 times of exposure limit, wear half mask respirator with organic vapors cartridges and fitted with a particulate filter. Use a dust particle mask when sanding.
Feet	Wear rubber boots to clean up a spill.

9. Physical and chemical properties			
Physical state	Liquid	Flammability	Combustible
Colour	Clear	Flammability limits	1.1 to 7.9%
Odour	Solvent odor	Flash point	39°C (102.2°F)
Odour threshold	N/Av.	Auto-ignition temperature	N/Av.
рН	N/Ap.	Sensibility to electrostatic charges	Yes
Melting point	N/Av.	Sensibility to sparks and/or friction	N.Av.
Freezing point	N/Av.	Vapour density	>1 (Air = 1)
Boiling point	151.1°C (304°F)	Relative density	0.817 kg/L (Water = 1)
Solubility	No	Partition coefficient n-octanol/water	N/Av.
Evaporation rate	> Butyl Acetate	Decomposition temperature	N/Av.
Vapour pressure	N/Av.	Viscosity	N/Av.
Percent Volatile	100%	Molecular mass	N/Ap.
N/Av.	: Not Available N/Ap.: Not Applicable	Und.: Undetermined	N/E: Not Established

10. Stability and reactivity	
Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions (including polymerizations)	A dangerous reaction will not occur.
Conditions to avoid	Avoid heat, flame and sparks. Avoid contact with incompatible materials.
Incompatible materials	Strong oxidants, strong bases, mineral acids, strong acids.
Hazardous decomposition products	In combustion: nitrogen oxides, carbon oxides (CO, CO2).

11. Toxicolo	ogical informati	ion	
Numerical measures of toxicity	Methyl n-amyl ketone	Ingestion 1670 mg/kg Rat LD50 Inhalation <18.7 mg/l/4h Rat LC50	
Likely routes of exposure	Skin, eyes, inhalation	, ingestion.	
Delayed, immediate and chronic effects	Skin contact	May cause slight irritation to eyes.  May cause slight irritation of the skin. Prolonged and repeated contact may cause drying and cracking of the skin. Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed.	
		Excessive inhalation is harmful. May cause slight upper respiratory tract irritation. High concentrations may cause central nervous system depression characterized by headache, dizziness, nausea, fatigue, drowsiness, unconsciousness. The severity of symptoms may vary depending on exposure conditions. Prolonged and repeated exposure may cause damage to liver, kidneys, lungs and blood forming organs.	
		May cause gastrointestinal irritation with nausea and vomiting. Contains a substance that can cause target organ damage, according to data obtained on animals.	
	IARC/NTP Classification	No ingredients listed.	
		Not listed as a carcinogen by IARC, ACGIH, NIOSH, NTP or OSHA.	
		This material is not known to cause teratogenic effect.	
	Mutagenicity	This material is not known to cause mutagenic effect.	
	Reproductive toxicity	This material is not known to cause effects on reproduction.	
	I -	No information available.	
Interactive effects	No information available for this product.		
Other information	estimate (ATE) by inh mg/L/4h. This value is toxicity estimate (ATE mg/kg. This value is of estimate (ATE) of the	I nervous system, kidneys, liver, lungs. blood forming organs. The acute toxicity alation of the mixture was calculated to be greater than 10 mg/L/4h but lower than 20 is classified according to GHS: Acute toxicity, inhalation (Category 4). The oral acute is of the mixture was calculated to be greater than 300 mg/Kg but lower than 2000 classified according to GHS: Acute toxicity, oral (Category 4). The skin acute toxicity mixture was calculated to be greater than 2000 mg/kg. This value is not classified and OSHA HCS 2012.	

12. Ecologic	12. Ecological information	
Ecological toxicity	N/Av. LC50 N/Av.	
Persistence	No information available for this product.	
Degradability	No information available for this product.	
Bioaccumulative potential	No information available for this product.	
Mobility in soil	No information available for this product.	
Other adverse effects	No information available for this product.	

# 13. Disposal considerations



Important! Prevent waste generation. Use in full. DO NOT dispose residue in sewers, streams or drinking water supply. Paint residues, including lacquers, dyes, shellacs, varnishes, paint solvents and thinners, can be reprocessed where there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.

14. Transport information	
UN Number	UN 1263
UN Proper Shipping Name	PAINT RELATED MATERIAL
Environmental hazards	This material is not listed as a marine pollutant.
Special precautions for user	No information available.
TDG - Transportation of Dangerous Goods (Canada)	
Transport hazard class(es)	Class 3
Packing group	III
IMO/IMDG - International Maritime Transport	
Classification	Regulated UN 1263. Class 3, PG III.
IATA - International Air Transport Association	
Classification	Regulated UN 1263. Class 3, PG III.
These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.	

# 15. Regulatory information

# Other regulations

UNITED STATE OF AMERICA:

- Toxic Substance Control Act (TSCA):

All ingredients are listed in the TSCA Inventory.

- EPCRA Section 313 Toxic Chemicals:

No material is listed.

- California Proposition 65:

No material is listed.

CANADA:

- Canada DSL and NDSL:

All ingredients are listed in the Domestic Substances List (DSL).

- Canadian National Pollutant Release Inventory Substances (NPRI):

No material is listed.

#### **WHMIS 1988**



Class B3 : Combustible Liquid Class D2B : Toxic material causing other toxic effects







Date (YYYY-MM-DD)	GEMINI INDUSTRIES, INC. 2014-12-10
Version	02
Other information	DATE OF FIRST VERSION OF SDS: 2014-10-16 CHANGES MADE IN THE VERSION 02: sections 5, 7 and 14. REFERENCES: - Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, http://hazmap.nlm.nih.gov/index.php - NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, http://www.cdc.gov/niosh/npg/npg.html - IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), http://www.inchem.org - Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), http://www.reptox.csst.qc.ca - IUCLID Chemical Dataset, European Chemical Substances Information System (ESIS), Joint Research Centre, http://esis.jrc.ec.europa.eu
	ACGIH: American Conference of Governmental Industrial Hygienists AIHA: American Industrial Hygiene Association HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association OSHA: Occupational Safety and Health Administration (USA) NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program RSST: Règlement sur la santé et la sécurité du travail (Québec) GHS: Globally Harmonized System IARC: International Agency for Research on Cancer IDLH: Immediately Dangerous to Life or Health STEL: Short Term Exposure Limit (15 min) TWA: Time Weighted Averages WHMIS: Workplace Hazardous Materials Information System
	To the best of our knowledge, the information contained herein is accurate. However, neither Prī¿½ventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.