



# Safety Data Sheet

## BLACK LACQUER SEALER



### 1. Identification

<b>Product identifier</b>	BLACK LACQUER SEALER		
<b>Product code</b>	U8129		
<b>Other means of identification</b>	None.		
<b>Recommended use of the chemical and restrictions on use</b>	A protective and/or decorative finish or accompanying paint product. Not recommended for: Any other use not detailed on product data sheet or label.		
<b>Manufacturer</b>	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 USA  Tel. 1-800-262-5710 Fax 1-405-262-9310 <a href="http://www.geminicoatings.com">www.geminicoatings.com</a>		
<b>Emergency phone number</b>	24-hour Emergency (Spill, Leak, Exposure or accident) INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English)  HAZMAT Response and MSDS Help: EMI 800-510-8510		

### 2. Hazard identification

<b>Summary</b>	FLAMABLE LIQUID! Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved.
----------------	--

#### WHMIS 2015/OSHA HCS 2012/GHS

Flammable liquids (Category 2)  
 Skin irritation (Category 2)  
 Serious eye damage/eye irritation (Category 1)  
 Germ cell mutagenicity (Category 1B)  
 Carcinogenicity (Category 1A)  
 Reproductive toxicity (Category 1A)  
 Specific target organ toxicity, single exposure, Narcotic effects (Category 3)  
 Specific target organ toxicity, repeated exposure (Category 1)  
 Aspiration hazard (Category 1)



**Other hazards which do not result in classification :**  
 Acute hazard to the aquatic environment (Category 2).  
 Long-term hazard to the aquatic environment (Category 2)

#### DANGER

H225: Highly Flammable liquid and vapour  
 H318: Causes serious eye damage  
 H350: May cause cancer

H340: May cause genetic defects  
H360: May damage fertility or the unborn child  
H372: Causes damage to organs through prolonged or repeated exposure by inhalation  
H304: May be fatal if swallowed and enters airways  
H315: Causes skin irritation  
H336: May cause drowsiness or dizziness  
H411: Toxic to aquatic life with long lasting effects  
P201: Obtain special instructions before use.  
P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.  
P240: Ground or bond container and receiving equipment.  
P241: Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P260: Do not breathe mist, vapours and spray.  
P264: Wash skin thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P271: Use only outdoors or in a well-ventilated area.  
P273: Avoid release to the environment.  
P280: Wear protective gloves, protective clothing and eye protection.  
P301+310+331: IF SWALLOWED: Immediately call a POISON CENTER or a physician. Do NOT induce vomiting.  
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or take a shower if necessary.  
P332+313: If skin irritation occurs: Get medical advice or attention.  
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P312: Call a POISON CENTER or doctor/physician if you feel unwell.  
P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.  
P310: Immediately call a POISON CENTER or doctor/physician.  
P308+313: IF exposed or concerned: Get medical advice/attention.  
P321: Specific treatment (see section 4 of SDS).  
P362+364: Take off contaminated clothing and wash before reuse.  
P370+378: In case of fire: Use the National Fire Protection Association Class B extinguisher for extinction.  
P391: Collect spillage.  
P403+P235+P233: Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
P405: Store locked up.  
P501: Dispose of contents and container to an approved waste disposal plant.

### 3. Composition/information on ingredients

Common name	CAS	Weight % content
Toluene	108-88-3	29 - 31 %
Acetone	67-64-1	19 - 21 %
Isobutyl acetate	110-19-0	13 - 15 %
Limestone	1317-65-3	10 - 12 %
Nitrocellulose	9004-70-0	5 - 7 %
Xylene	1330-20-7	4 - 6 %
Isopropyl alcohol	67-63-0	1.5 - 2.5 %
Bis(2-Ethylhexyl) adipate	103-23-1	1.5 - 2.5 %
Carbon black	1333-86-4	1.5 - 2.5 %
Ethylbenzene	100-41-4	0.5 - 1.5 %
Bis(hydrogenated tallow alkyl)dimethylammonium bentonite	68953-58-2	0.5 - 1.5 %

## 4. First-aid measures

<b>Inhalation</b>	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
<b>Skin contact</b>	Wash skin with warm water and mild soap for at least 15 minutes. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.
<b>Eye contact</b>	IMMEDIATELY! Flush with water for at least 15 minutes. Remove contact lenses. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.
<b>Ingestion</b>	DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If victim is conscious wash out mouth with water and give 1-2 glasses of water to drink. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.
<b>Other</b>	No information available.
<b>Symptoms</b>	May cause severe eye irritation or eye damage. May cause skin irritation. May cause an allergic reaction of the skin. May cause respiratory tract irritation. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. Aspiration hazards. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discolouration of the skin. Coughing, choking and gagging are often noted at the time of aspiration.
<b>Notes to the physician</b>	Treat symptomatically. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Class B extinguishers. Dry chemicals, alcohol resistant foam, carbon dioxide (CO <sub>2</sub> ). Do not use direct water jet.
<b>Specific hazards arising from the chemical</b>	Very flammable liquid and vapours. May be ignited by heat, sparks, flame or static electricity. Vapours are heavier than air and may travel to an ignition source distant from the material handling point. Do not apply to hot surfaces. Contact with strong oxidizers may cause fire. In a fire or if heated, a pressure increase will occur and the container may burst. Emits toxic fumes under fire conditions.
<b>Special protective equipment</b>	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
<b>Special protective actions for fire-fighters</b>	Use water spray to cool fire-exposed containers. Water spray can reduce the intensity of the flames. However, the water jets can spread the fire. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
<b>Environmental precautions</b>	Prevent entry in sewer and other enclosed area. For a large spill, consult the Department of Environment or the relevant authorities.
<b>Methods and materials for containment and cleaning up</b>	Remove sources of ignition. Ventilate the area well. Stop leak, if it's possible to do so without risk. Absorb with inert material (soil, sand, vermiculite) and place in an appropriate waste disposal clearly identified. Use non-sparking and antistatic tools. Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water. PS: Rags and others materials soaked with paint or solvent may spontaneously catch fire if improperly store or discarded. Immediately after each use place rags and paper towels in a sealed water-filled metal container to prevent spontaneous combustion.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Keep away from heat, sparks and open flame. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Use non-sparking and antistatic tools. Ground/bond all containers when transferring large quantities (5 gallons US or 20 L and more). Use only in well ventilated area. Avoid prolonged or repeated breathing of vapour or mists. Avoid contact with skin, eyes and clothing. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. Keep containers tightly closed when not in use. Containers of this material may be hazardous even when empty. Since empty containers retain product residues (vapour, liquid), all hazard precautions given in this sheet must be observed. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse. Rags, steel wool and paper towels soaked with this product may overheat and spontaneously ignite if piled in a heap. After use immediately store them in water-filled metal can with tight fitting lid.
<b>Conditions for safe storage, including any incompatibilities</b>	Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10).
<b>Storage temperature</b>	10 to 25°C (50 to 77°F)

## 8. Exposure controls/personal protection

<b>Immediately Dangerous to Life or Health</b>	Toluene: 500 ppm Acetone: 2500 ppm. Isobutyl acetate: 1300 ppm. Xylenes: 900 ppm. Isopropyl alcohol: 2000 ppm. Ethylbenzene: 800 ppm. Carbon Black: 1750 mg/m <sup>3</sup> .					
Toluene	TWA (8h)		20 ppm 50 ppm	188 mg/m <sup>3</sup>	ACGIH , BC, ON RSST (Pc)	
Acetone	STEL		500 ppm		ACGIH , BC	
			750 ppm	1782 mg/m <sup>3</sup>	ON	
			1000 ppm	2380 mg/m <sup>3</sup>	RSST	
			TWA (8h)	250 ppm		ACGIH , BC
Isobutyl acetate	TWA (8h)		500 ppm	1188 mg/m <sup>3</sup>	ON	
			500 ppm	1190 mg/m <sup>3</sup>	RSST	
			150 ppm		ACGIH , BC, ON	
			150 ppm	713 mg/m <sup>3</sup>	RSST	
Limestone	STEL	Total Dust		20 mg/m <sup>3</sup>	BC	
	TWA (8h)	Total Dust		10 mg/m <sup>3</sup>	ACGIH , BC, ON, RSST	
Xylene	STEL		150 ppm		ACGIH , BC, ON	
			150 ppm	651 mg/m <sup>3</sup>	RSST	
			TWA (8h)	100 ppm		ACGIH , BC, ON
			100 ppm	434 mg/m <sup>3</sup>	RSST	
Isopropyl alcohol	STEL		400 ppm		ACGIH , BC, ON	
			500 ppm	1230 mg/m <sup>3</sup>	RSST	
			TWA (8h)	200 ppm		ACGIH , BC, ON
			400 ppm	983 mg/m <sup>3</sup>	RSST	
Carbon black	TWA (8h)			3 mg/m <sup>3</sup>	ACGIH , BC, ON	
				3.5 mg/m <sup>3</sup>	RSST	

Ethylbenzene	STEL TWA (8h)	125 ppm 20 ppm 100 ppm	543 mg/m <sup>3</sup> 434 mg/m <sup>3</sup>	RSST ACGIH , BC, ON RSST
<b>Appropriate engineering controls</b>	Provide sufficient mechanical ventilation (general and/or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.			
<b>Individual protection measures</b>				
<b>Eye</b>	Wear chemical splash goggles.			
<b>Hands</b>	Wear Neoprene gloves. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly.			
<b>Skin</b>	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. Wear an apron or long-sleeve protective coverall suit.			
<b>Respiratory</b>	Respiratory protection is not required for normal use. Respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and CSA Standard Z 94.4 and approved by NIOSH / MSHA. In case of insufficient ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times the exposure limit, wear a half mask respirator with organic vapour cartridges fitted with P100 filters. For an APF until maximum 100 times of exposure limit, wear a full face respirator mask with organic vapour cartridges and P100 filters.			
<b>Feet</b>	Wear rubber boots to clean up a spill.			

## 9. Physical and chemical properties

<b>Physical state</b>	Liquid	<b>Flammability</b>	Flammable
<b>Colour</b>	Black	<b>Flammability limits</b>	N/Av.
<b>Odour</b>	Solvent odor	<b>Flash point</b>	-20°C (-4°F)
<b>Odour threshold</b>	N/Av.	<b>Auto-ignition temperature</b>	N/Av.
<b>pH</b>	N/Av.	<b>Sensibility to electrostatic charges</b>	Yes
<b>Melting point</b>	N/Av.	<b>Sensibility to sparks and/or friction</b>	N/Av.
<b>Freezing point</b>	N/Av.	<b>Vapour density</b>	>1 (Air = 1)
<b>Boiling point</b>	34°C (93.2°F)	<b>Relative density</b>	0.9787 kg/L (Water = 1)
<b>Solubility</b>	Partially soluble in water.	<b>Partition coefficient n-octanol/water</b>	N/Av.
<b>Evaporation rate</b>	> Butyl Acetate	<b>Decomposition temperature</b>	N/Av.
<b>Vapour pressure</b>	N/Av.	<b>Viscosity</b>	N/Av.
<b>Percent Volatile</b>	72.52%	<b>Molecular mass</b>	N/Av.

N/Av.: Not Available

N/Av.: Not Available

Und.: Undetermined

N/E: Not Established

## 10. Stability and reactivity

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under recommended storage conditions.
<b>Possibility of hazardous reactions (including polymerizations)</b>	A dangerous reaction will not occur.
<b>Conditions to avoid</b>	Avoid heat, flame and sparks. Avoid electro-static discharge. Avoid contact with incompatible materials.
<b>Incompatible materials</b>	Strong bases, mineral acids, strong oxidizing agents (such as nitric acid, perchloric acid, peroxides, chlorates and perchlorates).
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. Toxicological information

<b>Numerical measures of toxicity</b>	Toluene	Ingestion 5600 mg/kg	Rat	LD50
		Inhalation 30.2 mg/l/4h	Rat	LC50
		Skin 12600 mg/kg	Rabbit	LD50
	Acetone	Ingestion 5800 mg/kg	Rat	LD50
		Inhalation 71.4 mg/l/4h	Rat	LC50
		Skin 15800 mg/kg	Rabbit	LD50
	Isobutyl acetate	Ingestion 13400 mg/kg	Rat	LD50
		Inhalation >38 mg/l/4h	Rat	LC50
		Skin >17400 mg/kg	Rabbit	LD50
	Limestone	Ingestion 6450 mg/kg	Rat	LD50
	Nitrocellulose	Ingestion >5000 mg/kg	Rat	LD50
	Xylene	Ingestion 3523 mg/kg	Rat	LD50
		Inhalation 27.6 mg/l/4h	Rat	LC50
		Skin 3200 mg/kg	Rabbit	LD50
	Bis(2-Ethylhexyl) adipate	Ingestion 9100 mg/kg	Rat	LD50
		Inhalation >5.7 mg/l/4h	Rat	LC50
		Skin 17297 mg/kg	Rabbit	LD50
	Isopropyl alcohol	Ingestion 5045 mg/kg	Rat	LD50
		Inhalation 66.1 mg/l/4h	Rat	LC50
	Carbon black	Skin 6280 mg/kg	Rat	LD50
	Ingestion >15400 mg/kg	Rat	LD50	
	Skin >3000 mg/kg	Rabbit	LD50	
Bis(hydrogenated tallow alkyl)dimethylammonium bentonite	Ingestion >5000 mg/kg	Rat	LD50	
	Inhalation >12.6 mg/l/4h	Rat	LC50	
	Skin >2000 mg/kg	Rat	LD50	
Ethylbenzene	Ingestion 3500 mg/kg	Rat	LD50	
	Inhalation 17.3 mg/l/4h	Rat	LC50	
	Skin 15380 mg/kg	Rabbit	LD50	
<b>Likely routes of exposure</b>	Skin, eyes, inhalation, ingestion.			

<b>Delayed, immediate and chronic effects</b>	<b>Eye contact</b>	May cause severe eye irritation or eye damage. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with the other ingredients of this mixture gave not irritating to irritating results.
	<b>Skin contact</b>	May cause redness and slight irritation of the skin. Prolonged and repeated contact may cause dry skin, irritation or dermatitis. Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient of this mixture gave not irritating to irritating results.
	<b>Inhalation</b>	Excessive inhalation is harmful. May cause respiratory tract irritation. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. The severity of symptoms may vary depending on exposure conditions.
	<b>Ingestion</b>	Ingestion of large amounts may cause depression of the central nervous system characterized by headache, dizziness, convulsions and loss of consciousness. Aspiration hazard for the lungs (ingestion/vomiting). Can enter lungs and cause damage. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discolouration of the skin. Coughing, choking and gagging are often noted at the time of aspiration.
	<b>Respiratory or skin sensitization</b>	Ingredients present at levels greater than or equal to 0.1% of this product are not skin or respiratory sensitizers.
	<b>IARC/NTP Classification</b>	<b>Common name IARC NTP</b> Carbon black 2B - Ethylbenzene 2B - <small>IARC : 1- Carcinogenic; 2A- Probably carcinogenic; 2B- Possibly carcinogenic. NTP : K- Known to be carcinogens; R- Reasonably anticipated to be carcinogens.</small>
	<b>Carcinogenicity</b>	Contains ingredients possibly carcinogenic to humans.
	<b>Mutagenicity</b>	Experiments showed mutagenic effects in cultured cells.
	<b>Reproductive toxicity</b>	Toluene cross the placental barrier in humans and it is found in breast milk in animals. An epidemiological study (1992) has been done with women exposed only to toluene in a factory. The first group was exposed to ambient concentrations from 50 to 150 ppm and the second at concentrations from 0 to 25 ppm. Comparison with a control group demonstrated a higher spontaneous abortions rates significantly in women exposed to higher concentrations than those of little or no exposure group. Limestone (calcium carbonate) crosses the placenta in humans and is found in breast milk. Xylene overexposure may affect fetal development in laboratory animals by inhalation during pregnancy.
	<b>Specific target organ toxicity - single exposure</b>	Central nervous system, respiratory system.
	<b>Specific target organ toxicity - repeated exposure</b>	Central nervous system, respiratory system.
<b>Interactive effects</b>	No information available for this product.	
<b>Other information</b>	The oral and skin acute toxicity estimates (ATE) of the mixture were calculated to be greater than 2000 mg/kg. The acute toxicity estimate (ATE) by inhalation of the mixture was calculated to be greater than 20 mg/L/4h. These values are not classified according to WHMIS 2015 and OSHA HCS 2012.	

## 12. Ecological information

<b>Ecological toxicity</b>	Fish - Oncorhynchus mykiss - Rainbow trout	LC50 4.74-6.33 mg/L; 96 h (acetone)
	Aquatic Invertebrate - Daphnia magna	EC50 12600-12700 mg/L; 48 h (acetone)
	Fish - Fathead minnow, Pimephales promelas - fresh water	LC50 9640 mg/L; 96 h (Isopropyl alcohol)
	Aquatic Invertebrate - Crustaceans, Daphnia Magna	EC50 3644 mg/L; 48 h (Isopropyl alcohol)
	Plant - Lettuce seed germination, Lactuca Sativa	EC50 2100 mg/L; 72 h (Isopropyl alcohol)
	Fish - Pimephales promelas [flow-through]	LC50 18 mg/L; 96h (Butyl acetate)
	Aquatic Plant - Algae, Desmodesmus subspicatus	EC50 675 mg/L; 72h (Butyl acetate)

	<p>Algae, Pseudokirchneriella subcapitata EC50 579 mg/L; 96h (Nitrocellulose)</p> <p>Fish - Oncorhynchus mykiss - Rainbow trout LC50 13.5-17.3 mg/L; 96 h (Xylene)</p> <p>Aquatic Invertebrate - Daphnia magna EC50 3.82 mg/L; 48 h (Xylene)</p> <p>Fish - Oncorhynchus mykiss - Rainbow trout LC50 5.8 mg/L; 96 h (Toluene)</p> <p>Aquatic Invertebrate - Daphnia magna EC50 5.46-9.83 mg/L; 48 h (Toluene)</p> <p>Fish - Oncorhynchus mykiss - Rainbow trout LC50 4.2 mg/L; 96 h (Ethylbenzene)</p> <p>Aquatic invertebrate - Crangon franciscorum EC50 0.49 mg/L; 48 h (Ethylbenzene)</p>
<b>Persistence</b>	Inorganic compounds persist in the environment indefinitely or incorporate into biological systems.
<b>Degradability</b>	<p>Toluene in air is rapidly decomposed by photochemical processes, mainly through oxidation by hydroxyl free radicals as well as some decomposition by direct photolysis. The half-life time in air is estimated to be from 1 to 2 days. Toluene is Biodegradable (100% in 10 days, OECD 301C). Its Biochemical Oxygen Demand (BOD) is 2150 mg O<sub>2</sub>/L (IUCLID) and its Chemical Oxygen Demand (COD) is 2520 mg O<sub>2</sub>/g (IUCLID). Acetone undergoes slow photolysis in air (half-life time T<sub>1/2</sub> = 80 h) and in water (T<sub>1/2</sub> &gt;43 h). Isobutyl acetate is expected to biodegrade in soil and water environments based on 5- and 20- day theoretical biochemical oxygen demands of 60% and 81%, respectively, in fresh water dilution tests (TOXNET). Degradation of Nitrocellulose involves complex dissociation into a wide variety of products. Since it is not soluble in water, the biodegradation by a sludge-soil mixture will be done over a long period of time (TOXNET). Xylene in air is rapidly decomposed by photochemical processes, mainly through oxidation by hydroxyl free radicals as well as some decomposition by direct photolysis. The half-life time in air is estimated to be from 9.5 to 19.7 hours depending to the isomer. Xylene is readily biodegradable at 68% in 10 days and at 88% in 28 days (OECD Guideline 301F) with BOD<sub>5</sub>/COD ratio of 0.97 (IUCLID). Isopropyl alcohol is biodegradable, 49% in 5 days and 70% in 20 days (TOXNET). It does not undergo photolysis. Its atmospheric degradation (OH radical attack) in air has a half-time T<sub>1/2</sub> of 18 to 25 hours. Ethylbenzene is biodegraded fairly rapidly by sewage or activated sludge (TOXNET). Bis(2-Ethylhexyl) adipate is readily biodegradable &gt;90% in 28 days (OECD Guideline 301F).</p>
<b>Bioaccumulative potential</b>	<p>Toluene has Bioconcentration Factor (BCF) in two fish species of 13 and 90, and its partition factor Log Kow of 2.65. These values suggest a low to moderate potential of bioaccumulation. Acetone has a Bioconcentration Factor (BCF) of 0.65 and a partition factor Log Kow of -0.24, indicating no bioaccumulation. Isobutyl acetate is not expected to bioaccumulate based on a bioconcentration factor (BCF) of 7 and a partition coefficient Log Kow of 1.78 (TOXNET). Xylene has Bioconcentration Factor (BCF) of 6 to 23.4 and a partition factor Log Kow of 3.1 to 3.2, depending to the isomer. These values suggest a low potential of bioaccumulation (TOXNET). The Log Kow value &lt;0.4 and bioconcentration factor (BCF) value &lt;1 for isopropyl alcohol show no potential to bioaccumulate (IUCLID). Bis(2-Ethylhexyl) adipate has a Bioconcentration Factor (BCF) of 27, indicating no bioaccumulation. Ethylbenzene has a low potential for bioaccumulation (BCF) of 1.1 to 15 were measured in four species of fish. It has low water solubility and a moderate partition coefficient (Log Kow of 3.15).</p>
<b>Mobility in soil</b>	<p>Toluene will rapidly evaporate into the atmosphere because of its low soil absorption and its low solubility in water. Its Koc values range from 37 to 178 in a sandy soil suggest that toluene is expected to have high to moderate mobility in soil (TOXNET Data). Acetone evaporates very rapidly from dry soil surfaces. It is very soluble in water and it is expected to have very high mobility in soil with no adsorption to sediment. Isobutyl acetate is expected to have very high mobility in water based on an estimated Koc of 16 (TOXNET). Xylene will rapidly evaporate into the atmosphere because of its low soil absorption and its low solubility in water. Koc values range from 39-365 for the individual isomers. These values suggest that xylenes are expected to have high to moderate mobility in soil (TOXNET). Isopropyl alcohol is soluble in water and will quickly evaporate into the air. There is no partition in the ground. Bis(2-Ethylhexyl) adipate has an estimated Koc value of 49000 which suggests that it is expected to be immobile in soil. Ethylbenzene is expected to have a moderate mobility in soil with an estimated Koc value of 520 (TOXNET).</p>
<b>Other adverse effects</b>	This chemical does not deplete the ozone layer.

## 13. Disposal considerations

 <b>Container</b>	<p>Important! Prevent waste generation. Use in full. DO NOT dispose of residue in sewers, streams or drinking water supply. Paint residues, including lacquers, stains, shellac, varnish, solvents and paint thinners, can be reprocessed (recycle) anywhere there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.</p>
--	--

## 14. Transport information

<b>UN Number</b>	UN 1263
<b>UN Proper Shipping Name</b>	PAINT
<b>Environmental hazards</b>	This material does not contain marine pollutant.
<b>Special precautions for user</b>	Permit required for transportation with proper placards displayed on vehicle.
<b>TDG - Transportation of Dangerous Goods (Canada)</b>	
<b>Transport hazard class(es)</b>	 Class 3
<b>Packing group</b>	II
<b>IMO/IMDG - International Maritime Transport</b>	
<b>Classification</b>	UN 1263. PAINT. Class 3, PG II. Emergency schedules (EmS-No) F-E, S-E
<b>IATA - International Air Transport Association</b>	
<b>Classification</b>	UN 1263. PAINT. Class 3, PG II.
<p>These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.</p>	

## 15. Regulatory information

### CANADA

Common name	CAS	CEPA	DSL	NDSL	NPRI
Toluene	108-88-3	X	X		X
Acetone	67-64-1		X		
Isobutyl acetate	110-19-0		X		
Limestone	1317-65-3			X	
Nitrocellulose	9004-70-0		X		
Xylene	1330-20-7	X	X		X
Isopropyl alcohol	67-63-0	X	X		X
Bis(2-Ethylhexyl) adipate	103-23-1		X		X
Carbon black	1333-86-4		X		
Ethylbenzene	100-41-4	X	X		X
Bis(hydrogenated tallow alkyl)dimethylammonium bentonite	68953-58-2		X		

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act
- DSL: Domestic Substances List Inventory
- NDSL: Non-Domestic Substances List Inventory
- NPRI: National Pollutant Release Inventory Substances

**UNITED STATE OF AMERICA**

Common name	CAS	TSCA	CERCLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Priority
Toluene	108-88-3	X	X	X		X	X		X	X
Acetone	67-64-1	X	X			X				
Isobutyl acetate	110-19-0	X	X							
Limestone	1317-65-3	X								
Nitrocellulose	9004-70-0	X								
Xylene	1330-20-7	X	X	X		X	X		X	
Isopropyl alcohol	67-63-0	X		X					X	
Bis(2-Ethylhexyl) adipate	103-23-1	X								
Carbon black	1333-86-4	X								
Ethylbenzene	100-41-4	X	X	X		X	X		X	X
Bis(hydrogenated tallow alkyl)dimethylammonium bentonite	68953-58-2	X								

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act - Hazardous Organic National Emission Standard for Hazardous Air Pollutant
- CAA 112(b) HAP: Clean Air Act - Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act - Regulated Chemicals for Accidental Release Prevention
- CWA 311: Clean Water Act - List of Hazardous Substances
- CWA Priority: Clean Water Act - Priority Pollutant list

**California Proposition 65**

Common name	CAS	Cancer	Reproductive and Developmental Toxicity
Toluene	108-88-3		X
Carbon black	1333-86-4	X	
Ethylbenzene	100-41-4	X	

**Other regulations**

**WHMIS 1988**



B2 D2A D2B

Class B2 : Flammable Liquid

Class D2A : Very toxic material causing other toxic effects

Class D2B : Toxic material causing other toxic effects

**HMIS**



**NFPA**



## 16. Other information

<b>Date (YYYY-MM-DD)</b>	GEMINI INDUSTRIES, INC. 2016-02-26
<b>Version</b>	01
<b>Other information</b>	<p>- This SDS and the GHS hazards classification is a French translation of the original English version (SDS) from the manufacturer.</p> <p>REFERENCES:</p> <ul style="list-style-type: none"><li>- Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, <a href="http://hazmap.nlm.nih.gov/index.php">http://hazmap.nlm.nih.gov/index.php</a></li><li>- TOXNET Databases, Toxicology Data Network, NIH U.S. National Library of Medicine, <a href="http://toxnet.nlm.nih.gov/">http://toxnet.nlm.nih.gov/</a></li><li>- Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), <a href="http://www.reptox.csst.qc.ca">http://www.reptox.csst.qc.ca</a></li><li>- NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, <a href="http://www.cdc.gov/niosh/npg/npg.html">http://www.cdc.gov/niosh/npg/npg.html</a></li><li>- IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), <a href="http://www.inchem.org">http://www.inchem.org</a></li><li>- OECD Existing Chemicals Database, Chemicals Screening Information DataSet (SIDS) for High Volume Chemicals, UNEP publications, <a href="http://webnet.oecd.org/HPV/UI/Search.aspx">http://webnet.oecd.org/HPV/UI/Search.aspx</a></li></ul> <p>ACGIH: American Conference of Governmental Industrial Hygienists AIHA: American Industrial Hygiene Association HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association OSHA: Occupational Safety and Health Administration (USA) NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program RSST: Règlement sur la santé et la sécurité du travail (Québec) GHS: Globally Harmonized System IARC: International Agency for Research on Cancer IDLH: Immediately Dangerous to Life or Health STEL: Short Term Exposure Limit (15 min) TWA: Time Weighted Averages WHMIS: Workplace Hazardous Materials Information System</p> <p>To the best of our knowledge, the information contained herein is accurate. However, neither Préventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.</p>