



Safety Data Sheet

CLEAR WATERBORNE SEALER



1. Identification

Product identifier	CLEAR WATERBORNE SEALER		
Product code	WBS-0100		
Other means of identification	None.		
Recommended use of the chemical and restrictions on use	A protective and/or decorative finish or accompanying paint product. Not recommended for any other use not detailed on product data sheet or label.		
Manufacturer	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 USA Tel. 1-800-262-5710 Fax 1-405-262-9310 www.geminicoatings.com		
Emergency phone number	INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English) 24-hour HAZMAT Response and MSDS help: EMI 800-510-8510		

2. Hazard identification

Summary	Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved.
----------------	---

WHMIS 2015/OSHA HCS 2012/GHS

	<p>Acute toxicity, oral (Category 4) Acute toxicity, dermal (Category 4) Acute toxicity, inhalation (Category 4) Eye irritation (Category 2) Eye irritation (Category 2A) Skin sensitizer (Category 1) Reproductive toxicity (Category 1B)</p> <p>Other hazards which do not result in classification : Acute hazard to the aquatic environment (Category 1). Long-term hazard to the aquatic environment (Category 1).</p>
--	--

DANGER

- H360: May damage fertility or the unborn child
- H302 + H312 + H332: Harmful if swallowed, in contact with skin or if inhaled
- H319: Causes serious eye irritation
- H315: Causes skin irritation
- H317: May cause an allergic skin reaction
- H410: Very toxic to aquatic life with long lasting effects
- P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.
P261: Avoid breathing vapours, mist and spray.
P264: Wash skin thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.
P273: Avoid release to the environment.
P280: Wear protective gloves, protective clothing and eye protection.
P301+312+P330: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.
P302+352: IF ON SKIN: Wash with soap and water.
P333+313: If skin irritation or a rash occurs: Get medical advice/attention.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337+313: If eye irritation persists: Get medical advice or attention.
P321: Specific treatment (see section 4 of SDS or on this label).
P362+364: Take off contaminated clothing and wash before reuse.
P391: Collect spillage.
P403+233: Store in a well ventilated place. Keep container tightly closed.
P501: Dispose of contents and container to an approved waste disposal plant.

3. Composition/information on ingredients

Common name	CAS	Weight % content
2-Butoxyethanol	111-76-2	8 - 10 %
Dibutyl phthalate	84-74-2	1 - 3 %
Diethylene glycol monobutyl ether	112-34-5	1 - 2 %

4. First-aid measures

Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
Skin contact	Wash skin with warm water and mild soap. Remove contaminated clothing and wash before reuse. If a problem develops or persists, seek medical attention.
Eye contact	IMMEDIATELY flush with plenty of water. Remove contact lenses. Flush with water for at least 15 minutes. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. If victim is conscious wash out mouth with water and give 1-2 glasses of water to drink. Never give anything by mouth if victim is unconscious or convulsing. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.
Other	No information available.
Symptoms	May cause redness and irritation of the skin and to eyes. May cause an allergic reaction of the skin.
Notes to the physician	Treat symptomatically. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire-fighting measures

Suitable extinguishing media	Dry chemicals, water spray, chemical foam, carbon dioxide (CO ₂).
Specific hazards arising from the chemical	This product is an aqueous solution which does not support combustion unless the water has been evaporated. Do not apply to hot surfaces. In a fire or if heated, a pressure increase will occur and the container may burst. Emits toxic fumes under fire conditions.
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
Special protective actions for fire-fighters	Use water spray to cool fire-exposed containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
Environmental precautions	Prevent entry in sewer and other enclosed area. For a large spill, consult the Department of Environment or the relevant authorities.
Methods and materials for containment and cleaning up	Ventilate the area well. Stop leak, if it's possible to do so without risk. Absorb with inert material (soil, sand, vermiculite) or wipe up or scrape up and place in an appropriate waste disposal container clearly identified. Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water.

7. Handling and storage

Precautions for safe handling	Use only in well ventilated area. Avoid prolonged or repeated breathing of vapour or mists. Avoid contact with skin, eyes and clothing. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. Avoid high temperatures and intense heat. Keep containers tightly closed when not in use. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse.
Conditions for safe storage, including any incompatibilities	Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep away from direct sunlight and heat. Store away from oxidizing materials and incompatible materials (see section 10). Keep from freezing.
Storage temperature	10 to 35°C (50 to 95°F)

8. Exposure controls/personal protection

Immediately Dangerous to Life or Health	2-Butoxyethanol: 700 ppm. Dibutyl phthalate: 4000 mg/m ³ .			
2-Butoxyethanol	TWA (8h)	20 ppm		ACGIH , BC, ON
		20 ppm	97 mg/m ³	AB , RSST
Diethylene glycol monobutyl ether	TWA (8h)	Inhalable Fraction	10 ppm	ACGIH
Dibutyl phthalate	TWA (8h)		5 mg/m ³	AB , AB, ACGIH, ON, RSST
Appropriate engineering controls	Provide sufficient mechanical ventilation (general and/or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure			

limits.

Individual protection measures

Eye	If there is a risk of contact with eyes, wear chemical splash goggles.
Hands	If any risk of skin contact wear nitrile or neoprene gloves. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly. Disposable nitrile gloves can also be used, but discard after single use.
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. If necessary, wear an apron or long-sleeve protective coverall suit.
Respiratory	Respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and CSA Standard Z 94.4 and approved by NIOSH / MSHA. In case of insufficient ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times of exposure limit, wear a half mask respirator with organic vapour cartridges. For an APF until maximum 100 times of exposure limit, wear a full face mask respirator with organic vapour cartridges.
Feet	Wear rubber boots to clean up a spill.

9. Physical and chemical properties

Physical state	Liquid	Flammability	Non-flammable.
Colour	Clear or coloured	Flammability limits	N/Av.
Odour	Mild acrylic odor	Flash point	>93.4°C (200.1°F) Tagliabue closed cup
Odour threshold	N/Av.	Auto-ignition temperature	N/Av.
pH	8 to 9	Sensibility to electrostatic charges	N/Av.
Melting point	N/Av.	Sensibility to sparks and/or friction	N/Av.
Freezing point	N/Av.	Vapour density	4.9 (Air = 1)
Boiling point	56.1 to 100°C (133 to 212°F)	Relative density	1.01 to 1.02 kg/L (Water = 1)
Solubility	Soluble in water.	Partition coefficient n-octanol/water	N/Av.
Evaporation rate	N/Av.	Decomposition temperature	N/Av.
Vapour pressure	0.133kPa (1 mm Hg)	Viscosity	N/Av.
Percent Volatile	62.04%	Molecular mass	N/Av.
N/Av.: Not Available N/Av.: Not Applicable Und.: Undetermined N/E: Not Established			

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.
	A dangerous reaction will not occur.

Possibility of hazardous reactions (including polymerizations)	
Conditions to avoid	Avoid contact with incompatible materials. Avoid high temperatures and intense heat.
Incompatible materials	Strong oxidants, strong bases, strong acids.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information


Numerical measures of toxicity	<p>2-Butoxyethanol</p> <p>Ingestion 560 mg/kg Rat LD50 Inhalation 2.21 mg/l/4h Rat LC50 Skin 220 mg/kg Rabbit LD50</p> <p>Diethylene glycol monobutyl ether</p> <p>Ingestion 5660 mg/kg Rat LD50 Skin 2700 mg/kg Rabbit LD50</p> <p>Dibutyl phthalate</p> <p>Ingestion 3474 mg/kg Mouse LD50 Inhalation >15.68 mg/l/4h Rat LC50 Skin >25000 mg/kg Rabbit LD50</p>
Likely routes of exposure	Skin, eyes, inhalation, ingestion.
Delayed, immediate and chronic effects	<p>Eye contact May cause eye irritation. Diethylene glycol monobutyl ether (CAS no 112-34-5) is an eye irritant (rabbits, OECD 405). 2-Butoxyethanol can cause eye irritation (rabbits, OECD 405).</p> <p>Skin contact May cause skin irritation. Prolonged and repeated contact may cause drying and cracking of the skin. Diethylene glycol monobutyl ether (CAS no 112-34-5) can cause a mild skin irritation (rabbits, OECD 404). 2-Butoxyethanol can cause skin irritation (rabbits, OECD 404). Harmful if absorbed through skin. Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed.</p> <p>Inhalation Harmful if inhaled. May cause respiratory tract irritation. High concentrations may cause central nervous system depression characterized by headache, dizziness, vertigo, nausea, drowsiness and fatigue. The severity of symptoms may vary depending on exposure conditions.</p> <p>Ingestion Harmful if swallowed. Swallowing will causes digestive tract disturbances resulting in nausea, vomiting, cramps and diarrhea.</p> <p>Respiratory or skin sensitization A few cases of sensitization after exposure to Dibutyl phthalate have been reported in humans. May cause an allergic reaction of the skin.</p> <p>IARC/NTP Classification No ingredients listed.</p> <p>Carcinogenicity Ingredients present at levels greater than or equal to 0.1% of this product are not listed as a carcinogen by IARC, ACGIH, NIOSH, NTP or OSHA.</p> <p>Teratogenicity According to studies conducted on animals, dibutyl phthalate may cause birth defects.</p> <p>Mutagenicity Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause mutagenic effects.</p> <p>Reproductive toxicity Dibutyl phthalate has embryotoxic and fetotoxic effects in animals. It can cause testicular damage in animals. The tests show that this substance possibly causes toxicity to human reproduction or development. 2-butoxyethanol may have negative effects on reproduction and fertility at doses which were severely toxic to the animals (TOXNET).</p> <p>Specific target organ toxicity - single exposure No target organ is listed.</p> <p>Specific target organ toxicity - repeated exposure No target organ is listed.</p>

Interactive effects	No information available for this product.
Other information	The oral acute toxicity estimate (ATE) of the mixture was calculated to be greater than 300 mg/Kg but lower than 2000 mg/kg. This value is classified according to GHS: Acute toxicity, oral (Category 4). The skin acute toxicity estimates (ATE) of the mixture was calculated to be greater than 1000 mg/kg but lower than 2000 mg/Kg. This value is classified according to GHS: Acute toxicity, dermal (Category 4). The acute toxicity estimate (ATE) by inhalation (mists/aerosols) of the mixture was calculated to be greater than 1 mg/L/4h but lower than 5 mg/L/4h. This value is classified according to GHS: Acute toxicity, inhalation (Category 4).

12. Ecological information

Ecological toxicity	<p>Aquatic Invertebrate - <i>Gymnodinium breve</i> (alga) EC50 0.2 mg/L ; 96 h (Dibutyl phthalate)</p> <p>Fish - <i>Oncorhynchus mykiss</i> - Rainbow trout LC50 0.1 mg/L ; 96 h (Dibutyl phthalate)</p> <p>Fish - <i>Oncorhynchus mykiss</i> - Rainbow trout LC50 1474 mg/L; 96 h (2-butoxyethanol)</p> <p>Aquatic invertebrates - <i>Daphnia magna</i> EC50 1550 mg/L; 48 h (2-butoxyethanol)</p> <p>Algae, <i>Pseudokirchneriella subcapitata</i> EC50 1840 mg/L; 72 h (2-butoxyethanol)</p> <p>Fish - <i>Lepomis macrochirus</i> - Bluegill LC50 1300 mg/L; 96 h (CAS no 112-34-5)</p>
Persistence	Persistent in the environment.
Degradability	Dibutyl phthalate is readily biodegradable at 99% in 28 days (OECD 301B). 2-Butoxyethanol is readily biodegradable 90.4% in 28 days (OECD Guideline 301B). Diethylene glycol monobutyl ether is readily biodegradable at 88% in 28 days (OECD 301D).
Bioaccumulative potential	Dibutyl phthalate has potential to bioaccumulate in aquatic organisms (log Koc >3.8). 2-Butoxyethanol is not expected to bioaccumulate based on a low partition coefficient (Log Kow <2). Diethylene glycol monobutyl ether has low potential to bioaccumulate in aquatic organisms with an estimated bioconcentration factor (BCF) of 3.
Mobility in soil	The Koc value of 3.05-3.14 for dibutyl phthalate suggests that it has a low mobility in soil. The estimated Koc value of 0.83 suggests that 2-Butoxyethanol is expected to have high mobility in soil (TOXNET). The estimated log Koc of 0.56 suggests that diethylene glycol monobutyl ether is expected to have high mobility in soil (TOXNET).
Other adverse effects	This chemical does not deplete the ozone layer.

13. Disposal considerations

 Container	Important! Prevent waste generation. Use in full. DO NOT dispose of residue in sewers, streams or drinking water supply. Paint residues, including lacquers, stains, shellac, varnish, solvents and paint thinners, can be reprocessed (recycle) anywhere there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.
---	---

14. Transport information

UN Number	UN 3082
UN Proper Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Environmental hazards	Contains marine pollutant.
Special precautions for user	Permit required for transportation with proper placards displayed on vehicle.

TDG - Transportation of Dangerous Goods (Canada)**Transport hazard class(es)**

Class 9

Packing group

III

IMO/IMDG - International Maritime Transport**Classification**

UN 3082. ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Emergency schedules (EmS-No) F-A, S-F

IATA - International Air Transport Association**Classification**

Not regulated

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.

15. Regulatory information**CANADA**

Common name	CAS	CEPA	DSL	NDSL	NPRI
2-Butoxyethanol	111-76-2	X	X		X
Dibutyl phthalate	84-74-2	X	X		X
Diethylene glycol monobutyl ether	112-34-5	X	X		X

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act
- DSL: Domestic Substances List Inventory
- NDSL: Non-Domestic Substances List Inventory
- NPRI: National Pollutant Release Inventory Substances

UNITED STATE OF AMERICA

Common name	CAS	TSCA	CERCLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Priority
2-Butoxyethanol	111-76-2	X								
Dibutyl phthalate	84-74-2	X	X	X						X
Diethylene glycol monobutyl ether	112-34-5	X								

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act - Hazardous Organic National Emission Standard for Hazardous Air Pollutant
- CAA 112(b) HAP: Clean Air Act - Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act - Regulated Chemicals for Accidental Release Prevention
- CWA 311: Clean Water Act - List of Hazardous Substances
- CWA Priority: Clean Water Act - Priority Pollutant list

California Proposition 65

Common name	CAS	Cancer	Reproductive and Developmental Toxicity
Dibutyl phthalate	84-74-2		X

Other regulations

CANADA :

- First Priority Substances List (PSL1):
Dibutyl phthalate (CAS no 84-74-2).

WHMIS 1988



D1A D2A D2B

Class D1A : Very toxic material causing immediate and serious toxic effects

Class D2A : Very toxic material causing other toxic effects

Class D2B : Toxic material causing other toxic effects

HMIS



NFPA



16. Other information

Date (YYYY-MM-DD)	GEMINI INDUSTRIES, INC. 2016-03-23
Version	01
Other information	<p>REFERENCES:</p> <ul style="list-style-type: none">- Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, http://hazmap.nlm.nih.gov/index.php- TOXNET Databases, Toxicology Data Network, NIH U.S. National Library of Medicine, http://toxnet.nlm.nih.gov/- Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), http://www.reptox.csst.qc.ca- NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, http://www.cdc.gov/niosh/npg/npg.html- IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), http://www.inchem.org <p>DATE OF FIRST VERSION OF SDS: 2014-12-15.</p> <p>CHANGES MADE IN THE VERSION 02: sections 2, 3, 8, 11, 12, 14 and 15.</p> <p>ACGIH: American Conference of Governmental Industrial Hygienists AIHA: American Industrial Hygiene Association HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association OSHA: Occupational Safety and Health Administration (USA) NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program RSST: Règlement sur la santé et la sécurité du travail (Québec) GHS: Globally Harmonized System IARC: International Agency for Research on Cancer IDLH: Immediately Dangerous to Life or Health STEL: Short Term Exposure Limit (15 min) TWA: Time Weighted Averages WHMIS: Workplace Hazardous Materials Information System</p>

To the best of our knowledge, the information contained herein is accurate. However, neither Préventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.