



Safety Data Sheet ECLIPSE WHITE PRIMER



1. Identification

Product identifier	ECLIPSE WHITE PRIMER
Product code	ECLWP-1000
Other means of identification	N.Av.
Recommended use of the chemical and restrictions on use	A protective and/or decorative finish or accompanying product. Not recommended for any other use not detailed on product data sheet or label.
Distributor	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 USA Tel. 1-800-262-5710 Fax 1-405-262-9310 http://www.gemini-coatings.com/
Emergency phone number	24-hour Emergency (Spill, Leak, Exposure or Accident) INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English) HAZMAT Response and Safety Data Sheet Help: EMI 800-510-8510

2. Hazard identification

Summary	Avoid contact with skin, eyes and clothing. Do not breathe vapors and aerosols. Do not ingest. If medical advice is needed, have this SDS or label at hand. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved.
----------------	--

WHMIS 2015/GHS/OSHA HCS 2012



Carcinogenicity (Category 2)
Specific target organ toxicity, repeated exposure (Category 1)

DANGER

H372: Causes damage to organs through prolonged or repeated exposure

H351: Suspected of causing cancer

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe vapours and dust.

P264: Wash face, hands and any exposed skin thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P280: Wear protective gloves, protective clothing and eye protection.

P308+313: IF exposed or concerned: Get medical attention.

P314: Get medical advice/attention if you feel unwell.

P405: Store locked up.

P501: Dispose of contents and container to a licensed chemical disposal agency in accordance with local, regional and national regulations.

3. Composition/information on ingredients

Common name	CAS	Weight % content
Titanium dioxide	13463-67-7	10 - 30 %
Talc	14807-96-6	3 - 7 %
Diethylene glycol monobutyl ether	112-34-5	1 - 5 %

Note: The manufacturer withholds the actual concentration range of the ingredients as a trade secret.

4. First-aid measures

Inhalation	Move person to fresh air. If a problem develops or persists, seek medical attention.
Skin contact	Wash skin with warm water and mild soap. Remove contaminated clothing and wash before reuse. If a problem develops or persists, seek medical attention.
Eye contact	IMMEDIATELY! Flush with water for at least 15 minutes. Remove contact lenses if easy to do. Hold eyelids apart to rinse properly. If a problem develops or persists, seek medical attention.
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. Never give anything by mouth if victim is unconscious or convulsing. If victim is conscious wash out mouth with plenty of water. Seek medical attention or contact a Poison Centre immediately.
Other	No additional information.
Symptoms	May cause redness and irritation to eyes. May cause redness and slight irritation of the skin. Prolonged or excessive exposure may cause headache, drowsiness, nausea, dizziness, respiratory tract irritation. Ingestion can cause abdominal pain, nausea, cramps, headache, dizziness, diarrhea and vomiting.
Notes to the physician	Treat symptomatically. If gastric lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire-fighting measures

Suitable extinguishing media	Water spray, carbon dioxide (CO ₂).
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst.
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
Special protective actions for fire-fighters	Use water spray to cool fire-exposed containers. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
Environmental precautions	Prevent entry into sewers, closed areas and release to the environment.
Methods and materials for containment and cleaning up	Ventilate the area well. Stop leak, if it's possible to do so without risk. Absorb with inert material (soil, sand, vermiculite) and place in an appropriate waste disposal clearly identified. Finish cleaning by rinsing with water contaminated surface. Dispose via a licensed waste disposal contractor.

7. Handling and storage

Precautions for safe handling	Use only in well ventilated area. Avoid contact with skin, eyes and clothing. Do not breathe vapors and aerosols. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. Keep away from heat and open flame. Keep containers tightly closed when not in use. Do not eat, do not drink and do not smoke during use. Remove contaminated clothing before entering eating areas. After use, wash hands with soap and water. Wash contaminated clothing before reuse.
Conditions for safe storage, including any incompatibilities	Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep away from direct sunlight and heat. Protect from freezing.
Storage temperature	15 to 25°C (59 to 77°F)

8. Exposure controls/personal protection

Immediately Dangerous to Life or Health	Titanium dioxide: 5000 mg/m ³ . Talc: 1000 mg/m ³ .			
Titanium dioxide	TWA (8h)	Total Dust	10 mg/m ³	ACGIH , BC, ON, RSST
Talc	TWA (8h)	Respirable Dust	2 mg/m ³	ACGIH , BC, ON
		Respirable Dust	3 mg/m ³	RSST (Pr)
Diethylene glycol monobutyl ether	TWA (8h)	Inhalable Fraction	10 ppm	ACGIH , ON
Appropriate engineering controls	Provide sufficient mechanical ventilation (general or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.			
Individual protection measures				
Eye	DO NOT wear contact lenses. Wear chemical splash goggles.			
Hands	Wear nitrile, PVC, or neoprene gloves. Disposable nitrile gloves can also be used, but discard after single use. Gloves must only be worn on clean hands.			
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. If necessary, wear an apron or long-sleeve protective coverall suit.			
Respiratory	Where the conditions in the workplace require a respirator, it is necessary to follow a respiratory protection program. Moreover, respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and standard 29 CFR 1910.134 (OSHA), ANSI Z88.2 or CSA Z 94.11 (Canada) and approved by NIOSH/MSHA. In case of insufficient			

ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times the exposure limit, wear a half mask respirator with organic vapour cartridges fitted with P100 filters. For an APF until maximum 100 times of exposure limit, wear a full face respirator mask with organic vapour cartridges and P100 filters.

Feet

Wear rubber boots to clean up a spill.

9. Physical and chemical properties

Physical state	Liquid	Flammability	Non-flammable
Colour	N.Av.	Flammability limits	N/Av.
Odour	Characteristic	Flash point	>55°C (131°F)
Odour threshold	N/Av.	Auto-ignition temperature	>250°C (482°F)
pH	8.00	Sensibility to electrostatic charges	No
Melting point	<1°C (33.8°F)	Sensibility to sparks and/or friction	No
Freezing point	<1°C (33.8°F)	Vapour density	N/Av. (Air = 1)
Boiling point	>55°C (131°F)	Relative density	1.3700 kg/L @ 20°C (68°F) (Water = 1)
Solubility	N.Av.	Partition coefficient n-octanol/water	N/Av.
Evaporation rate	N/Av.	Decomposition temperature	N/Av.
Vapour pressure	N/Av.	Viscosity	N/Av.
Percent Wt. Volatile	N/Av.	Molecular mass	N/Av.
VOC (g/L)	N/Av.	% Volume Volatile (VOC)	N/Av.
VOC (lb/gal)	N/Av.	% Wt. Volatile (VOC)	N/Av.

N/Av.: Not Available N/Av.: Not Applicable Und.: Undetermined N/E: Not Established

10. Stability and reactivity

Reactivity	No reaction expected.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions (including polymerizations)	A dangerous reaction will not occur.
Conditions to avoid	Avoid sunlight and heat. Protect from freezing.
Incompatible materials	None reported.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.


11. Toxicological information

Numerical measures of toxicity	<table border="1"> <tr> <td>Titanium dioxide</td> <td>Ingestion</td> <td>>10000 mg/kg</td> <td>Rat</td> <td>LD50</td> </tr> <tr> <td></td> <td>Inhalation</td> <td>>6.82 mg/l/4h</td> <td>Rat</td> <td>LC50</td> </tr> <tr> <td></td> <td>Skin</td> <td>>10000 mg/kg</td> <td>Rabbit</td> <td>LD50</td> </tr> <tr> <td>Talc</td> <td>Ingestion</td> <td>>5000 mg/kg</td> <td>Rat</td> <td>LD50</td> </tr> <tr> <td></td> <td>Skin</td> <td>>2000 mg/kg</td> <td>Rabbit</td> <td>LD50</td> </tr> <tr> <td>Diethylene glycol monobutyl ether</td> <td>Ingestion</td> <td>5660 mg/kg</td> <td>Rat</td> <td>LD50</td> </tr> <tr> <td></td> <td>Skin</td> <td>2700 mg/kg</td> <td>Rabbit</td> <td>LD50</td> </tr> </table>	Titanium dioxide	Ingestion	>10000 mg/kg	Rat	LD50		Inhalation	>6.82 mg/l/4h	Rat	LC50		Skin	>10000 mg/kg	Rabbit	LD50	Talc	Ingestion	>5000 mg/kg	Rat	LD50		Skin	>2000 mg/kg	Rabbit	LD50	Diethylene glycol monobutyl ether	Ingestion	5660 mg/kg	Rat	LD50		Skin	2700 mg/kg	Rabbit	LD50
Titanium dioxide	Ingestion	>10000 mg/kg	Rat	LD50																																
	Inhalation	>6.82 mg/l/4h	Rat	LC50																																
	Skin	>10000 mg/kg	Rabbit	LD50																																
Talc	Ingestion	>5000 mg/kg	Rat	LD50																																
	Skin	>2000 mg/kg	Rabbit	LD50																																
Diethylene glycol monobutyl ether	Ingestion	5660 mg/kg	Rat	LD50																																
	Skin	2700 mg/kg	Rabbit	LD50																																
Likely routes of exposure	Skin, eyes, inhalation.																																			
Delayed, immediate and chronic effects	<table border="1"> <tr> <td>Eye contact</td> <td>May cause redness and irritation to eyes. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with each ingredient of this mixture gave not irritating to irritating results.</td> </tr> <tr> <td>Skin contact</td> <td>May cause redness and slight irritation of the skin. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient of this mixture gave not irritating to slightly irritating results.</td> </tr> <tr> <td>Inhalation</td> <td>Prolonged or excessive exposure may cause headache, drowsiness, nausea, dizziness, respiratory tract irritation. Chronic effects associated with exposure to non-fibrous talc (CAS no 14807-96-6) are generally grouped under the name of talcosis. It is characterized by the presence of radiological changes with or without symptoms (cough, shortness of breath, wheezing and numbness in the fingers). The severity of symptoms may vary depending on exposure conditions.</td> </tr> <tr> <td>Ingestion</td> <td>Ingestion can cause abdominal pain, nausea, cramps, headache, dizziness, diarrhea and vomiting.</td> </tr> <tr> <td>Respiratory or skin sensitization</td> <td>Ingredients present at levels greater than or equal to 0.1% of this product are not skin or respiratory sensitizers.</td> </tr> <tr> <td>IARC/NTP Classification</td> <td>Common name IARC NTP Titanium dioxide 2B - IARC : 1- Carcinogenic; 2A- Probably carcinogenic; 2B- Possibly carcinogenic. NTP : K- Known to be carcinogens; R- Reasonably anticipated to be carcinogens.</td> </tr> <tr> <td>Carcinogenicity</td> <td>Contains an ingredient possibly carcinogenic to humans (Group 2B, IARC). If material is to be dried and sanded by users, the risk of inhalation of dust will be increased, together with the risk of cancer hazard.</td> </tr> <tr> <td>Mutagenicity</td> <td>Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause mutagenic effects.</td> </tr> <tr> <td>Reproductive toxicity</td> <td>Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause reproduction effects.</td> </tr> <tr> <td>Specific target organ toxicity - single exposure</td> <td>No target organ is listed.</td> </tr> <tr> <td>Specific target organ toxicity - repeated exposure</td> <td>No target organ is listed.</td> </tr> </table>	Eye contact	May cause redness and irritation to eyes. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with each ingredient of this mixture gave not irritating to irritating results.	Skin contact	May cause redness and slight irritation of the skin. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient of this mixture gave not irritating to slightly irritating results.	Inhalation	Prolonged or excessive exposure may cause headache, drowsiness, nausea, dizziness, respiratory tract irritation. Chronic effects associated with exposure to non-fibrous talc (CAS no 14807-96-6) are generally grouped under the name of talcosis. It is characterized by the presence of radiological changes with or without symptoms (cough, shortness of breath, wheezing and numbness in the fingers). The severity of symptoms may vary depending on exposure conditions.	Ingestion	Ingestion can cause abdominal pain, nausea, cramps, headache, dizziness, diarrhea and vomiting.	Respiratory or skin sensitization	Ingredients present at levels greater than or equal to 0.1% of this product are not skin or respiratory sensitizers.	IARC/NTP Classification	Common name IARC NTP Titanium dioxide 2B - IARC : 1- Carcinogenic; 2A- Probably carcinogenic; 2B- Possibly carcinogenic. NTP : K- Known to be carcinogens; R- Reasonably anticipated to be carcinogens.	Carcinogenicity	Contains an ingredient possibly carcinogenic to humans (Group 2B, IARC). If material is to be dried and sanded by users, the risk of inhalation of dust will be increased, together with the risk of cancer hazard.	Mutagenicity	Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause mutagenic effects.	Reproductive toxicity	Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause reproduction effects.	Specific target organ toxicity - single exposure	No target organ is listed.	Specific target organ toxicity - repeated exposure	No target organ is listed.													
Eye contact	May cause redness and irritation to eyes. Eye Irritation/Corrosion, Rabbit (OECD TG 405): tests performed with each ingredient of this mixture gave not irritating to irritating results.																																			
Skin contact	May cause redness and slight irritation of the skin. Skin Irritation/Corrosion, Rabbit (OECD 404) : tests performed with each ingredient of this mixture gave not irritating to slightly irritating results.																																			
Inhalation	Prolonged or excessive exposure may cause headache, drowsiness, nausea, dizziness, respiratory tract irritation. Chronic effects associated with exposure to non-fibrous talc (CAS no 14807-96-6) are generally grouped under the name of talcosis. It is characterized by the presence of radiological changes with or without symptoms (cough, shortness of breath, wheezing and numbness in the fingers). The severity of symptoms may vary depending on exposure conditions.																																			
Ingestion	Ingestion can cause abdominal pain, nausea, cramps, headache, dizziness, diarrhea and vomiting.																																			
Respiratory or skin sensitization	Ingredients present at levels greater than or equal to 0.1% of this product are not skin or respiratory sensitizers.																																			
IARC/NTP Classification	Common name IARC NTP Titanium dioxide 2B - IARC : 1- Carcinogenic; 2A- Probably carcinogenic; 2B- Possibly carcinogenic. NTP : K- Known to be carcinogens; R- Reasonably anticipated to be carcinogens.																																			
Carcinogenicity	Contains an ingredient possibly carcinogenic to humans (Group 2B, IARC). If material is to be dried and sanded by users, the risk of inhalation of dust will be increased, together with the risk of cancer hazard.																																			
Mutagenicity	Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause mutagenic effects.																																			
Reproductive toxicity	Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause reproduction effects.																																			
Specific target organ toxicity - single exposure	No target organ is listed.																																			
Specific target organ toxicity - repeated exposure	No target organ is listed.																																			
Interactive effects	No information available for this product.																																			
Other information	The oral and skin acute toxicity estimates (ATE) of the mixture were calculated to be greater than 2000 mg/kg. The acute toxicity estimates (ATE) by inhalation of the mixture were calculated to be greater than 20 mg/L/4h for vapours and to be greater than 5 mg/L/4h for the aerosols and mists. These values are not classified according to WHMIS 2015 and OSHA HCS 2012.																																			

12. Ecological information

Ecological toxicity	Fish - Pimephales promelas [flow-through] LC50 >500 mg/L; 96 h (CAS no 13463-67-7)
	Aquatic Invertebrates - Daphnia pulex EC50 >100 mg/L; 48 h (CAS no 13463-67-7)
	Fish - Lepomis macrochirus - Bluegill LC50 1300 mg/L; 96 h (CAS no 112-34-5)
Persistence	No information available.
Degradability	No information available.
Bioaccumulative potential	No information available.
Mobility in soil	No information available.
Other adverse effects	This chemical does not deplete the ozone layer.

13. Disposal considerations

 Container	<p>Important! Prevent waste generation. Use in full. DO NOT dispose residue in sewers, streams or drinking water supply. Paint residues, including lacquers, dyes, shellacs, varnishes, paint solvents and thinners, can be reprocessed where there is a recovery program. Empty containers can be treated (recycled) where there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.</p>
--	---

14. Transport information

UN Number	UN N/A
UN Proper Shipping Name	Not regulated by TDG (Canada) and 49 CFR DOT (USA).
Environmental hazards	This material does not contain marine pollutant.
Special precautions for user	No information available.
TDG - Transportation of Dangerous Goods (Canada & US DOT)	
Transport hazard class(es)	Not regulated
Packing group	Not regulated
IMO/IMDG - International Maritime Transport	
Classification	Not available
IATA - International Air Transport Association	
Classification	Not available
<p>These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.</p>	

15. Regulatory information

CANADA

Common name	CAS	CEPA	DSL	NDSL	NPRI
Titanium dioxide	13463-67-7		X		
Talc	14807-96-6		X		
Diethylene glycol monobutyl ether	112-34-5	X	X		X

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act
- DSL: Domestic Substances List Inventory
- NDSL: Non-Domestic Substances List Inventory
- NPRI: National Pollutant Release Inventory Substances

UNITED STATE OF AMERICA

Common name	CAS	TSCA	CER CLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Prio.
Titanium dioxide	13463-67-7	X								
Talc	14807-96-6	X								
Diethylene glycol monobutyl ether	112-34-5	X				X				

- TSCA: Toxic Substance Control Act
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act list of hazardous substances
- EPCRA 313: Emergency Planning and Community Right-to-Know Act, Section 313 Toxic Chemicals
- EPCRA 302/304: Emergency Planning and Community Right-to-Know Act, Section 302/304 Extremely Hazardous Substances
- CAA 112(b) HON: Clean Air Act - Hazardous Organic National Emission Standard for Hazardous Air Pollutant
- CAA 112(b) HAP: Clean Air Act - Hazardous Air Pollutants lists pollutants
- CAA 112(r): Clean Air Act - Regulated Chemicals for Accidental Release Prevention
- CWA 311: Clean Water Act - List of Hazardous Substances
- CWA Priority: Clean Water Act - Priority Pollutant list

California Proposition 65

Common name	CAS	Cancer	Reproductive and Developmental Toxicity
Titanium dioxide	13463-67-7	X	

Other regulations

HMIS 	NFPA 
--	--

16. Other information

Date (YYYY-MM-DD)	GEMINI INDUSTRIES, INC. 2021-04-15
Version	01
Other information	REFERENCES: - The GHS hazards classification in this SDS is from the original SDS provided by the manufacturer. - Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, https://haz-map.com/ - Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité

du travail (CNESST), <https://www.cnesst.gouv.qc.ca/fr>

- The National Center for Biotechnology Information, National Institutes of Health (NIH), U.S. National Library of Medicine, <https://pubchem.ncbi.nlm.nih.gov>

- IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), <http://www.inchem.org>

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

HMIS: Hazardous Materials Identification System

NFPA: National Fire Protection Association

OSHA: Occupational Safety and Health Administration (USA)

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

RSST: Règlement sur la santé et la sécurité du travail (Québec)

GHS: Globally Harmonized System

IARC: International Agency for Research on Cancer

IDLH: Immediately Dangerous to Life or Health

STEL: Short Term Exposure Limit (15 min)

TWA: Time Weighted Averages

WHMIS: Workplace Hazardous Materials Information System

To the best of our knowledge, the information contained herein is accurate. However, neither Preventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.