



SAFETY DATA SHEET

SECTION 1 - Chemical Product and Company Information

Product Name: CA-AUTO REFINISH WHT ZR Product Code: AR-67-CA

Manufactured by:
Gemini Coatings
 2300 Holloway Drive
 El Reno, OK 73036
 800-262-5710

24- Hour Emergency (Spill, Leak, Exposure or Accident):
INFOTRAC 800-535-5053
Outside USA, Call Collect 1-352-323-3500

24- Hour Emergency HAZMAT Response and MSDS Help:
EMI 800-510-8510

Product Use: A protective and/or decorative finish or accompanying product (reference label or product data sheet for more information).

Not recommended for: Any other use not detailed on product data sheet or label.

SECTION 2 - Hazards Identification

GHS Ratings:

Flammable liquid	3	Flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$ (140°F)
Dermal Toxicity	Acute Tox. 1	Dermal $\leq 50\text{mg/kg}$
Inhalation Toxicity	Acute Tox. 4	Gases $>2500 + \leq 5000\text{ppm}$, Vapors $>10 + \leq 20\text{mg/l}$, Dusts&mists $>1 + \leq 5\text{mg/l}$
Skin corrosive	3	Reversible adverse effects in dermal tissue, Draize score: $\geq 1.5 < 2.3$
Skin sensitizer	1	Skin sensitizer
Mutagen	1B	Known to produce heritable mutations in human germ cells Subcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1B	Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity
Reproductive toxin	1B	Presumed, Based on experimental animals

GHS Hazards

H226	Flammable liquid and vapour
H310	Fatal in contact with skin
H316	Causes mild skin irritation
H317	May cause an allergic skin reaction
H332	Harmful if inhaled
H340	May cause genetic defects
H350	May cause cancer
H360	May damage fertility or the unborn child

GHS Precautions

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/mixers/equipm ent
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P262	Do not get in eyes, on skin, or on clothing
P264	Wash any exposed skin thoroughly after handling

P270	Do not eat, drink or smoke when using this product
P271	Use only outdoors or in a well-ventilated area
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P310	Immediately call a POISON CENTER or doctor/physician
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P321	Specific treatment (see First Aid section on this label)
P322	Specific measures (see First Aid section on this label)
P361	Remove/Take off immediately all contaminated clothing
P363	Wash contaminated clothing before reuse
P302+P350	IF ON SKIN: Gently wash with soap and water
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P370+P378	In case of fire: Use the NFPA Class B extinguisher for extinction
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool
P501	Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations.

Signal Word: Danger



SECTION 3 - Composition/Information on Ingredients

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
-------------------------	----------------------	-----------------------	-----------------------

Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6 24%			
Titanium dioxide 13463-67-7 20%	15 mg/m3 TWA (total dust)	10 mg/m3 TWA	NIOSH: 2.4 mg/m3 TWA (CIB 63, fine); 0.3 mg/m3 TWA (CIB 63, ultrafine, including engineered nanoscale)
Talc 14807-96-6 16%		2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	NIOSH: 2 mg/m3 TWA (containing no Asbestos and <1% Quartz, respirable dust)
n-Butyl acetate 123-86-4 4%	150 ppm TWA; 710 mg/m3 TWA	150 ppm STEL (listed under Butyl acetates, all isomers) 50 ppm TWA (listed under Butyl acetates, all isomers)	NIOSH: 150 ppm TWA; 710 mg/m3 TWA 200 ppm STEL; 950 mg/m3 STEL
Methyl propyl ketone 107-87-9 4%	200 ppm TWA; 700 mg/m3 TWA	150 ppm STEL	NIOSH: 150 ppm TWA; 530 mg/m3 TWA
Solvent naphtha, petroleum, heavy aromatic 64742-94-5 2%			
Chlorite-group minerals 1318-59-8 1%			
MINERAL SPIRITS 8052-41-3 0.4%	500 ppm TWA; 2900 mg/m3 TWA	100 ppm TWA	NIOSH: 350 mg/m3 TWA 1800 mg/m3 Ceiling (15 min)
Naphthalene 91-20-3 0.3%	10 ppm TWA; 50 mg/m3 TWA	10 ppm TWA	NIOSH: 10 ppm TWA; 50 mg/m3 TWA 15 ppm STEL; 75 mg/m3 STEL
2-Butanone, oxime 96-29-7 0.1%			

SECTION 4 - First Aid Measures

Inhalation:

Remove exposed individual to fresh air and assist breathing if necessary. Seek medical attention.

Eye Contact:

Flush eyes with lukewarm water for 15 minutes. Seek medical attention immediately.

Skin:

Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

Ingestion:

Rinse mouth out immediately. Drink 1 or 2 glasses of water to dilute. DO NOT induce vomiting. Contact physician or poison control center immediately.

SECTION 5 - Fire Fighting Measures

Alcohol Foam, CO2, Dry Chemical

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Do not apply to hot surfaces. Never use welding or cutting torch on or near container (even empty) because product (even residue) may ignite explosively. Liquid and vapor states of this

substance are dangerous fire hazards and moderate explosion hazards when exposed to heat or flame.

Oxidation may produce carbon and nitrogen oxides.

Clear fire area of unprotected personnel. Do not enter confined space without helmet, face shield, bunker coat, gloves, rubber boots and a positive pressure NIOSH-approved self-contained breathing apparatus. A water stream can scatter flames. A spray of water may be used to cool closed containers to prevent pressure buildup and possible auto ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.

Use the National Fire Protection Association Class B extinguisher.

SECTION 6 - Accidental Release Measures

Stay upwind and away from spill or leak unless wearing appropriate protective equipment. Stop and/or contain discharge if it may be done safely. Keep all sources of ignition away. Ventilate area of spill. Use non-sparking tools for clean up. Cover with inert material to reduce fumes. Keep out of drains, sewer or waterways.

If large spill occurs, alert spill response teams. Contact fire authorities. Notify local health and pollution control agencies.

SECTION 7- Handling and Storage

Handling:

Bond and ground metal containers when transferring liquid. Avoid free fall of liquid in excess of a few inches. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this sheet must be observed.

Storage:

Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas.

SECTION 8 - Exposure Controls/Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6			
Titanium dioxide 13463-67-7	15 mg/m ³ TWA (total dust)	10 mg/m ³ TWA	NIOSH: 2.4 mg/m ³ TWA (CIB 63, fine); 0.3 mg/m ³ TWA (CIB 63, ultrafine, including engineered nanoscale)
Talc 14807-96-6		2 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	NIOSH: 2 mg/m ³ TWA (containing no Asbestos and <1% Quartz, respirable dust)
n-Butyl acetate 123-86-4	150 ppm TWA; 710 mg/m ³ TWA	150 ppm STEL (listed under Butyl acetates, all isomers) 50 ppm TWA (listed under Butyl acetates, all isomers)	NIOSH: 150 ppm TWA; 710 mg/m ³ TWA 200 ppm STEL; 950 mg/m ³ STEL
Methyl propyl ketone 107-87-9	200 ppm TWA; 700 mg/m ³ TWA	150 ppm STEL	NIOSH: 150 ppm TWA; 530 mg/m ³ TWA
Solvent naphtha, petroleum, heavy aromatic 64742-94-5			
Chlorite-group minerals 1318-59-8			

MINERAL SPIRITS 8052-41-3	500 ppm TWA; 2900 mg/m3 TWA	100 ppm TWA	NIOSH: 350 mg/m3 TWA 1800 mg/m3 Ceiling (15 min)
Naphthalene 91-20-3	10 ppm TWA; 50 mg/m3 TWA	10 ppm TWA	NIOSH: 10 ppm TWA; 50 mg/m3 TWA 15 ppm STEL; 75 mg/m3 STEL
2-Butanone, oxime 96-29-7			

Use local exhaust as required to control vapor concentrations.
Avoid prolonged or repeated breathing of vapors.

Respiratory Protection:

If exposure exceeds TLV or PELs, use NIOSH approved respirator to prevent overexposure.

Skin Protection:

Required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile. An apron should be worn to avoid skin contact.

Eye Protection:

Wear splash proof goggles and face shield if there is a likelihood of contact with eyes.

Hygienic Practices

Wash hands thoroughly before eating or using the restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

SECTION 9 - Physical and Chemical Properties

<p>Vapor Density Heavier Than Air</p> <p>Boiling range: 102 - 3000°C</p> <p>Freezing point: N/A</p> <p>Flammability: N/A</p> <p>Autoignition temperature: 425°C</p> <p>Relative Density: N/A</p> <p>Odor threshold: N/A</p> <p>SPECIFIC GRAVITY 1.4991</p> <p>Partition coefficient (n-octanol/water): N/A</p> <p>Grams VOC less water: N/A</p> <p>% WT. VOLATILE (VOC) 11.9116</p> <p>Lbs VOC/Gallon Solids 2.8529</p> <p>SOLIDS VOL% 52.1193</p> <p>SPREAD @ 1 MIL 835.9936</p> <p>Appearance Colored Liquid</p> <p>Physical State Liquid</p> <p>Coating VOC (g/l) 244.0749</p> <p>Coating VOC (Lb/Gl) 2.0368</p>	<p>Evaporation Rate Faster than Butyl Acetate</p> <p>Melting point: N/A</p> <p>Flash point: 111°F, 44°C</p> <p>Explosive Limits: N/A</p> <p>Decomposition temperature: N/A</p> <p>Vapor Pressure N/A</p> <p>pH: N/A</p> <p>Solubility: N/A</p> <p>Viscosity: N/A</p> <p>% VOLUME VOLATILE (VOC) 20.8817</p> <p>% Pig. by wt. 37.4556</p> <p>VOLATILE WT% 35.9845</p> <p>DENSITY (Lb/Gal) 12.4829</p> <p>HAPS (lbs/gl) 0.1404</p> <p>Odor N/A</p> <p>Material VOC (g/l) 178.1772</p> <p>Material VOC (Lb/Gl) 1.4869</p>
---	---

SECTION 10 - Stability and Reactivity

Stability: Stable under normal conditions.

Materials to Avoid: Strong oxidizing agents, strong alkalines, strong mineral acids.

Conditions to avoid: high heat, sparks, flames, static discharge.

Hazardous Decomposition: Oxidation may produce carbon and nitrogen oxides.
Hazardous polymerization will not occur.

SECTION 11 - Toxicological Information

Mixture Toxicity

Dermal Toxicity LD50: 11mg/kg
Inhalation Toxicity LC50: 18mg/L

Component Toxicity

98-56-6	Benzene, 1-chloro-4-(trifluoromethyl)- Oral LD50: 13 g/kg (Rat) Dermal LD50: 2 mL/kg (Rabbit) Inhalation LC50: 33 mg/L (Rat)
123-86-4	n-Butyl acetate Inhalation LC50: 390 ppm (Rat)
107-87-9	Methyl propyl ketone Oral LD50: 1,600 mg/kg (Rat) Inhalation LC50: 2,000 - (Rat)
64742-94-5	Solvent naphtha, petroleum, heavy aromatic Oral LD50: 5,000 mg/kg (Rat) Dermal LD50: 2 mL/kg (Rabbit) Inhalation LC50: 590 mg/m ³
91-20-3	Naphthalene Oral LD50: 1,110 mg/kg (Rat) Dermal LD50: 1,120 mg/kg (Rabbit) Inhalation LC50: 340
96-29-7	2-Butanone, oxime Oral LD50: 930 mg/kg (Rat) Dermal LD50: 1,000 - (Rabbit) Inhalation LC50: 5 mg/L (Rat)

Primary Routes of Entry: Inhalation, Skin Contact, Eyes, Ingestion

Skin:

Skin contact can cause redness, dryness or rash. Prolonged contact can cause irritation, dry skin, cracks, and dermatitis.

Ingestion:

Can cause vomiting, nausea, diarrhea, and gastrointestinal irritation.

Inhalation:

Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache possible unconsciousness and even asphyxiation. High vapor concentrations or prolonged breathing of lower concentrations may result in damage to the liver, kidneys, lungs and blood forming organs. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

Eyes:

Can cause irritation, redness, tearing and blurred vision.

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
13463-67-7	Titanium dioxide	20%	Titanium dioxide: NIOSH: potential occupational carcinogen IARC: Possible human carcinogen OSHA: listed
8052-41-3	MINERAL SPIRITS	0.4%	MINERAL SPIRITS: EU REACH: Present (P)
91-20-3	Naphthalene	0.3%	Naphthalene: IARC: Possible human carcinogen OSHA: listed

SECTION 12 - Ecological Information

Ecological Information:

Uncontrolled release of the product may result in contamination of air, ground, waterways and/or sewers.

Component Ecotoxicity

Benzene, 1-chloro-4-(trifluoromethyl)-	LC50 96 h Danio rerio 3 mg/L [semi-static] (ECHA) EC50 48 h Daphnia magna 3.68 mg/L (IUCLID)
Talc	LC50 96 h Brachydanio rerio >100 g/L [semi-static]
n-Butyl acetate	LC50 96 h Lepomis macrochirus 100 mg/L [static] (EPA); LC50 96 h Pimephales promelas 17 - 19 mg/L [flow-through] (EPA) EC50 72 h Desmodesmus subspicatus 674.7 mg/L (IUCLID)
Methyl propyl ketone	LC50 96 h Pimephales promelas 1190 - 1290 mg/L [flow-through] (EPA)
Solvent naphtha, petroleum, heavy aromatic	LC50 96 h Pimephales promelas 19 mg/L [static] (IUCLID); LC50 96 h Oncorhynchus mykiss 2.34 mg/L (IUCLID); LC50 96 h Lepomis macrochirus 1740 mg/L [static] (IUCLID); LC50 96 h Pimephales promelas 45 mg/L [flow-through] (IUCLID); LC50 96 h Pimephales promelas 41 mg/L (IUCLID) EC50 48 h Daphnia magna 0.95 mg/L (IUCLID)
Naphthalene	LC50 96 h Pimephales promelas 5.74 - 6.44 mg/L [flow-through] (EPA); LC50 96 h Oncorhynchus mykiss 1.6 mg/L [flow-through] (EPA); LC50 96 h Oncorhynchus mykiss 0.91 - 2.82 mg/L [static] (EPA); LC50 96 h Pimephales promelas 1.99 mg/L [static] (IUCLID); LC50 96 h Lepomis macrochirus 31.0265 mg/L [static] (EPA) LC50 48 h Daphnia magna 2.16 mg/L (IUCLID); EC50 48 h Daphnia magna 1.96 mg/L [Flow through] (EPA); EC50 48 h Daphnia magna 1.09 - 3.4 mg/L [Static] (EPA)
2-Butanone, oxime	LC50 96 h Pimephales promelas 777 - 914 mg/L [flow-through] (EPA); LC50 96 h Poecilia reticulata 760 mg/L [static] (IUCLID) EC50 48 h Daphnia magna 750 mg/L (IUCLID) EC50 72 h Desmodesmus subspicatus 83 mg/L (IUCLID)

SECTION 13 - Disposal Considerations

Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations. See Section 8 for information on exposure control and necessary personal protective equipment.

SECTION 14 - Transportation Information

Ship according to the Department of Transportation (DOT) 49 CFR regulations.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	COMBUSTIBLE LIQUID NOS (CONTAINS: RULE 66 MINERAL SPIRITS) Freight Class:	NA 1993	III	COMB LIQ.

SECTION 15 - Regulatory Information

Hazardous Material Information System (HMIS)

HEALTH	<input type="checkbox"/>	3	HMIS & NFPA Hazard Rating Legend * = Chronic Health Hazard 0 = INSIGNIFICANT 1 = SLIGHT 2 = MODERATE 3 = HIGH
FLAMMABILITY	<input type="checkbox"/>	2	
PHYSICAL HAZARD	<input type="checkbox"/>	1	
PERSONAL PROTECTION	<input checked="" type="checkbox"/>	X	

SECTION 16 - Disclaimer

Date Prepared: 1/28/2022

Date revised: 2022-01-28

Reviewer Revision

THIS DOCUMENT SUPERSEDES ANY PROVISION CONTAINED IN THE FORMS, LETTERS, AND PAPERS OF YOUR COMPANY. THIS PRODUCT IS DESIGNED AND INTENDED FOR PROFESSIONAL APPLICATION ONLY. ALL PRODUCTS SHOULD BE THOROUGHLY TESTED UNDER APPLICATION CONDITIONS PRIOR TO USE. THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE RELIABLE. HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED. INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OR WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.