



# QUICKSTAIN®

## ALKYD WIPING STAIN

### 1U-1000

#### Features

- Tint Base For Custom Colors
- Ready To Use Formulation
- Uniform Penetration
- Superior Grain Definition
- Resists Fading and Bleeding
- Fast Drying For Lacquers

#### General Description

Lenmar® QuickStain® Alkyd Wiping Stains have been uniquely designed for the professional woodworker in the Flooring, Furniture & Cabinet Industry and are formulated for ease of use, and color stability. The major benefits of this stain include: a natural / clear tint base for custom tinting with industrial colorants, ease of application for uniform penetration, superior grain definition, and resistance to bleeding and fading.

#### Recommended For

Kitchen Cabinets, Wood Floors, Furniture, Window & Door Trim, Baseboards & Molding, Interior Doors & Hand Rails.

#### Limitations

- For floor applications, wait 2-3 hours before proceeding with topcoats.

#### Product Information

Product Information	
<b>Colors — Standard:</b> N/A	<b>Technical Data</b> ∆ <b>Natural/Clear Base</b>
<b>— Tint Bases:</b> 1U-1000, Natural/Clear Base  Can be tinted with Industrial Colorants	Vehicle Type Alkyd Pigment Type N/A Weight Solids 10.3% Volume Solids 8.9% Coverage per Gallon at 1 mil DFT N/A Recommended Film — Wet N/A Thickness — Dry N/A Dry Time @ 75 °F — Tack Free 15 Minutes (23.8 °C) @ 50% RH — To Recoat 30 Minutes
<b>— Special Colors:</b> Contact your Dealer/Distributor.	High humidity and cool temperatures will result in longer dry, recoat and service times. Dries By Oxidation Viscosity 18 – 22 Seconds (#2 Zahn) Flash Point 100 °F (37.8 °C) Gloss / Sheen N/A Surface Temperature — Min. 68 °F at Application — Max. 90 °F Thin With Do Not Thin Clean Up Thinner 1A-137 Mineral Spirits Weight Per Gallon 7.33 lbs
<b>Certification &amp; Qualifications:</b> <b>VOC compliant in federally regulated areas only</b>  The products supported by this data sheet contain a maximum of 750 grams per liter VOC (6.26 lbs/gal.) excluding water & exempt solvents. *Thinning this material may result in increasing the VOC levels of this product. Refer to your local regulations before thinning.	Storage Temperature — Min. 50 °F — Max. 90 °F
<b>Technical Assistance:</b> Available through your local authorized independent Lenmar dealer. For the location of the dealer nearest you, call 1-877-299-3600 or visit <a href="http://www.lenmar-coatings.com">www.lenmar-coatings.com</a>	<b>Volatile Organic Compounds (VOC)</b>  736 Grams/Liter 6.14 Lbs./Gallon

May, 2022

## QuickStain Alkyd Wiping Stain 1U-1000

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### Application

Over properly prepared interior wood surfaces, apply only one full coat of QuickStain® Alkyd Wiping Stain by spray, natural bristle brush or with a clean lint-free cloth. Remove all excess stain within 5 minutes after application. When dry (usually 30 minutes), continue with sealer and topcoat system in accordance with their Product Data Sheets. Check adhesion before proceeding with this type of application. See characteristics for finish options and recommended dry times. For floor applications, wait 2-3 hours before proceeding with topcoats.

### Specifications

Moisture content of wood should be no higher than 9%. Wood must be free of all surface contaminants. Using 120 – 150 grit sandpaper, sand with the grain and remove all dust. Thoroughly mix stain and intermix multiple containers of same color. Test color before proceeding. Color intensity may vary due to wood species, surface preparation, and method of application. Submerge stain soaked rags in water to avoid spontaneous combustion. Read label and SDS for additional information and warnings

### Clean up

Clean up with 1A-137 Mineral Spirits.

### Environmental Health & Safety Information

#### **DANGER!**

**Causes skin irritation**

**Suspected of causing cancer**

**May cause drowsiness or dizziness**

**Causes damage to organs through prolonged or repeated exposure**

**May be fatal if swallowed and enters airways**

**Flammable liquid and vapor**

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep cool.

**Response:** IF exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.

**Storage:** Store locked up. Store in a well-ventilated place. Keep container tightly closed.

**Disposal:** Dispose of contents/container to an approved waste disposal plant.

**DANGER -** Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.



**WARNING** Cancer and Reproductive Harm—  
[www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

**FOR PROFESSIONAL USE ONLY  
KEEP OUT OF REACH OF CHILDREN**

**THIS PRODUCT IS INTENDED FOR SHOP OR  
OEM APPLICATION ONLY.**

**FOR WOOD SUBSTRATES ONLY  
FOR INTERIOR USE ONLY**

**READ ALL DIRECTIONS BEFORE USE.  
UNDERSTAND ALL DANGERS WITH THIS  
PRODUCT PRIOR TO USE.**

**Refer to Safety Data Sheet for  
additional health and safety information.**