



AQUA-PLASTIC®

URETHANE CLEAR C1WB-14XX

Features

- Soap and water cleanup
- Crystal clear finish
- Hard, durable finish with good gloss retention

General Description

These Waterborne Acrylic Urethane Clears represent the most recent technology. When cured, these crystal-clear finishes exhibit outstanding hardness, durability, abrasion resistant and gloss retention.

Recommended For

On interior areas such as trim, furniture, doors or cabinets.

Limitations

NOTE: not recommended for use on floors.

Product Information

Colors — Standard:		Technical Data		Satin
Clear		Vehicle Type	Acrylic Polyurethane	
Gloss	C1WB-1400	Pigment Type	n/a	
		Weight Solids	31.2 ± 1.0%	
Semi-Gloss	C1WB-1410	Volume Solids	27.5 ± 1.0%	
		Coverage per Gallon	400 – 500 Sq. Ft.	
Satin	C1WB-1427	Recommended Film Thickness	– Wet	3.2 – 4 mils
Dull	C1WB-1420		– Dry	0.9 – 1.1 mils
— Tint Bases:		Coverage calculation does not include spray loss or equipment inefficiency. Also allow for wood species, surface preparation, surface defects and porosity of substrate to affect spread rates.		
N/A		Dry Time @ 75 °F (23.8 °C) @ 50% RH		
— Special Colors:		– Tack Free 1 hour		
N/A		– To Recoat 2 – 4 hours		
Certifications & Qualifications:		High humidity and cool temperatures will result in longer dry and recoat times.		
VOC compliant in all regulated areas		Dries By Evaporation, Coalescence		
The products supported by this data sheet contain a maximum of 275 grams per liter VOC / VOS (2.29 lbs. /gal.) excluding water and exempt solvents.		Viscosity 65 – 68 KU		
		Flash Point 200 °F or greater (TT-P-141, Method 4293)		
		Gloss / Sheen Gloss, Semi-Gloss, Satin, Dull		
		Surface Temperature at Application		
		– Min. 55 °F		
		– Max. 90 °F		
		Thin With Clean Water		
		Clean Up Thinner Warm soapy water.		
		Weight Per Gallon 8.7 lbs		
		Storage Temperature		
		– Min. 50 °F		
		– Max. 90 °F		
Technical Assistance:		Volatile Organic Compounds (VOC)		
Available through your local authorized independent Lenmar dealer.		247.7 Grams/Liter 2.06 Lbs./Gallon		
For the location of the dealer nearest you, call 1-877-299-3600 or visit www.lenmar-coatings.com				

Aqua-Plastic® Urethane Clears C1WB-14XX

Surface Preparation

Surface to be coated must be clean and free of dust, grease, dirt or wax. If wax is a suspect contaminate, remove with a commercial wax stripper. New interior wood must be sanded smooth. This product may not be used over sanding sealers containing silicone, wax or stearates. Use this waterborne clear as a self-seal and topcoat system allowing 2 to 4 hours dry time between coats and sanding lightly before applying.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

This varnish may be applied by brush, roller or spray. Stir thoroughly before and occasionally during application. Do not shake. Best rolling results are achieved with a ¼" short nap roller. For best brush application, use a good quality synthetic brush. When brushing or rolling, flow material on with a minimum of strokes. Thinning is not recommended, if necessary use water sparingly. Do not apply when surface or air temperatures are below 55 °F. Sand lightly with fine sandpaper between coats. Apply Aqua-Plastic in thin coats to avoid prolonged milky appearance of the film.

Clean Up

Warm soapy water.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "Clean Up"

**FOR PROFESSIONAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING
FOR WOOD SUBSTRATES ONLY
FOR INTERIOR USE ONLY**

**Refer to Safety Data Sheet for additional
health and safety information.**