



Safety Data Sheet

275 VOC PREMIUM C.V., SEMI-GLOSS, CLEAR



1. Identification

Product identifier	275 VOC PREMIUM C.V., SEMI-GLOSS, CLEAR		
Product code	CV275-0060		
Other means of identification	None.		
Recommended use of the chemical and restrictions on use	A protective and/or decorative finish or accompanying paint product.		
Manufacturer	GEMINI INDUSTRIES, INC. 2300 Holloway Drive El Reno, OK 73036 Tel. 1-800-262-5710 Fax 1-405-262-9310 www.geminicoatings.com		
Emergency phone number	24-hour Emergency (Spill, Leak, Exposure or accident) INFOTRAC 800-535-5053 Outside USA, Call Collect 1-352-323-3500 (French & English) HAZMAT Response and MSDS Help: EMI 800-510-8510		

2. Hazard identification

Summary	Keep away from heat, sparks and open flame. Avoid contact with skin, eyes and clothing. Do not breathe vapours, mists or aerosols. Do not ingest. If ingested consult physician immediately and show this Safety Data Sheet. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved.
----------------	---

WHMIS 2015/OSHA HCS 2012/GHS

Flammable liquids (Category 3)
 Skin corrosion/irritation (Category 2)
 Serious eye damage/eye irritation (Category 1)
 Skin sensitizer (Category 1)
 Reproductive toxicity (Category 2)
 Specific target organ toxicity, single exposure (Category 3)

Other hazards which do not result in classification :
 Acute hazard to the aquatic environment (Category 2).
 Long-term hazard to the aquatic environment (Category 2)



DANGER

- H226: Flammable liquid and vapour
- H318: Causes serious eye damage
- H315: Causes skin irritation
- H317: May cause an allergic skin reaction
- H335: May cause respiratory irritation
- H336: May cause drowsiness or dizziness
- H361: Suspected of damaging fertility or the unborn child

H411: Toxic to aquatic life with long lasting effects
P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat, sparks, open flames and other ignition sources. No smoking.
P240: Ground or bond container and receiving equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P261: Avoid breathing vapours, mist and dust.
P264: Wash face, hands and any exposed skin thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.
P273: Avoid release to the environment.
P280: Wear protective gloves, protective clothing and eye protection.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water and soap or take a shower if necessary.
P333+313: If skin irritation or a rash occurs: Get medical advice/attention.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor/physician.
P308+313: IF exposed or concerned: Get medical advice/attention.
P321: Specific treatment (see section 4 of SDS or on this label).
P362+364: Take off contaminated clothing and wash before reuse.
P370+378: In case of fire: Use the National Fire Protection Association Class B extinguisher for extinction.
P391: Collect spillage.
P403+P235+P233: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P405: Store locked up.
P501: Dispose of contents and container to an approved waste disposal plant.

3. Composition/information on ingredients

Common name	CAS	Weight % content
1-Chloro-4-(trifluoromethyl)benzene	98-56-6	32 - 33 %
Urea, polymer with formaldehyde, butylated	68002-19-7	14 - 15 %
n-Butyl Alcohol	71-36-3	11 - 12 %
Methyl Propyl Ketone	107-87-9	1.5 - 2.5 %
Propylene glycol monomethyl ether acetate	108-65-6	1 - 2 %

4. First-aid measures

Inhalation	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen by trained personnel. If a problem develops or persists, seek medical attention.
Skin contact	Wash skin with warm water and mild soap for at least 15 minutes. Remove contaminated clothing and wash before reuse. Avoid touching eyes with contaminated body parts. If a problem develops or persists, seek medical attention.
Eye contact	IMMEDIATELY flush with plenty of water. Remove contact lenses. Flush with water for at least 15 minutes. Hold eyelids apart to rinse properly. Seek medical attention immediately.
Ingestion	DO NOT induce vomiting, unless recommended by medical personnel. If victim is conscious rinse mouth with water and give 1-2 glasses of water to drink. Never give anything by mouth if victim is unconscious or convulsing. If spontaneous vomiting occurs, keep head below hip level to prevent aspiration into the lungs. Seek medical attention or contact a Poison Centre immediately.
Other	No information available.

Symptoms	May cause severe eye irritation or eye damage. May cause redness and irritation of the skin. May cause an allergic reaction of the skin. May cause irritation to nose, throat and respiratory tract. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue.
Notes to the physician	Treat symptomatically. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire-fighting measures

Suitable extinguishing media	Class B extinguishers. Dry chemicals, alcohol resistant foam, carbon dioxide (CO ₂). Do not use direct water jet.
Specific hazards arising from the chemical	Flammable liquid and vapours. Vapours are heavier than air and may travel to an ignition source distant from the material handling point. May be ignited by heat, sparks, flame or static electricity. Do not apply to hot surfaces. Contact with strong oxidizers may cause fire. In a fire or if heated, a pressure increase will occur and the container may burst. Emits toxic fumes under fire conditions.
Special protective equipment	Firefighters must wear self contained breathing apparatus with full face mask. Firefighting suit may not be efficient against chemicals.
Special protective actions for fire-fighters	Use water spray to cool fire-exposed containers. Water spray can reduce the intensity of the flames. However, the water jets can spread the fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Do not touch spilled material. Make sure to wear personal protective equipment mentioned in this Safety Data Sheet.
Environmental precautions	Prevent entry in sewer and other enclosed area. For a large spill, consult the Department of Environment or the relevant authorities.
Methods and materials for containment and cleaning up	Remove sources of ignition. Ventilate the area well. Stop leak, if it's possible to do so without risk. Absorb with inert material (soil, sand, vermiculite) and place in an appropriate waste disposal clearly identified. Use non-sparkling and antistatic tools. Dispose via a licensed waste disposal contractor. Finish cleaning the contaminated surface by rinsing with soapy water. PS: Rags and others materials soaked with paint or solvent may spontaneously catch fire if improperly store or discarded. Immediately after each use place rags and paper towels in a sealed water-filled metal container to prevent spontaneous combustion.

7. Handling and storage

Precautions for safe handling	Keep away from heat, sparks and open flame. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Use non-sparkling and antistatic tools. Ground/bond all containers when transfer large quantities (5 gallons US or 20 L and more). Use only in well ventilated area. Avoid prolonged or repeated breathing of vapour or mists. Avoid contact with skin, eyes and clothing. Wear eye protection, gloves and other protective clothing that are adapted to the task being performed and the risks involved. Keep containers tightly closed when not used. Containers of this material may be hazardous when emptied. Since empty containers retain product residues (vapour, liquid), all hazard precautions given in this sheet must be observed. Do not eat, do not drink and do not smoke during use. Wash hands, forearms and face thoroughly after handling this compound and before eating, drinking or using toiletries. Remove contaminated clothing and wash before reuse. Rags, steel wool and paper towels soaked with this product may overheat and spontaneously ignite if piled in a heap. After use immediately store them in water-filled metal can with tight fitting lid.
--------------------------------------	---

Conditions for safe storage, including any incompatibilities	Storage and handling should follow the NFPA 30 Flammable and/or Combustible Liquids Code and the National Fire Code of Canada (NFCC). Store tightly closed and in properly labelled container in a dry, cool and well ventilated place. Ground/bond all containers when transfer large quantities (5 gallons US or 20 L and more). Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store away from oxidizing materials and incompatible materials (see section 10).
Storage temperature	10 to 25°C (50 to 77°F)

8. Exposure controls/personal protection

Immediately Dangerous to Life or Health	N-Butyl Alcohol: 1400 ppm. Methyl Propyl Ketone: 1500 ppm.				
n-Butyl Alcohol	Ceiling	30 ppm			BC
		50 ppm	152 mg/m ³		RSST (Pc, RP)
	TWA (8h)	15 ppm			BC
		20 ppm			ACGIH , ON
Methyl Propyl Ketone	Ceiling	150 ppm			ACGIH , ON
	STEL	250 ppm			BC
	TWA (8h)	150 ppm			BC
		150 ppm	530 mg/m ³		RSST
Propylene glycol monomethyl ether acetate	STEL	75 ppm			BC
	TWA (8h)	50 ppm			BC , US AIHA
		50 ppm	270 mg/m ³		ON
Appropriate engineering controls	Provide sufficient mechanical ventilation (general and/or local exhaust) to keep the airborne concentrations of vapours, mists, aerosols or dust below their respective occupational exposure limits.				
Individual protection measures					
Eye	Wear chemical splash goggles.				
Hands	Wear nitrile or neoprene gloves. Disposable nitrile gloves can also be used, but discard after single use. Before using, user should confirm impermeability. Discard gloves with tears, pinholes, or signs of wear. Gloves must only be worn on clean hands. Wash gloves with water before removing them. After using gloves, hands should be washed and dried thoroughly.				
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Wear normal work clothing covering arms and legs as required by employer code. Wear an apron or long-sleeve protective coverall suit.				
Respiratory	Respiratory protection is not required for normal use. Respiratory protection equipment (RPE) must be selected, fitted, maintained and inspected in accordance with regulations and CSA Standard Z 94.4 and approved by NIOSH / MSHA. In case of insufficient ventilation or in confined or enclosed space and for an assigned protection factor (APF) up to 10 times the exposure limit: wear a half mask respirator with organic vapor cartridges fitted with P100 filters. For an APF until maximum 100 times of exposure limit, wear a full face respirator mask with organic vapor cartridges and P100 filters.				
Feet	Wear rubber boots to clean up a spill.				

9. Physical and chemical properties

Physical state	Liquid	Flammability	Flammable
Colour	Clear	Flammability limits	N/Av.
Odour	Solvent	Flash point	37°C (98.6°F)

Odour threshold	N/Av.	Auto-ignition temperature	N/Av.
pH	N/Av.	Sensibility to electrostatic charges	Yes
Melting point	N/Av.	Sensibility to sparks and/or friction	N/Av.
Freezing point	N/Av.	Vapour density	>1 (Air = 1)
Boiling point	102°C (215.6°F)	Relative density	1.1172 kg/L (Water = 1)
Solubility	Partially soluble in water.	Partition coefficient n-octanol/water	N/Av.
Evaporation rate	> Butyl Acetate	Decomposition temperature	N/Av.
Vapour pressure	N/Av.	Viscosity	N/Av.
Percent Volatile	49.3%	Molecular mass	N/Av.
N/Av.: Not Available N/Av.: Not Applicable Und.: Undetermined N/E: Not Established			

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions (including polymerizations)	A dangerous reaction will not occur.
Conditions to avoid	Avoid heat, flame and sparks. Avoid electro-static discharge. Avoid contact with incompatible materials.
Incompatible materials	Strong bases, mineral acids, strong oxidizing agents (such as nitric acid, perchloric acid, peroxides, chlorates and perchlorates).
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Numerical measures of toxicity	1-Chloro-4-(trifluoromethyl)benzene	Ingestion	5546 mg/kg	Rat	LD50
		Inhalation	20 mg/l/4h	Mouse	LC50
			33 mg/l/4h	Rat	LC50
	n-Butyl Alcohol	Skin	>2000 mg/kg	Rabbit	LD50
		Ingestion	2510 mg/kg	Rat	LD50
		Inhalation	24.2 mg/l/4h	Rat	LC50
	Methyl Propyl Ketone	Skin	3400 mg/kg	Rabbit	LD50
		Ingestion	3730 mg/kg	Rat	LD50
			1600 mg/kg	Mouse	LD50
	Propylene glycol monomethyl ether acetate	Inhalation	11 mg/l/4h	Rat	LC50
		Skin	6472 mg/kg	Rabbit	LD50
		Ingestion	8532 mg/kg	Rat	LD50
		Inhalation	28.7 mg/l/4h	Rat	LC50
	Skin	>5000 mg/kg	Rabbit	LD50	
	Skin, eyes, inhalation, ingestion.				


Likely routes of exposure	
Delayed, immediate and chronic effects	<p>Eye contact May cause severe eye irritation or eye damage. Butyl Alcohol instilled in rabbit eyes resulted in severe corneal irritation and eye damage (OECD 405). Methyl n-propyl ketone is moderately irritating to the eyes of rabbits (OECD TG 405). 1-Chloro-4-(trifluoromethyl)benzene is not irritating in rabbits (in vivo test). Propylene glycol monomethyl ether acetate is not irritating to the eyes (rabbits, OECD GL 405).</p> <p>Skin contact May cause redness, dryness, rash and skin irritation. Prolonged and repeated contact may cause dry skin, irritation or dermatitis. Widespread contact with skin for several hours can cause harmful amounts of material to be absorbed. The data indicate that butyl alcohol is irritating to the skin (Draize test). Methyl n-propyl ketone was considered to be a slight skin irritant (guinea pig, OECD TG 404). 1-Chloro-4-(trifluoromethyl)benzene is not irritating in rabbits (in vivo test). Propylene glycol monomethyl ether acetate is not irritating to the skin (rabbits, OECD GL 404).</p> <p>Inhalation Excessive inhalation is harmful. May cause irritation to nose, throat and respiratory tract. Inhalation of vapours may cause central nervous system depression such as drowsiness, headache, dizziness, vertigo, nausea and fatigue. The severity of symptoms may vary depending on exposure conditions.</p> <p>Ingestion May be harmful if swallowed. May cause gastro-intestinal irritation with nausea and vomiting. Ingestion of large amounts may cause depression of the central nervous system characterized by headache, dizziness, convulsions and loss of consciousness.</p> <p>Respiratory or skin sensitization 1-Chloro-4-(trifluoromethyl)benzene is a skin sensitizer (mouse, OECD TG 429). May cause an allergic reaction of the skin. This product is not a respiratory sensitizer.</p> <p>IARC/NTP Classification No ingredients listed.</p> <p>Carcinogenicity Ingredients present at levels greater than or equal to 0.1% of this product are not listed as a carcinogen by IARC, ACGIH, NIOSH, NTP or OSHA.</p> <p>Mutagenicity Ingredients in this product present at levels greater than or equal to 0.1% are not known to cause mutagenic effect.</p> <p>Reproductive toxicity High vapor concentration exposure has an embryotoxic and/or foetotoxic effect on rats and rabbits at doses which may be toxic to the animals</p> <p>Specific target organ toxicity - single exposure Central nervous system, respiratory system.</p> <p>Specific target organ toxicity - repeated exposure No target organ is listed.</p>
Interactive effects	No information available for this product.
Other information	The oral and skin acute toxicity estimates (ATE) of the mixture were calculated to be greater than 2000 mg/kg. The acute toxicity estimate (ATE) by inhalation of the mixture was calculated to be greater than 20 mg/L/4h. This value is not classified according to GHS. These values are not classified according to WHMIS 2015 and OSHA HCS 2012.

12. Ecological information

Ecological toxicity	Fish - Danio rerio	LC50	3.68 mg/L; 96h [1-Chloro-4-(trifluoromethyl)benzene] OECD 203
	Fish - Danio rerio	CES0	2.2 mg/L; 72h [1-Chloro-4-(trifluoromethyl)benzene] OECD 203
	Aquatic Invertebrate - Daphnia magna	EC50	3.68 mg/L; 48h [1-Chloro-4-(trifluoromethyl)benzene] OECD 202
	Fish - Pimephales promelas [static]	LC50	1376 mg/L; 96h (n-Butyl Alcohol) OEDC 203
	Aquatic Invertebrate - Daphnia magna	EC50	1983 mg/L; 48h (n-Butyl Alcohol) OEDC 202
	Algae - Desmodesmus subspicatus	EC50	>500mg/L; 72h (n-Butyl Alcohol)
		LC50	100-180 mg/L; 96h (CAS no 108-65-6) OECD 203


	<p>Fish - Oncorhynchus mykiss - Rainbow trout</p> <p>Aquatic Invertebrate - Daphnia magna (static) LC50 >500 mg/L; 48h (CAS no 108-65-6)</p> <p>Fish - Pimephales promelas [flow-through] LC50 1224 mg/L; 96 Hr (Methyl Propyl Ketone)</p> <p>Aquatic Invertebrate - Daphnia magna EC50 >110 mg/L; 96 Hr (Methyl Propyl Ketone) OECD 202</p>
Persistence	The product contains components that may persist in the environment.
Degradability	1-Chloro-4-(trifluoromethyl)benzene is not degraded by photolysis in water. It has also showed to be not ready biodegradable, 19.2% during 28 days (OECD TG 301D). n-Butyl Alcohol is readily biodegradable. Degradation by Biochemical Oxygen Demand BOD (O ₂ consumption) was reported as 92% after 20 days. Propylene glycol monomethyl ether acetate is readily biodegradable (83% in 10 days) OECD Guideline 301 E. Methyl propyl ketone (CAS no 107-87-9) has been shown to readily biodegrade at 70% under aerobic and conditions (OCDE TG 301D).
Bioaccumulative potential	According to an estimated Bioconcentration Factors (BCF) of 110 in fish and an estimated partition coefficient log Kow of 3.6 suggest that 1-Chloro-4-(trifluoromethyl)benzene has a potential for bioaccumulation in aquatic organisms is high (TOXNET). Butyl Alcohol is soluble in water and has a low Bioconcentration Factor (BCF) of 3 and a log Kow of 0.88. BA would not be expected to accumulate in food chains. Propylene glycol monomethyl ether acetate is not expected to bioaccumulate based on a low partition coefficient (Log Kow 0.36). Methyl propyl ketone (CAS no 107-87-9) is soluble in water and has a low Bioconcentration Factor (BCF) of 3 and a log Kow of 0,93. Methyl propyl ketone is not be expected to accumulate in food chains.
Mobility in soil	The Koc value of 1600 suggest that 1-Chloro-4-(trifluoromethyl)benzene is expected to have low mobility in soil (TOXNET). n-Butyl alcohol is soluble in water. The estimated Koc value of 3.2 suggests that it is expected to have very high mobility in soil. Propylene glycol monomethyl ether acetate is soluble in water and will be distributed to air (10.22%), water (89.73%), soil (0.03%), and sediment (0.02%). Methyl propyl ketone (CAS no 107-87-9) can be volatilized from moist soil surfaces (SRC). The estimated Koc value of 75 indicates that it is expected to have high mobility in soil.
Other adverse effects	This chemical does not deplete the ozone layer.

13. Disposal considerations

	<p>Container Important! Prevent waste generation. Use in full. DO NOT dispose of residue in sewers, streams or drinking water supply. DO NOT puncture, cut, heat or burn container, even after use. Paint residues, including lacquers, stains, shellac, varnish, solvents and paint thinners, can be reprocessed (recycle) anywhere there is a recovery program. Dispose via a licensed waste disposal contractor. Observe all federal, state/provincial and municipal regulations. If necessary consult the Department of Environment or the relevant authorities.</p>
--	---

14. Transport information

UN Number	UN 1263
UN Proper Shipping Name	PAINT
Environmental hazards	This material does not contain marine pollutant.
Special precautions for user	Permit required for transportation with proper placards displayed on vehicle.
TDG - Transportation of Dangerous Goods (Canada)	

Transport hazard class(es)	 Class 3
Packing group	III
IMO/IMDG - International Maritime Transport	
Classification	UN 1263. PAINT. Class 3, PG III. Emergency schedules (EmS-No) F-E, S-E
IATA - International Air Transport Association	
Classification	UN 1263. PAINT. Class 3, PG III.
These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. In addition, if a domestic exemption exists, it is the responsibility of the shipper to define the application of it.	

15. Regulatory information

CANADA

Common name	CAS	CEPA	DSL	NDSL	NPRI
1-Chloro-4-(trifluoromethyl)benzene	98-56-6		X		
Urea, polymer with formaldehyde, butylated	68002-19-7		X		
n-Butyl Alcohol	71-36-3	X	X		X
Methyl Propyl Ketone	107-87-9		X		
Propylene glycol monomethyl ether acetate	108-65-6	X	X		X

- CEPA: List of Toxic Substances Managed Under Canadian Environmental Protection Act
- DSL: Domestic Substances List Inventory
- NDSL: Non-Domestic Substances List Inventory
- NPRI: National Pollutant Release Inventory Substances

UNITED STATE OF AMERICA

Common name	CAS	TSCA	CERCLA	EPCRA 313	EPCRA 302/304	CAA 112(b) HON	CAA 112(b) HAP	CAA 112(r)	CWA 311	CWA Priority
1-Chloro-4-(trifluoromethyl)benzene	98-56-6	X								
Urea, polymer with formaldehyde, butylated	68002-19-7	X								
n-Butyl Alcohol	71-36-3	X	X	X					X	
Methyl Propyl Ketone	107-87-9	X								
Propylene glycol monomethyl ether acetate	108-65-6	X								

Other regulations

WHMIS 1988



B2

D2B

Class B2 : Flammable Liquid

Class D2B : Toxic material causing other toxic effects

HMIS

NFPA



16. Other information

Date (YYYY-MM-DD)	GEMINI INDUSTRIES, INC. 2016-01-26
Version	01
Other information	<p>REFERENCES:</p> <ul style="list-style-type: none"> - Haz-Map, Information on Hazardous Chemicals and Occupational Diseases, http://hazmap.nlm.nih.gov/index.php - TOXNET Databases, Toxicology Data Network, NIH U.S. National Library of Medicine, http://toxnet.nlm.nih.gov/ - Service du répertoire toxicologique de la Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST), http://www.reptox.csst.qc.ca - NIOSH Pocket Guide to Chemical Hazards, Centers for Disease Control and Prevention, NIOSH Publications, 2007, http://www.cdc.gov/niosh/npg/npg.html - IPCS INCHEM, Chemical Safety Information from Intergovernmental Organizations, Canadian Centre for Occupational Health and Safety (CCOHS), Copyright International Programme on Chemical Safety (IPCS), http://www.inchem.org - OECD Existing Chemicals Database, Chemicals Screening Information DataSet (SIDS) for High Volume Chemicals, UNEP publications, http://webnet.oecd.org/HPV/UI/Search.aspx <p>ACGIH: American Conference of Governmental Industrial Hygienists AIHA: American Industrial Hygiene Association HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association OSHA: Occupational Safety and Health Administration (USA) NIOSH: National Institute for Occupational Safety and Health NTP: National Toxicology Program RSST: Règlement sur la santé et la sécurité du travail (Québec) GHS: Globally Harmonized System IARC: International Agency for Research on Cancer IDLH: Immediately Dangerous to Life or Health STEL: Short Term Exposure Limit (15 min) TWA: Time Weighted Averages WHMIS: Workplace Hazardous Materials Information System</p> <p>To the best of our knowledge, the information contained herein is accurate. However, neither Préventis System nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.</p>