



SAFETY DATA SHEET

SECTION 1 - Chemical Product and Company Information

Product Name: ACE® INTERIOR SOLVENT-BASED POLYURETHANE SATIN FINISH Product Code:AH276B114

Manufactured by:
Gemini Coatings
 2300 Holloway Drive
 El Reno, OK 73036
 800-262-5710

24- Hour Emergency (Spill, Leak, Exposure or Accident):
INFOTRAC 800-535-5053
Outside USA, Call Collect 1-352-323-3500

24- Hour Emergency HAZMAT Response and MSDS Help:
EMI 800-510-8510

Product Use: A protective and/or decorative finish or accompanying product (reference label or product data sheet for more information).

Not recommended for: Any other use not detailed on product data sheet or label.

SECTION 2 - Hazards Identification

GHS Ratings:

| | | |
|------------------------|--------------|--|
| Dermal Toxicity | Acute Tox. 1 | Dermal≤50mg/kg |
| Inhalation Toxicity | Acute Tox. 4 | Gases>2500+<=5000ppm, Vapors>10+<=20mg/l, Dusts&mists>1+<=5mg/l |
| Respiratory sensitizer | 1 | Respiratory sensitizer |
| Skin sensitizer | 1 | Skin sensitizer |
| Mutagen | 1B | Known to produce heritable mutations in human germ cells Subcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity |
| Carcinogen | 1A | Known Human Carcinogen Based on human evidence |
| Reproductive toxin | 2 | Human or animal evidence possibly with other information |
| Aspiration hazard | 1 | Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity ? 20.5 mm ² /s at 40° C. |

GHS Hazards

| | |
|------|---|
| H304 | May be fatal if swallowed and enters airways |
| H310 | Fatal in contact with skin |
| H317 | May cause an allergic skin reaction |
| H332 | Harmful if inhaled |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled |
| H340 | May cause genetic defects |
| H350 | May cause cancer |
| H361 | Suspected of damaging fertility or the unborn child |

GHS Precautions

| | |
|------|---|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray |
| P262 | Do not get in eyes, on skin, or on clothing |
| P264 | Wash any exposed skin thoroughly after handling |
| P270 | Do not eat, drink or smoke when using this product |
| P271 | Use only outdoors or in a well-ventilated area |
| P272 | Contaminated work clothing should not be allowed out of the workplace |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection |
| P281 | Use personal protective equipment as required |

| | |
|-----------|--|
| P285 | In case of inadequate ventilation wear respiratory protection |
| P310 | Immediately call a POISON CENTER or doctor/physician |
| P312 | Call a POISON CENTER or doctor/physician if you feel unwell |
| P321 | Specific treatment (see First Aid section on this label) |
| P322 | Specific measures (see First Aid section on this label) |
| P331 | Do NOT induce vomiting |
| P361 | Remove/Take off immediately all contaminated clothing |
| P363 | Wash contaminated clothing before reuse |
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician |
| P302+P350 | IF ON SKIN: Gently wash with soap and water |
| P302+P352 | IF ON SKIN: Wash with soap and water |
| P304+P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing |
| P304+P341 | IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing |
| P308+P313 | IF exposed or concerned: Get medical advice/attention |
| P333+P313 | If skin irritation or a rash occurs: Get medical advice/attention |
| P342+P311 | Call a POISON CENTER or doctor/physician |
| P405 | Store locked up |
| P501 | Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations. |

Signal Word: Danger



SECTION 3 - Composition/Information on Ingredients

| Chemical Name / CAS No. | OSHA Exposure Limits | ACGIH Exposure Limits | Other Exposure Limits |
|--|-----------------------------|------------------------------|------------------------------|
| Petroleum distillates, hydrotreated light 64742-47-8 32% | | | |
| Octamethylcyclotetrasiloxane 556-67-2 10% | | | |

| | | | |
|--|---|---|---|
| Silica, amorphous, fumed, crystalline-free 112945-52-5 4% | | | |
| Quartz 14808-60-7 0.7% | 50 µg/m ³ TWA (listed under Respirable crystalline silica) | 0.025 mg/m ³ TWA (respirable particulate matter) | NIOSH: 0.05 mg/m ³ TWA (respirable dust) |
| MINERAL SPIRITS 8052-41-3 0.3% | 500 ppm TWA; 2900 mg/m ³ TWA | 100 ppm TWA | NIOSH: 350 mg/m ³ TWA 1800 mg/m ³ Ceiling (15 min) |
| 2-Butanone, oxime 96-29-7 0.2% | | | |
| Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7 0.1% | | | |

SECTION 4 - First Aid Measures

Inhalation:

Remove exposed individual to fresh air and assist breathing if necessary. Seek medical attention.

Eye Contact:

Flush eyes with lukewarm water for 15 minutes. Seek medical attention immediately.

Skin:

Remove contaminated clothing, wash area immediately with soap and water. See physician if irritation persists.

Ingestion:

Rinse mouth out immediately. Drink 1 or 2 glasses of water to dilute. DO NOT induce vomiting. Contact physician or poison control center immediately.

SECTION 5 - Fire Fighting Measures

Alcohol Foam, CO₂, Dry Chemical

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Do not apply to hot surfaces. Never use welding or cutting torch on or near container (even empty) because product (even residue) may ignite explosively. Liquid and vapor states of this substance are dangerous fire hazards and moderate explosion hazards when exposed to heat or flame.

Oxidation may produce carbon and nitrogen oxides.

Clear fire area of unprotected personnel. Do not enter confined space without helmet, face shield, bunker coat, gloves, rubber boots and a positive pressure NIOSH-approved self-contained breathing apparatus. A water stream can scatter flames. A spray of water may be used to cool closed containers to prevent pressure buildup and possible auto ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.

Use the National Fire Protection Association Class B extinguisher.

SECTION 6 - Accidental Release Measures

Stay upwind and away from spill or leak unless wearing appropriate protective equipment. Stop and/or contain discharge if it may be done safely. Keep all sources of ignition away. Ventilate area of spill. Use non-sparking tools for clean up. Cover with inert material to reduce fumes. Keep out of drains, sewer or waterways.

If large spill occurs, alert spill response teams. Contact fire authorities. Notify local health and pollution control agencies.

SECTION 7- Handling and Storage

Handling:

Bond and ground metal containers when transferring liquid. Avoid free fall of liquid in excess of a few inches. Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact

be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this sheet must be observed.

Storage:

Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. DO NOT SMOKE in or near storage areas.

| SECTION 8 - Exposure Controls/Personal Protection | | | |
|--|---|---|---|
| Chemical Name / CAS No. | OSHA Exposure Limits | ACGIH Exposure Limits | Other Exposure Limits |
| Petroleum distillates, hydrotreated light 64742-47-8 | | | |
| Octamethylcyclotetrasiloxane 556-67-2 | | | |
| Silica, amorphous, fumed, crystalline-free 112945-52-5 | | | |
| Quartz 14808-60-7 | 50 µg/m3 TWA (listed under Respirable crystalline silica) | 0.025 mg/m3 TWA (respirable particulate matter) | NIOSH: 0.05 mg/m3 TWA (respirable dust) |
| MINERAL SPIRITS 8052-41-3 | 500 ppm TWA; 2900 mg/m3 TWA | 100 ppm TWA | NIOSH: 350 mg/m3 TWA 1800 mg/m3 Ceiling (15 min) |
| 2-Butanone, oxime 96-29-7 | | | |
| Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) 136-52-7 | | | |

Use local exhaust as required to control vapor concentrations. Avoid prolonged or repeated breathing of vapors.

Respiratory Protection:

If exposure exceeds TLV or PELs, use NIOSH approved respirator to prevent overexposure.

Skin Protection:

Required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile. An apron should be worn to avoid skin contact.

Eye Protection:

Wear splash proof goggles and face shield if there is a likelihood of contact with eyes.

Hygienic Practices

Wash hands thoroughly before eating or using the restroom. Remove contaminated clothing immediately and do not wear again until it has been properly laundered.

SECTION 9 - Physical and Chemical Properties

| | |
|---|--|
| <p>Vapor Density Heavier Than Air</p> <p>Boiling range: 175°C</p> <p>Freezing point: N/A</p> <p>Flammability: N/A</p> <p>Autoignition temperature: N/A</p> | <p>Evaporation Rate Faster than Butyl Acetate</p> <p>Melting point: N/A</p> <p>Flash point: 999°F, 999°C</p> <p>Explosive Limits: N/A</p> <p>Decomposition temperature: N/A</p> |
|---|--|

| | |
|--|--|
| Relative Density: N/A Odor threshold: N/A SPECIFIC GRAVITY 0.9375 Partition coefficient (n- N/A octanol/water): Grams VOC less water: N/A % WT. VOLATILE (VOC) 33.1521 Lbs VOC/Gallon Solids 5.0781 SOLIDS VOL% 50.9653 SPREAD @ 1 MIL 817.4838 Appearance Colored Liquid Physical State Liquid Coating VOC (g/l) 344.2353 Coating VOC (Lb/Gl) 2.8727 | Vapor Pressure N/A pH: N/A Solubility: N/A Viscosity: N/A % VOLUME VOLATILE (VOC) 39.1259 % Pig. by wt. 4.9225 VOLATILE WT% 43.1927 DENSITY (Lb/Gal) 7.8066 HAPS (lbs/gl) 0.0018 Odor N/A Material VOC (g/l) 310.1257 Material VOC (Lb/Gl) 2.5880 |
|--|--|

SECTION 10 - Stability and Reactivity

Stability: Stable under normal conditions.

Materials to Avoid: Strong oxidizing agents, strong alkalines, strong mineral acids.

Conditions to avoid: high heat, sparks, flames, static discharge.

Hazardous Decomposition: Oxidation may produce carbon and nitrogen oxides.
Hazardous polymerization will not occur.

SECTION 11 - Toxicological Information

Mixture Toxicity

Dermal Toxicity LD50: 8mg/kg
Inhalation Toxicity LC50: 15mg/L

Component Toxicity

| | |
|------------|---|
| 64742-47-8 | Petroleum distillates, hydrotreated light Oral LD50: 5,000 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Rabbit) Inhalation LC50: 5 mg/L |
| 556-67-2 | Octamethylcyclotetrasiloxane Oral LD50: 1,540 mg/kg (Rat) Dermal LD50: 794 µL/kg (Rabbit) Inhalation LC50: 36 g/m3 |
| 96-29-7 | 2-Butanone, oxime Oral LD50: 930 mg/kg (Rat) Dermal LD50: 1,000 - (Rabbit) Inhalation LC50: 5 mg/L (Rat) |
| 136-52-7 | Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1) Dermal LD50: 5,000 mg/kg (Rabbit) Inhalation LC50: 10 mg/L (Rat) |

Primary Routes of Entry: Inhalation, Skin Contact, Eyes, Ingestion

Skin:

Skin contact can cause redness, dryness or rash. Prolonged contact can cause irritation, dry skin, cracks, and dermatitis.

Ingestion:

Can cause vomiting, nausea, diarrhea, and gastrointestinal irritation.

Inhalation:

Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache possible unconsciousness and even asphyxiation. High vapor concentrations or prolonged breathing of lower concentrations may result in damage to the liver, kidneys, lungs and blood forming organs. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous

system damage.

Eyes:

Can cause irritation, redness, tearing and blurred vision.

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

| <u>CAS Number</u> | <u>Description</u> | <u>% Weight</u> | <u>Carcinogen Rating</u> |
|-------------------|--------------------|-----------------|--|
| 14808-60-7 | Quartz | 0.7% | Quartz: NIOSH: potential occupational carcinogen IARC: Human carcinogen OSHA: listed |
| 8052-41-3 | MINERAL SPIRITS | 0.3% | MINERAL SPIRITS: EU REACH: Present (P) |

SECTION 12 - Ecological Information

Ecological Information:

Uncontrolled release of the product may result in contamination of air, ground, waterways and/or sewers.

Component Ecotoxicity

| | |
|---|--|
| Petroleum distillates, hydrotreated light | LC50 96 h Pimephales promelas 45 mg/L [flow-through] (IUCLID); LC50 96 h Lepomis macrochirus 2.2 mg/L [static] (EPA); LC50 96 h Oncorhynchus mykiss 2.4 mg/L [static] (EPA) |
| Octamethylcyclotetrasiloxane | LC50 96 h Brachydanio rerio >500 mg/L (IUCLID); LC50 96 h Lepomis macrochirus >1000 mg/L (IUCLID) |
| 2-Butanone, oxime | LC50 96 h Pimephales promelas 777 - 914 mg/L [flow-through] (EPA); LC50 96 h Poecilia reticulata 760 mg/L [static] (IUCLID) EC50 48 h Daphnia magna 750 mg/L (IUCLID) EC50 72 h Desmodesmus subspicatus 83 mg/L (IUCLID) |

SECTION 13 - Disposal Considerations

Do not flush to sewer, watershed or waterway. Dispose of product in accordance with applicable local, county, state and federal regulations. See Section 8 for information on exposure control and necessary personal protective equipment.

SECTION 14 - Transportation Information

Ship according to the Department of Transportation (DOT) 49 CFR regulations.

| <u>Agency</u> | <u>Proper Shipping Name</u> | <u>UN Number</u> | <u>Packing Group</u> | <u>Hazard Class</u> |
|---------------|-----------------------------|------------------|----------------------|---------------------|
| DOT | PAINT | UN1263 | II | 3 |
| | Freight Class: 55 | | | |

SECTION 15 - Regulatory Information

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This product contains the following listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

- None

The following ingredients are listed in the TSCA Section 8(b) Inventory (Hydrated forms of chemical substances are exempt from the inventory as mixtures; the anhydrous chemical substances, however, are reportable for the inventory):

- 136-52-7 Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)
- 96-29-7 2-Butanone, oxime
- 8052-41-3 MINERAL SPIRITS
- 14808-60-7 Quartz
- 556-67-2 Octamethylcyclotetrasiloxane
- 64742-47-8 Petroleum distillates, hydrotreated light

US CAA Section 112 Hazardous Air Pollutants (HAPs) List

- None

US EPCRA (SARA Title III) Section 313 - Toxic Chemical:

- None

Hazardous Material Information System (HMIS)

| | | |
|----------------------------|--------------------------------|---|
| HEALTH | <input type="text" value="3"/> | HMIS & NFPA Hazard Rating Legend * = Chronic Health Hazard 0 = INSIGNIFICANT 1 = SLIGHT 2 = MODERATE 3 = HIGH |
| FLAMMABILITY | <input type="text" value="2"/> | |
| PHYSICAL HAZARD | <input type="text" value="0"/> | |
| PERSONAL PROTECTION | <input type="text" value="H"/> | |

SECTION 16 - Disclaimer

Date Prepared: 3/21/2023

Date revised: 2022-09-22

Reviewer Revision

THIS DOCUMENT SUPERSEDES ANY PROVISION CONTAINED IN THE FORMS, LETTERS, AND PAPERS OF YOUR COMPANY. THIS PRODUCT IS DESIGNED AND INTENDED FOR PROFESSIONAL APPLICATION ONLY. ALL PRODUCTS SHOULD BE THOROUGHLY TESTED UNDER APPLICATION CONDITIONS PRIOR TO USE. THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE RELIABLE. HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED. INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OR WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.