

PRODUCT DATA SHEET

Master's Magic Aerosol No- Halo Touch Up Lacquer

DESCRIPTION

Master's Magic No Halo Touch Up Lacquer offers the professional wood finisher, the hobbyist and the DIY-er the same high quality performance seen in our professional lacquers, in a convenient and easy to use package specifically designed for wood touch up. This product has been specially formulated for touch up in conspicuous areas to blend in perfectly without leaving a tell-tale halo around the repaired area. For wood substrates and wood touch up only. For interior use only.

Product Numbers / Sheens	PRODUCT DETAILS	ADDUCATION INSTRUCTIONS
		Application Instructions
ANHSS- SEALER	Container: 16 ounce can with a 10 ounce fill.	Surface Preparation:
ANH50 – 50 DEGREE	Backaring, Darkand 10 same to a same	Curference must be cleaned in and free from
ANH35 – RUBBED EFFECT	Packaging: Packaged 12 cans to a case, one case minimum order.	Surfaces must be clean, dry and free from any contamination; moisture content of
ANH25 – SATIN		the substrate should be lower than 9%.
ANH10 – FLAT	Dry Time: 8-15 minutes MIR Value- <1.45	Finishing over a new or aged finish will require complete cleaning and light
		sanding of the area to be touched up for
Product Advantages	Service Conditions: Color of the finish may	best results.
Phthalate Free	change over time depending upon temperature and exposure to sunlight.	Material Preparation:
Fast Dry		
 Easy Sanding 	Storage: Do Not store near or around any	Before using always shake the can
	source of heat, flames or sparks. Contents under pressure.	vigorously up and down until the agitator ball inside is loose. Once the agitator ball
No Halo Formula		is loose, swirl the can in a circular motion
	DOT Classification: Aerosols, Flammable,	and continue shaking for 1 minute.
	2.1, UN1950 (shipped as "Limited Quantity")	Sealers, Primers and low sheen products may need longer agitation.
	Read the directions on the can label before	
	using. Always read the Safety Data Sheet for this and any material before using.	Application: Ensure compatibility by testing on an
	for this and any material before using.	inconspicuous area. Always use in a well
	Shelf Life: 2 years from date of manufacture	ventilated area, that for best results is at
		least 70°F degrees (both substrate and aerosol can). Never apply aerosol near
		an open flame, or where there is a pilot
		light, as aerosols are flammable.
		Light coats are best for most touch up
		and repair applications.
		Multiple thin coats will yield the best finish
		results for new work.
	Note: These numbers represent actual control values	Clean Up: Turn can upside down and press nozzle until only propellant is
	on a smooth, sanded substrate. Spray techniques, texture, and sealing as well as film thickness may give	coming from the can.
	different results on actual work, but they may be used for comparison. To the best of our knowledge, the	
	above technical data is true and accurate at the date of issuance but is subject to change without prior	
	notice.	
March 2022	l	

March, 2023

The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABLE TOR GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER. CAUTION: DANGER! FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN! BEFORE using this product it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact the manufacturer.