



PRODUCT DATA SHEET

Aerosol White Lacquers

DESCRIPTION

Gemini's Aerosol White Lacquer series offers the professional wood finisher, the hobbyist, and the do it yourselfer the same high quality performance seen in our bulk products, but in a convenient and easy to use package. Perfect for when you need a white pigmented lacquer for touch up work. For wood substrates and wood touch up only. For interior use only.

PRODUCT NUMBERS / SHEENS	PRODUCT DETAILS	APPLICATION INSTRUCTIONS
AWPS - WHITE LACQUER SEALER AWPL60 - SEMI-GLOSS AWPL30 - SATIN	<p>Container: 16 ounce can with a 10 ounce fill.</p> <p>Packaging: Packaged 12 cans to a case, one case minimum order.</p> <p>Dry Time: 8-15 minutes MIR Value- <1.45</p> <p>Service Conditions: Color of the finish may change over time depending upon temperature and exposure to sunlight.</p> <p>Storage: Do Not store near or around any source of heat, flames or sparks. Contents under pressure.</p> <p>DOT Classification: Aerosols, Flammable, 2.1, UN1950 (shipped as "Limited Quantity")</p> <p>Read the directions on the can label before using. Always read the Safety Data Sheet for this and any material before using.</p> <p>Shelf Life: 2 years from date of manufacture</p> <p><i>Note: These numbers represent actual control values on a smooth, sanded substrate. Spray techniques, texture, and sealing as well as film thickness may give different results on actual work, but they may be used for comparison. To the best of our knowledge, the above technical data is true and accurate at the date of issuance but is subject to change without prior notice.</i></p>	<p>Surface Preparation:</p> <p>Surfaces must be clean, dry and free from any contamination; moisture content of the substrate should be lower than 9%. Finishing over a new or aged finish will require complete cleaning and light sanding of the area to be touched up for best results.</p> <p>Material Preparation:</p> <p>Before using always shake the can vigorously up and down until the agitator ball inside is loose. Once the agitator ball is loose, swirl the can in a circular motion and continue shaking for 1 minute. Sealers, primers and low sheen products may need longer agitation.</p> <p>Application:</p> <p>Ensure compatibility by testing on an inconspicuous area. Always use in a well ventilated area, that for best results is at least 70°F degrees (both substrate and aerosol can). Never apply aerosol near an open flame, or where there is a pilot light, as aerosols are flammable.</p> <p>Light coats are best for most touch up and repair applications.</p> <p>Multiple thin coats will yield the best finish results for new work.</p> <p>Clean Up: Turn can upside down and press nozzle until only propellant is coming from the can.</p>
PRODUCT ADVANTAGES		
<ul style="list-style-type: none"> ➤ Phthalate Free ➤ Fast Dry ➤ Easy Sanding 		

March, 2023

The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. **HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER. **CAUTION: DANGER! FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN!** BEFORE using this product it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact the manufacturer.